GIANT YELLOWKNIFE GOLD MINES LIMITED

CORE RECORD

HOLE No. U-B 479 | SHAFT 2

BEARING S60°E | LEVEL 425

DIP AT COLLAR -59° | LAT. 12963.32 | DEP. 7413.24 | DATE COMPLETED | PURPOSE No. 1 Shoot Third Level Definition. | WORKING B-308W

LENGTH 90.0' | ELEV. 5599 | SECTION 1100W

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	GOLD ASSAYS OZ./TON
0 - 2.0	Casing.				
2.0 - 6.0	40% qtz-carb, py, aspy, minor gry min, sp. v.g.	3972	4.0	.91	3.640
6.0 - 11.0	40% qtz-carb, py, aspy, sp. gry min.	3973	5.0	.91	4.550
11.0 - 15.0	As above.	3974	4.0	2.37	9.480
15.0 - 21.0	Qtz lenses in ser sch, local min.	3975	6.0	.19	1.140
21.0 - 26.0	As above, well banded ser sch.	3976	5.0	.23	1.150
26.0 - 29.0	40% qtz, sp, gry min, v.g.	3983	3.0	1.73	5.190
					25.150
56.0 - 61.0	40% qtz, sparing min, tr gry min & sp.	3984	5.0	.28	
61.0 - 65.5	Qtz lenses in ser sch, minor min.	3985	4.5	.08	
65.5 - 73.0	20% qtz in partly silic ser sch, local min.	3986	7.5	.08	
73.0 - 80.5	30% qtz in ser sch, py, aspy.	3987	7.5	.16	
80.5 - 90.0	Chl-ser sch.				

From	To	C.L.	Calc. Grade. Uncut	Cut.
2.0	29.0	27.0	.93	.75
56.0	61.0	5.0	.28	---
73.5	80.5	7.5	.16	---

Logged by JDB

Hole No. U-B 479