GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B702
BEARING -
DIP AT COLLAR +90
LENGTH 150.0
LAT. 11896.5
DEP. 7361
ELEV. 5758
DATE COMPLETED
PURPOSE Stope Dev.
SHAFT 2
LEVEL 250
WORKING B-210S
SECTION 150N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 1.0	Cs				
1.0 - 69.0	gry-grn chl grs sch; chl-ser sch 17.0 - 23.0, bx Fault 21.0				
69.0 - 73.5	grn-gry chl-ser sch				
73.5 - 92.0	gry-buff ser sch w qutz carb strs & lenses, 6' ground to 90.0				
92.0 - 97.0	qutz-carb lenses in ser sch, neg min	7419	5.0	.06	
97.0 - 102.0	as above; 20% qutz	7420	5.0	.06	
102.0 - 106.0	20% qutz-carb, minor min	7421	4.0	.16	
106.0 - 121.0	gry ser sch w qutz-carb lenses; neg min				
121.0 - 126.0	30% qutz-carb, py aspy	7422	5.0	.25	1.250
126.0 - 131.0	As above	7423	5.0	.38	1.900
131.0 - 136.0	50% qutz-carb & as above, v.g.	7424	5.0	.48	2.400
136.0 - 141.0	20% qutz-carb; minor min	7425	5.0	.18	.900
141.0 - 145.5	40% qutz-carb; py: aspy	7426	4.5	.46	2.070
145.5 - 150.0	30% and as above	7427	4.5	.25	1.125
					9.645

Logged by JDB

From	To	C.L.	Grade
121.0	150.0	29.0	.33

Hole No. U-B702

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-2701 | SHAFT 2
BEARING 540E | LAT. 11372.00 | DATE COMPLETED | LEVEL 100
DIP AT COLLAR -15 | DEP. 7338.50 | PURPOSE Mining | WORKING D-100E
LENGTH 107.0 | ELEV. 5688.6 | D-200 stope | SECTION 200W

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 3.0	Os				
3.0 - 35.0	grn chl grs sch; qtz- carb lenses				
35.0 - 38.5	grn-gry chl-ser sch; qtz lenses, no min,				
38.5 - 45.0	30% qtz-carb, py, [illegible],	7401	6.5	.05	4.174
45.0 - 51.0	40% qtz & as above	7402	6.0	.07	.420
51.0 - 58.0	As above; add lx 55.0 (fault)	7403	7.0	.24	1.680
58.0 - 65.0	As above	7404	7.0	.09	.630
65.0 - 72.0	30% & as above	7405	7.0	.14	.980
72.0 - 79.0	As above	7406	7.0	.08	.560
79.0 - 84.0	40% qtz & as above	7407	5.0	.25	1.250
84.0 - 87.0	As above	7408	3.0	.42	1.260
87.0 - 96.5	grn chl-ser sch				12.954
96.5 - 107.0	grn chl grs sch				

From	To	S.L.	Grade
38.5	87.0	48.5	.26

Logged by [illegible] | Hole No. U-2701

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-R 700 | SHAFT [illegible]

BEARING W60N | LAT. 12317.54 | DATE COMPLETED | LEVEL 572

DIP AT COLLAR ∠ 17½ | DEP. 2747.93 | PURPOSE Expl. | WORKING [illegible]

LENGTH 330.0 | ELEV. 2442 | SECTION 1600W

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	GOLD ASSAYS OZ./TON
0 - 57.0	f.g. grn grn sch, calc.				
57.0 - 62.0	f.g. grn-gry sch w quts lenses & sp, dress Finely band sect., i.e. 57.0 - 62.0	7395	5.0	.06	
62.0 - 115.0	grn-buff chl-ser sch, grad w above				
115.0 - 172.5	buff ser sch				
172.5 - 177.5	20% quts, minor min, tr sp & gry min	7396	5.0	.21	
177.5 - 180.5	gry-buff ser sch				
180.5 - 183.0	40% quts; tr sp & gry min	7397	2.5	.66	2.150
183.0 - 188.0	ser sch q quts lenses; minor min	7398	5.0	.32	1.100
188.0 - 195.0	as above	7399	7.0	.17	1.190
195.0 - 207.0	grn-buff ser sch				4.140
207.0 - 213.0	40% quts, sp, tr gry min & sp; water flow 213.0	7400	6.0	.57	
213.0 - 240.0	chlor ser sch, gr	7411	7.0	.04	
240.0 - 246.0	dk gry chl-ser sch; minor min	7412	6.0	.03	

Logged by [illegible] | Hole No. U-R700

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
246.0 - 250.0	gry ser sch, minor qtz & min	7413	6.0	.03	
250.0 - 253.0	50% qtz-carb, sp, gry min, v.s.	7414	3.0	(.47 (.47	
253.0 - 257.0	gry ser sch, minor qtz & min	7415	4.0	.06	
257.0 - 265.0	gry chl-ser sch				
265.0 - 270.0	30% qtz; minor min; silic,	7416	5.0	.28	
270.0 - 295.0	As above	7417	5.0	.41	
295.0 - 300.0	qtz strs in ser sch, local min	7418	5.0	.08	
300.0 - 303.0	gry ser sch				
303.0 - 330.0	gry-grn grn grz sch or chl-ser sch				

From	To	G. L.	Grade
172.5	177.5	5.0	.57
190.5	205.0	14.5	.30
250.0	253.0	3.0	.47
265.0	295.0	10.0	.34

Dip Tests

Depth	Read	Correct
150	15	14½
300	14	11½

SHEET No. 2

HOLE No. U-5703

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-D692 | SHAFT 2
BEARING S20E | LAT. 11266.27 | DATE COMPLETED | LEVEL 100
DIP AT COLLAR Hor. | DEP. 7332.39 | PURPOSE Mining (2-208) | WORKING B-102E
LENGTH 116.0 | ELEV. 5202 | SECTION 200W

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 23.0	f.g. grn sch grs w chty sp & qutz sect, hem fract.				
23.0 - 61.0	f.g. grn grs sch w qutz-calc strs, variol resid towards 61.0				
61.0 - 66.0	qutz-carb strs in ser sch, minor min	7386	5.0	.08	
66.0 - 70.5	70% qutz-carb, sparing min	7387	4.5	.38	1.710
70.5 - 76.0	30% qutz-carb, py, aspy	7391	5.5	.34	1.670
76.0 - 82.0	As above	7392	6.0	.45	2.700
82.0 - 89.0	qutz lenses in ser sch, minor min	7393	7.0	.07	6.230
89.0 - 94.0	As above (fault? 94.0)	7394	5.0	.02	
94.0 - 101.0	grn chl-ser sch				
101.0 - 116.0	dk gry-grn grs sch				

From	To	C. L.	Grade
66.0	82.0	16.0	.37

Logged by [illegible] Hole No. U-D692

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B698 | SHAFT 2

BEARING - | LAT. 12195.62 | DATE COMPLETED | LEVEL 425

DIP AT COLLAR 450 | DEP. 2499.91 | PURPOSE Mining (B-10) | WORKING 9-206 stope

LENGTH 40.0 | ELEV. 5691.67 | SECTION 4778

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 1.0	Co.				
1.0 - 8.0	20% quts in silic ser sch, py, aspy	7376	7.0	.05	
8.0 - 15.0	20% quts part 8 as above	7377	7.0	.04	
15.0 - 18.0	gry ser sch	7378	3.0	.04	
18.0 - 25.0	30% quts; py, aspy	7379	7.0	.31	0.380
25.0 - 30.0	As above	7380	5.0	.22	1.150
30.0 - 40.0	gry-blk ser sch	7381	5.0	.21	1.200
					1.030

From	To	C. I.	Grade
18.0	35.0	17.0	.30

Logged by [illegible] | Hole No. U-B698

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-5697 | SHAFT 2

BEARING N 69½° | LAT. 12197.43 | DATE COMPLETED Jan. 24, 1950 | LEVEL 485

DIP AT COLLAR 43½° | DEP. 7195.45 | PURPOSE Mining (O-P) | WORKING B-306 stope

LENGTH 85.0 | ELEV. 5481.39 | SECTION 4775N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 24.0	f.g. gry buff ser sch, qtz lenses, no min				
24.0 - 32.0	40% qtz-carb, minor min	7369	5.0	.06	
32.0 - 36.0	20% qtz; minor min	7374	7.0	.10	
36.0 - 40.0	qtz lenses in ser sch, minor min	7375	4.0	.04	
40.0 - 85.0	buff & gry ser sch q qtz lenses no sig min				

Logged by JDB | Hole No. U-5697

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-2696 | SHAFT 2

BEARING N20W | LAT. 13257.04 | DATE COMPLETED | LEVEL 575

DIP AT COLLAR Hor. | DEP. 7749.49 | PURPOSE Expl. | WORKING R-403N

LENGTH 403.0 | ELEV. 5441 | SECTION 1612N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 68.0	f.g. grn grs sch, calc strs, mottled w qtz bx 30.0 - 62.0, some sect merg w sch grs				
68.0 - 98.0	f.g. sch grs, calc. merg w grs sch				
98.0 - 132.0	buff-grn grs sch, bx tx (flow bx?); calc				
132.0 - 197.0	f.g. grn sch grs, calc, minor cp in short sect, some bx tx				
197.0 - 216.0	grey buff tuffac. sch, brtx, trs. 213.0 - 216.0	7364	3.0	.17	.510
216.0 - 220.0	70% qtz-carb, py, carp (not ore type)	7365	4.0	.20	1.200
220.0 - 225.0	qtz & py in tuffac sch	7366	5.0	.18	0.90
225.0 - 230.0	20% qtz-carb & as above	7367	5.0	.36	1.800
230.0 - 233.5	30% qtz & as above	7368	3.5	.43	1.505
233.5 - 237.5	grn tuffac sch				4.615
237.5 - 272.0	f.g. to m.g, post shear some di w chill'd cont against sch 237.5				

Logged by JEP | Hole No. U-2696

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
272.0 - 279.5	80% qutz-carb, py, sp	7370	7.5	1.60	12.000
279.5 - 283.0	80% qutz, py; po	7371	3.5	1.22	4.270
283.0 - 288.0	80% qutz-carb; py, sp	7372	5.0	.97	4.850
288.0 - 352.0	grn tuffac sch w py bands				
	t.s. 288.0 - 293.0	7373	5.0	.91	4.550
	t.s. 310.0 - 311.0	7382	1.0	.32	25.600
	t.s. 317.0 - 320.0	7383	3.0	.28	.300
	t.s. 344.0 - 349.0	7384	5.0	.06	.240
	t.s. 356.5 - 359.0	7385	2.5	.02	
	t.s. 293.0 - 298.0	7386	5.0	.14	.700
	t.s. 298.0 - 304.0	7389	6.0	.65	3.900
	t.s. 304.0 - 310.0	7390	6.0	.55	3.300
	t.s. 311.0 - 317.0	7409	6.0	.18	32.940
					1.050
	t.s. 320.0 - 334.0	7410	4.0	.05	25.000
	WaterFlow 343.0				
352.0 - 365.5	buff-grey chl-ser sch				
365.5 - 403.0	f.g. grn-buff grs sch				

From	To	S. I.	Grade
212.0	232.5	20.5	.32
272.0	317.0	45.0	.20

SHEET No. 3

HOLE No. U-7606

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-9695
BEARING N50W
DIP AT COLLAR 15.0
LENGTH [illegible]
LAT. 12132.71
DEP. 7450.79
ELEV. 5656.00
DATE COMPLETED January 22, 1950
PURPOSE Mining (C-S)
SHAFT 2
LEVEL 425
WORKING E-306 stope
SECTION 400 N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 7.5	qtz lenses in ser sch, neg min				
7.5 - 15.0	gra chl-ser sch merg w grs sch.				

Logged by JCB

Hole No. U-9695

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-3624 | SHAFT 2

BEARING N58½°W | LAT. 12122.71 | DATE COMPLETED | LEVEL 425

DIP AT COLLAR Hor. | DEP. 7450.72 | PURPOSE Mining (C-7) | WORKING B-306 stope

LENGTH 22.0 | ELEV. 5457.24 | SECTION 100N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 6.0	qtz lenses in ser sch, mag min				
6.0 - 14.0	grn chl-ser sch				
14.0 - 22.0	f.g. grn grs sch				

Logged by JDP | Hole No. U-3624

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B693
BEARING N72½ W
DIP AT COLLAR -50
LENGTH 28.0

LAT. 12177.05
DEP. 7456.18
ELEV. 5661.49

DATE COMPLETED
PURPOSE Mining (B-6)

SHAFT 2
LEVEL 425
WORKING B-306 stope
SECTION 442 N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 3.0	30% qutz, port well min	7363	3.0	.14	
3.0 - 28.0	buff & gry ser sch, no min				

Logged by [illegible]

Hole No. U-B693

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B692 | SHAFT 2

BEARING - | LAT. 12176.65 | DATE COMPLETED | LEVEL 425

DIP AT COLLAR 490 | DEP. 7460.52 | PURPOSE Mining B-5 | WORKING B-206 stope

LENGTH 47.0 | ELEV. 5667.13 | SECTION 41.5N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 1.0	Cs				
1.0 - 5.0	40% qutz-carb, py, aspy	7355	4.0	.39	1.540
5.0 - 10.5	As above	7356	5.5	.38	1.540
10.5 - 16.0	As above	7357	5.5	.40	3.200
16.0 - 22.0	60% qutz & as above, v.s.	7358	6.0	(.78 (1.06	3.550
22.0 - 27.0	30% qutz; py, aspy	7359	5.0	.67	3.350
27.0 - 33.0	40% qutz; part well min	7360	6.0	.27	1.620
33.0 - 38.5	30% qutz & as above	7361	5.5	.42	2.310
38.5 - 43.0	20% qutz; minor min	7362	4.5	.01	18.100
43.0 - 47.0	buff ser sch				

From	To	C. L.	Grade
1.0	38.5	37.5	.48

Logged by JDB

Hole No. U-B692

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B621 | SHAFT 2

BEARING N72½W | LAT. 12177.78 | DATE COMPLETED | LEVEL 125

DIP AT COLLAR 40° | DEP. 7456.35 | PURPOSE Mining B-4 | WORKING B-306 stope

LENGTH 16.0 | ELEV. ~~5664.20'~~ | SECTION 44 SW

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 3.5	50% qutz; park min w gry min and sp	7337	3.5	.26	
3.5 - 12.0	gry ser sch				
12.0 - 16.0	gry - grn chl-ser sch				

Logged by JDB

Hole No. U-B621

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B690
BEARING N53¾ W
DIP AT COLLAR -25
LENGTH 34.0
LAT. 12148.56
DEP. 7465.71
ELEV. 5656.80
DATE COMPLETED
PURPOSE Mining (1-2)
SHAFT 2
LEVEL 425
WORKING B-306 stope
SECTION 422 N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
U-B 690(-40)					
0 - 5.0	40% qutz, minor min, into muck 5.0	7331	5.0	.04	
U-B 690A (-25)					
0 - 4.0	40% qutz, minor min	7332	4.0	.01	
4.0 - 8.0	20% qutz & as above	7333	4.0	.02	
8.0 - 14.0	qutz lenses in ser sch, minor min	7334	6.0	.09	
14.0 - 22.0	gry ser sch				
22.0 - 34.0	gry chl-ser sch				

Logged by [illegible]

Hole No. U-B690A

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-2689

BEARING N65E

DIP AT COLLAR Hor.

LENGTH 266.0

LAT. 13472.79

DEP. 7436.98

ELEV. 5441.5

DATE COMPLETED

PURPOSE Sloughwise

SHAFT 2

LEVEL 575

WORKING D-407N

SECTION 1550N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	GOLD ASSAYS OZ./TON
0 - 7.5	mottled grs sch, snfl alt.				
7.5 - 95.0	m.g. dk grn grs sch; local snfl, becom gry after 58.0				
95.0 - 101.0	40% qutz-carb, py aspy, sp, v.g.	7336	6.0	(4.55 (3.61	24.480
101.0 - 107.0	qutz lenses in chl-ser sch, local min; water flow 107.0	7337	6.0	.80	4.800
107.0 - 113.0	20% qutz in two sect. local min; spack v.g.	7338	6.0	(.97 (.71	5.040
113.0 - 117.0	qutz lenses in chl-ser sch, local min	7339	4.0	.62	2.480
117.0 - 121.5	40% qutz-carb, py, aspy, sp, gry min	7340	4.5	2.19	9.855
121.5 - 127.0	70% qutz-carb, part richly min w sp, gry min & v.g.	7341	5.5	(2.39 (2.65	13.860
127.0 - 129.5	grn ser sch, minor qutz & min	7342	2.5	.09	.225
129.5 - 134.5	70% qutz-carb; richly min w sp, gry min & v.g. throughout	7343	5.0	(9.48 (7.00	41.200
134.5 - 136.5	gry ser sch, minor min	7344	2.0	1.06	2.120
					104.060
136.5 - 156.0	buff & dk. gry ser sch, part mottled w some chty tx				
156.0 - 162.5	gry ser sch w qutz lenses & minor min	7345	6.5	.07	
162.5 - 166.5	40% qutz-carb, py, aspy	7346	4.0	.64	2.560

Logged by [illegible]

Hole No. U-2689

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
166.5 - 172.5	Silic ser sch; py	7447	6.0	.05	.200
172.5 - 178.0	20% qutz in silic ser sch; py, aspy	7448	5.5	.67	3.485
178.0 - 185.0	buff, partly silic ser sch, py	7449	7.0	.08	6.545
185.0 - 220.0	buff banded ser sch, chty tx; 1" Fault bx 205.0				
220.0 - 225.0	20% qutz lenses well min aspy	7450	5.0	.40	2.000
225.0 - 230.5	50% qutz well min w aspy; v.s.	7451	5.5	(.20 (.44	3.010
230.5 - 235.5	qutz lenses in ser sch, py	7452	5.0	.17	.850
235.5 - 238.5	As above	7453	3.0	.19	.570
238.5 - 258.5	dk gch, chty & bx tx; locally impreg w py & soaked w qutz-carb (tuff); very sharp cont 258.5 (fault); t.s. 243.5 - 250.0	7454	6.5	.39	6.820
258.5 - 266.0	dense f.g. homog. diabase				

From	To	S. I.	Grade Uncut	Grade Cut
95.0	136.5	41.5	2.50	2.11
162.5	178.0	15.5	.42	--
220.0	238.5	18.5	.37	--
243.5	250.0	6.5	.39	

SHEET No. 2

HOLE No. U-2462

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8682 | SHAFT 2

BEARING N53°W | LAT. 12148.56 | DATE COMPLETED | LEVEL 425

DIP AT COLLAR 45 | DEP. 7465.71 | PURPOSE Mining | WORKING B-306 stope

LENGTH 45.0 | ELEV. 5659.0 | SECTION 423N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 7.5	Minor qutz sect. in ser sch, minor min	7325	7.5	.04	
7.5 - 13.5	20% qutz-carb lenses in silic ser sch, py aspy	7326	6.0	.06	
13.5 - 17.0	80% qutz-carb; gry min, v.g.	7327	3.5	(1.05 (.75	3.150
17.0 - 21.0	60% mosaic carb; sparing min	7328	4.0	.30	1.200
21.0 - 24.0	90% qutz-carb, heavily min w gry min & sp	7329	3.0	.34	1.020
24.0 - 31.0	70% qutz-mosaic carb, local gry min; v.g.	7330	7.0	1.00	7.000
31.0 - 45.0	qutz lenses in chl-ser sch, no min				12.370

From	To	C. L.	Grade
13.5	31.0	17.5	.70

Logged by JGB | Hole No. U-8682

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8687
BEARING N53°W
DIP AT COLLAR Hor.
LENGTH
LAT. 12148.56
DEP. 7465.71
ELEV. 5657.62
DATE COMPLETED
PURPOSE 14 Mining
SHAFT 2
LEVEL 425
WORKING 2-30% stope
SECTION 4231

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 6.0	20% qutz; minor min	7320	6.0	.03	
6.0 - 10.0	gry ser sch, neg qutz & min	7321	4.0	.20	
10.0 - 14.0	as above	7322	4.0	.05	
14.0 - 19.0	30% qutz-carb, minor min	7323	5.0	.10	
19.0 - 23.0	20% qutz & as above	7324	4.0	.02	
23.0 - 37.0	grn chl-ser sch; approach grn sch towards 37.0				

From	To	C. L.	Grade
6.0	10.0	4.0	.20

Logged by JDB

Hole No. U-8687

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8686
BEARING N60W
DIP AT COLLAR -30
LENGTH To be deepened 185

LAT. 13221.73
DEP. 7545.73
ELEV. 5522

DATE COMPLETED
PURPOSE Expl.

SHAFT 2
LEVEL 425
WORKING 8-3120
SECTION 1400W

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 21.0	f.g. grn sch grs				
21.0 - 47.0	grn chl-ser sch				
47.0 - 51.5	40% qutz, py, aspy, sp	7313	4.5	.92	4.140
51.5 - 56.0	gry ser sch	7314	6.5	.01	.065
56.0 - 63.0	40% qutz, py, aspy, sp	7315	5.0	.30	1.500
63.0 - 68.0	As above	7316	5.0	.14	.700
68.0 - 72.0	30% and as above	7317	4.0	.24	.960
72.0 - 77.0	50% qutz & as above	7318	5.0	.21	1.050
77.0 - 81.0	30% and as above	7319	4.0	.19	.760
					9.175

From	To	C. L.	Grade
47.0	81.0	34.0	.27

Logged by JOB

Hole No. U-8686

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
82.0 - 140.0	gry chl-ser sch, qtz-carb lenses				
140.0 - 157.0	finely banded ser sch (tuffac) silic 150.0 - 156.0				
157.0 - 169.5	chty sch (tuff) heavily impreg w py				
169.5 - 173.5	finely banded tuffac sch.				
173.5 - 185.0	f.g. grs sch				

SHEET No. Dragon

HOLE No. U-[illegible]

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-2685 | SHAFT 2

BEARING 360° | LAT. 13463.00 | DATE COMPLETED | LEVEL 575

DIP AT COLLAR -50 | DEP. 7437.00 700W | PURPOSE Expl. | WORKING S-4070

LENGTH 174.0 | ELEV. 5442 | SECTION 1550W

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 3.0	qutz lenses in chl-ser sch, (tuffac)				
3.0 - 46.0	gry grs sch merg throughout w chl-ser sch				
46.0 - 51.0	qutz lenses in ser sch, py	2401	5.0	.34	1.700
51.0 - 55.5	As above	2402	4.5	.12	.855
55.5 - 61.0	30% qutz-carb, py, aspy, sp, gry min	2403	5.5	1.13	6.215
61.0 - 68.0	qutz lenses in ser sch, py, aspy	2404	6/7.0	.28	2.660
68.0 - 79.0	as above	7301	8/11.0	.59	6.490
79.0 - 83.0	30% qutz-carb, py, aspy	7302	4.0	1.06	4.240
83.0 - 89.0	gry ser sch, minor qutz & min	7303	6.0	.31	1.860
89.0 - 94.0	as above	7304	5.0	.05	.250
94.0 - 99.0	qutz lenses in ser sch, local min	7305	5.0	.88	4.400
99.0 - 105.0	gry ser sch	7306	6.0	.04	.240
105.0 - 109.0	20% qutz, py, aspy	7307	4.0	1.22	4.880
109.0 - 114.0	gry ser sch	7308	5.0	.02	33.600

Logged by JDB | Hole No. U-2685

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
114.0 - 119.0	As above	7309	5.0	.08	
119.0 - 124.0	As above	7310	5.0	.01	
124.0 - 129.0	40% qutz, py, aspy, sp	7311	5.0	.63	
129.0 - 134.0	qutz lenses in ser sch, minor min	7312	5.0	.05	
134.0 - 159.5	gry chl-ser sch, calc strs,				
159.5 - 174.0	gry ser sch				

From	To	C. L.	Grade
46.0	109.0	63.0	.53
124.0	129.0	5.0	.63

SHEET No. 2

HOLE No. U-2/65

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B684 | SHAFT 2

BEARING N60W | LAT. 13231.73 | DATE COMPLETED | LEVEL 425

DIP AT COLLAR Hor. | DEP. 7545.73 | PURPOSE No. 1 Shoot Def. | WORKING B-312N

LENGTH 177.0 | ELEV. 5594.5 | SECTION 1400N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 4.0	f.g. grn grs				
4.0 - 10.5	f.g. sch grs (chl) , bx tx; 3" Fault bx 10.5				
10.5 - 11.5	20% qutz; py (No. 1 shoot appear.)	2244	1.0	.12	
11.5 - 104.0	gry chl-ser sch; grn & gran after 35.0 barren qutz-carb; strong bx Fa Fault zone 94.0 - 98.0				
104.0 - 125.0	gry grn ser sch, qutz lenses; strong 6" Fault zone 111.0 - 112.0				
	t.s. 107.5 - 108.5	2248	1.0	.08	
	t.s. 113.5 - 115.0	2249	1.5	.18	
125.0 - 127.5	40% qutz; py, minor aspy	2250	2.5	.20	
127.5 - 135.0	grn chl-ser marg w grs sch, waterflow 135.0				
135.0 - 171.0	grn chl grs sch				
171.0 - 177.0	grn sch grs w sp strs & snfl alt.				

From	To	C.L.	Grade
125.0	127.5	2.5	.20

Logged by JDB

Hole No. U-B684

GIANT YELLOWKNIFE GOLD MINES LIMITED

CORE RECORD

HOLE No. U-B683 | SHAFT 2

BEARING N60W | LAT. 12751.62 | DATE COMPLETED | LEVEL 425

DIP AT COLLAR -60 | DEP. 7578.26 219 W | PURPOSE Ore Def. | WORKING B-304N

LENGTH 36.0 | ELEV. 5588 | SECTION 1000N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 2.0	Co.				
2.0 - 36.0	Gry ser sch; t.s. 25.0 - 28.0	2243	3.0	.08	

Logged by JDB

Hole No. U-B683

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B682
BEARING 560E
DIP AT COLLAR -60
LENGTH 54.0

LAT. 12747.01
DEP. 7584.84 212W
ELEV. 5588

DATE COMPLETED
PURPOSE Ore Def.

SHAFT 2
LEVEL 425
WORKING B-304N
SECTION 1000N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 2.0	Cs.				
2.0 - 4.0	gry ser sch	2233	2.0	.04	
4.0 - 9.0	70% qutz-carb, py, aspy	2234	5.0	.83	4.150
9.0 - 14.0	40% qutz-carb w sch, py, aspy, v.g.	2235	5.0	(1.00 (1.35	5.850
14.0 - 19.0	20% qutz-carb and as above	2236	5.0	.42	2.100
19.0 - 23.0	30% qutz & as above, some heavy py	2237	4.0	.78	3.120
23.0 - 30.0	50% qutz; py, aspy, gry min	2238	7.0	.76	5.320 20.540
30.0 - 48.0	gry slaty ser sch w qutz lenses; no min				
48.0 - 51.0	30% qutz; py, aspy	2242	3.0	.25	
51.0 - 54.0	grn chl-ser sch				

From	To	C. L.	Grade
4.0	30.0	26.0	.79
48.0	51.0	3.0	.25

Logged by JDB

Hole No. U-B682

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-2681 | SHAFT 2
BEARING S60W | LAT. 13468.90 | DATE COMPLETED | LEVEL 575
DIP AT COLLAR +30 | DEP. 7437.00 700W. | PURPOSE Expl. | WORKING B-407N
LENGTH 145.0 | ELEV. 5.445 | SECTION 1550N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 6.5	grn frag sch w minor slaty sect to 1.0				
6.5 - 81.0	f.g. grn grs sch; gry w gran tx towards 81.0				
81.0 - 100.5	gry comp ser sch; water flow 83.0				
100.5 - 106.0	90% qutz; gry mis, sp, heavily loaded v.g.	2239	5.5	(20.20 (22.41 (19.50	103.500
106.0 - 111.0	Ser sch well min w gy	2240	5.0	.24	1.250
111.0 - 116.0	As above w minor qutz	2241	5.0	.13	.650
116.0 - 121.0	20% qutz, py, aspy	2245	5.0	.15	.750
121.0 - 126.0	30% qutz & as above w sp	2246	5.0	.14	.700
					106.850
126.0 - 145.0	gry ser sch t.s. 126.0 - 139.5	2247	3.5	.65	30.850

From	To	C.I.	Grade Uncut	Grade Cut
100.5	126.0	25.5	4.19	1.21
136.0	139.5	3.5	.65	--

Logged by JDS | Hole No. U-2681

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B650
BEARING S60W
DIP AT COLLAR -45
LENGTH 59.0

LAT. 12742.7
DEP. 7444.7
ELEV. 575°

DATE COMPLETED
PURPOSE No. 2 Shoot Expl.

SHAFT 2
LEVEL 250
WORKING B-202N
SECTION 925N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 1.0	Cs				
1.0 - 7.5	qutz leases in ser sch, minor min; 1" fault bx 5.0	2229	6.5	.02	
7.5 - 59.0	buff ser sch, no sig qutz or min, t.s. 47.0 - 53.0; min sect,	2230	6.0	.01	

Logged by JDP

Hole No. U-B650

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8679 | SHAFT 2
BEARING N60W | LAT. 12747.8 | DATE COMPLETED | LEVEL 250
DIP AT COLLAR -50 | DEP. 7436.3 | PURPOSE No. 2 Shoot Def. | WORKING 8-2021
LENGTH 57.0 | ELEV. 5750 | SECTION 925N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 1.0	Cs				
1.0 - 6.0	70% qutz, py, minor gry min	2213	5.0	.15	.750
6.0 - 13.0	60% qutz & as above	2214	7.0	.11	.770 .650 2.170
13.0 - 19.5	30% qutz & as above	2215	6.5	.10	
19.5 - 23.5	40% qutz & as above	2216	4.0	.53	2.120
23.5 - 29.0	70% dk qutz, py, minor sp	2217	5.5	1.93	10.615
29.0 - 35.5	30% qutz lenses, py	2218	6.5	.18	1.170
35.5 - 41.0	qutz-carb lenses in ser sch, minor min	2219	5.5	.02	13.905
41.0 - 57.0	dragf ser sch, no sig min				

From	To	C.L.	Grade
1.0	19.5	18.5	.11
19.5	35.5	16.0	.83

Logged by JDB

Hole No. U-8679

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8678 | SHAFT 2
BEARING N60W | LEVEL 575
LAT. 13347.54 | DATE COMPLETED
DIP AT COLLAR Hor. | DEP. 7717.93 | PURPOSE Expl. | WORKING B-403N
LENGTH 306.0 | ELEV. 5441 | SECTION 1600N

FOOTAGE	DESCRIPTION		SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 51.0	f.g. grn grs sch, calc					
51.0 - 85.0	f.g. grn chl sch merg w. above; calc,					
85.0 - 87.0	chl-ser sch w qutz lenses					
87.0 - 104.0	f.g. grn chl sch.					
104.0 - 123.0	grn-buff chl-ser sch					
123.0 - 193.0	gry-buff ser sch,	t.s. 137.0 - 138.0	2203	1.0	.15	
		t.s. 174.5 - 175.5	2206	1.0	.11	
		t.s. 179.0 - 180.5	2207	1.5	.22	
		t.s. 186.0 - 193.0	2208	7.0	.04	
193.0 - 197.5	ser sch w minor sect min qutz-carb		2209	4.5	.03	
197.5 - 204.5	30% qutz-carb, py, sp, tr gry min		2210	7.0	(.63 (.52	
204.5 - 209.5	Silic ser sch; py, minor qutz		2211	5.0	.01	
209.5 - 215.0	As above		2212	5.5	.04	
215.0 - 222.0	qutz lenses in ser sch, minor min		2220	7.0	.04	
222.0 - 227.0	qutz lenses in ser sch, local py, assay; 620225.0		2221	5.0	1.18	5.900

Logged by JRS | Hole No. U-8678

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
227.0 - 233.0	50% qutz-carb, sp, gry min; v.g. in 2 places, some heavy aspy min	2222	6.0	(1.66 (1.55	9.600
233.0 - 237.0	qutz-carb lenses in silic ser sch; py aspy, sp	2223	4.0	.90	3.600
237.0 - 242.0	Silic ser sch, part soaked w aspy	2224	5.0	.29	1.450
					20.550
242.0 - 272.5	gry-buff ser sch w minor min sect,				
	t.s. 250.0- 251.5	2225	1.5	.01	
	t.s. 260.5- 263.0	2226	2.5	.03	
272.5 - 277.0	60% qutz-carb, py, aspy, sptr	2227	4.5	.36	
277.0 - 284.0	grn-gry chl-ser sch; po				
284.0 - 288.5	30% qutz in 2 sect, minor min	2228	4.5	1.26	5.670
288.5 - 293.5	Silic ser sch, py; po	2231	5.0	.12	.600
293.5 - 299.0	qutz-carb lenses in ser sch; py, aspy, po	2232	5.5	.38	2.090
					8.360
299.0 - 306.0	grn chl-ser sch, po				

From	To	C. L.	Grade
197.5	204.5	7.0	.72
222.0	242.0	20.0	1.02
272.5	277.0	4.5	.36
284.0	299.0	15.0	.55

SHEET No. 2

HOLE No. U-R678

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B677 | SHAFT 2

BEARING - | LAT. 3776.0 | DATE COMPLETED | LEVEL 250

DIP AT COLLAR -90 | DEP. 7440.0 | PURPOSE No. 2 Shaft Ext. | WORKING B-2028

LENGTH 53.0 | ELEV. 5750 | SECTION 225N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 2.0	Cs				
2.0 - 8.0	80% qutz-carb, py, aspy, sp, tr gry min	2399	6.0	.81	4.860
8.0 - 14.0	90% gry qutz, sparing min	2400	6.0	.24	1.440
14.0 - 20.0	90% black qutz; sparing min	2202	6.0	.21	1.260
20.0 - 24.0	90% dk qutz; some heavy py min	2204	4.0	.57	2.280
24.0 - 26.0	qutz lenses in ser sch, minor min	2205	2.0	.02	9.840
26.0 - 53.0	grey ser sch, possible fault bx 35.0				

From	To	C. L.	Grade
2.0	4.0	22.0	.44

Logged by JDB

Hole No. U-B677

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B676
BEARING S60E
DIP AT COLLAR Hor.
LENGTH 137.0

LAT. 13468.99
DEP. ~~7437.00~~ 700W
ELEV. 5442

DATE COMPLETED
PURPOSE Expl.

SHAFT 2
LEVEL 575
WORKING B-407U
SECTION 1550W

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0-19.5	f.g. dk gry to black; local bxtx (tuffac?)				
19.5 - 61.5	f.g. very dk grn gry grs sch (?)				
61.5 - 71.5	As above, med gry				
71.5 - 87.0	gry buff chl-ser sch merg into ser sch towards 87.0				
87.0 - 101.5	bedded chty & slaty tuff, part soaked wry.				
101.5 - 107.0	60% qutz-carb, py, po	2393	2.0/5.5	.21	1.155
107.0 - 108.0	30% qutz, py; tr sp & gry min	2394	1.0	2.39	2.390
108.0 - 115.0	minor qutz lenses in ser sch, py	2395	7.0	.13	3.545
115.0 - 120.0	As above	2396	5.0	.04	
120.0 - 123.5	As above	2397	3.5	.02	
123.5 - 127.0	20% qutz, minor min	2398	3.5	.26	
127.0 - 137.0	buff ser sch				

From	To	S. L.	Grade
101.5	108.0	6.5	.54
123.5	127.0	3.5	.26

Logged by JOB

Hole No. U-B676

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B675
BEARING N60W
DIP AT COLLAR Hor.
LENGTH 90°

LAT. 13474.70
DEP. ~~7426.96~~ 712W.
ELEV. 5442

DATE COMPLETED
PURPOSE Expl.

SHAFT 2
LEVEL 575
WORKING B-407N
SECTION 1550N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 15.5	f.g. chty & frag tuff; heavily min w py to 9.0; also po				
	t.s. 0 - 5.0	2384	5.0	.01	
	5.0 - 9.0	2385	4.0	.02	
15.5 - 90.0	mass m.g. ep grs; srfl alt, intr (?); mottled tx.				

Logged by JDB

Hole No. U-B675

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B674
BEARING N60W
DIP AT COLLAR 45
LENGTH 51.0
LAT. 13223.57
DEP. 7462.14 556 W
ELEV. 5445
DATE COMPLETED
PURPOSE No. 1 Shoot Def.
SHAFT 2
LEVEL 575
WORKING B-408S
SECTION 1350N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 8.5	f.g. grs sch merg w chl-ser sch				
8.5 - 12.5	f.g. chl-ser sch				
12.5 - 18.0	20% qutz lenses, py, aspy	2386	5.5	.27	
18.0 - 23.5	10% qutz & as above	2387	5.5	.09	
23.5 - 51.0	gry chl-ser sch				

From	To	C.L.	Grade
12.5	18.0	5.5	.27

Logged by JDB

Hole No. U-B674

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B673
BEARING N60W
DIP AT COLLAR 45
LENGTH 63.0

LAT. 13134.73
DEP. 7415.79 55W
ELEV. 5445

DATE COMPLETED
PURPOSE No. 1 Shoot Def.

SHAFT 2
LEVEL 575
WORKING B-4085
SECTION 1250N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 21.5	grn-gry grs sch merg into chl-ser sch by 2.0				
21.5 - 26.0	20% qutz lenses, part well min waspy; tr gry min & sp	2380	4.5	1.07	
26.0 - 27.5	minor blue qutz in ser sch	2381	1.5	.05	
27.5 - 36.5	gry chl-ser sch				
36.5 - 39.5	py in ser sch	2382	3.0	.01	
39.5 - 46.5	qutz lenses in ser sch heav min w py	2383	7.0	.03	
46.5 - 50.0	grn-gry ser sch				
50.0 - 63.0	grn-gry chl-ser sch				

From	To	C.L.	Grade
21.5	26.0	4.5	1.07

Logged by JDB

Hole No. U-B673

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B672
BEARING S72 - 37E
DIP AT COLLAR +51°
LENGTH 53.0

LAT. 12063.08
DEP. 7433.39
ELEV. ~~5276.54~~ 2

DATE COMPLETED
PURPOSE Mining

SHAFT 2
LEVEL 425
WORKING B-306 Stope
SECTION 330N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 1.0	Cs				
1.0 - 6.0	20% qutz-carb, minor min	2377	5.0	.09	
6.0 - 10.0	As above	2378	4.0	.32	
10.0 - 17.0	qutz-carb lenses in ser sch neg min	2379	7.0	.04	
17.0 - 24.0	qutz lenses in ser sch, minor min	2388	7.0	.10	
24.0 - 27.5	As above	2389	3.5	.01	
27.5 - 33.0	60% qutz-carb, aspy tr gry min & spy v.g.	2390	5.5	(1.42 (1.55	8.195
33.0 - 36.5	20% qutz intere w silic ser sch, py, aspy; tr gry min & v.g.	2391	3.5	(.34 (.20	.945 9.140
36.5 - 43.0	gry-buff ser sch, neg qutz & min				
43.0 - 46.5	20% qutz-carb; py aspy, v.g.	2392	3.5	(.28 (.20	
46.5 - 53.0	gry ser sch; chl togards 53.0				

From	To	C.L.	Grade
6.0	10.0	4.0	.32
27.5	36.5	9.0	1.01
43.5	46.5	3.5	.24

.3

Logged by JDB

Hole No. U-B672

N.M.P.-F3742-3

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B671
BEARING N60W
DIP AT COLLAR + 45
LENGTH 82.0

LAT. 13091.16
DEP. 7391.26
ELEV. 5445

DATE COMPLETED
PURPOSE No. 1 Shoot Def.

SHAFT 2
LEVEL 575
WORKING B-408S
SECTION 1200N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLDS ASSAYS OZ./TON	OZ./TON
0 - 11.0	f.g. gry grs sch grad w chl- ser sch				
11.0 - 24.5	chl-ser sch, gry t.s. 18.0 - 20.0	2370	2.0	.20	
24.5 - 29.5	gry ser sch				
29.5 - 34.5	qutz-carb lenses in ser sch, minor min	2371	5.0	.44	2.200
34.5 - 39.0	60% qutz-carb, sparing min	2372	4.5	.49	2.205
39.0 - 41.0	gry ser sch				4.405
41.0 - 55.5	grn-gry chl-ser sch				
55.5 - 66.0	f.g. grs sch				
66.0 - 82.0	f.g. gry chl-ser sch; local py				

From	To	C.L.	Grade
18.0	20.0	2.0	.20
29.5	39.0	9.5	.46

LOGGED BY JDB

HOLE No. U-B671

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B670
BEARING S72 - 37E
DIP AT COLLAR -35
LENGTH 35.0

LAT. 12064.15
DEP. 7431.03
ELEV. 5668.64

DATE COMPLETED
PURPOSE Mining

SHAFT 2
LEVEL 425
WORKING B-306 stope
SECTION 330N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 5.0	20% qutz; minor	2368	5.0	.10	
5.0 - 9.5	As above	2373	4.5	.22	
9.5 - 14.0	60% qutz-carb., py, aspy	2374	4.5	.10	
14.0 - 19.5	50% & as above	2375	4.5	.37	
19.5 - 28.0	20% qutz-carb; minor min	2376	7.5/8.5	.05	
28.0 - 35.0	f.g. grn ser sch				

From	To.	C. L.	Grade
5.0	9.5	4.5	.22
14.0	19.5	4.5	.37

Logged by JDB

Hole No. U-B670

N.M.P.-F3742-3

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B669
BEARING -
DIP AT COLLAR +90
LENGTH 111.0

LAT. 13089.0
DEP. 7395.0
ELEV. 5446.5

DATE COMPLETED
PURPOSE No. 1 Shoot Def.

SHAFT 2
LEVEL 575
WORKING B-408S
SECTION 1200N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLDS ASSAYS OZ./TON	GOLDS ASSAYS OZ./TON
0 - 1.0	cs				
1.0 - 24.5	gry grs sch w tan lent alt fl merg w chl-ser sch, t.s. 2.5 - 7.5	2360	5.0	.40	
24.5 - 31.5	qutz in dk gry ser sch, minor py	2361	7.0	.26	1.820
31.5 - 36.0	40% qutz; sparing min; v.g.	2362	4.5	.88) 1.17)	9.090
36.0 - 42.0	30% qutz; py	2363	6.0	1.16) 1.13)	6.840
42.0 - 49.5	80% dk qutz; sparing min, consid. v.g. throughout	2264	7.5	7.23) 7.94)	61.275
49.5 - 83.0	buff ser sch; t.s. sect w py (tuffac?) 64.0 - 69.0	2369	5.0	9.35)	79.025
83.0 - 111.0	dk gry-buff ser sch				

From	To	C.L.	Grade
24.5	49.5	25.0	3.16

LOGGED BY JDB

HOLE No. U-B669

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B668
BEARING S72-37E
DIP AT COLLAR Hor.
LENGTH 38.0

LAT. 12063.79
DEP. 7431.78
ELEV. 5670.94

DATE COMPLETED
PURPOSE Mining

SHAFT 2
LEVEL 425
WORKING B-306 stope
SECTION 330N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 2.0	20% qutz; neg min	2365	2.0	.24	
2.0 - 21.5	gry-grn ser sch w qutz strs & lenses t.s. 11.0 - 16.0	2366	5.0	.16	
21.5 - 28.0	40% qutz-carb, py aspy	2367	6.5	.21	
28.0 - 38.0	grn chl-ser sch				

From	To	C. L.	Grade
0	2.0	2.0	.24
11.0	16.0	5.0	.16
21.5	28.0	6.5	.21

Logged by JDB

Hole No. U-B668

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON

From	To	C.L.	Grade
1.0	20.5	19.5	.37
42.5	56.0	13.5	.26
67.0	73.5	6.5	.26

SHEET No. JDB

HOLE No. U-8667

N.M.P.-F3742-3

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B667
BEARING N60W
DIP AT COLLAR -71
LENGTH 84.0

LAT. 12062.5
DEP. 7469.5
ELEV. 5749

DATE COMPLETED
PURPOSE ~~B-306 Stope~~ def.

SHAFT 2
LEVEL 250
WORKING B-209E
SECTION 350W

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLDS ASSAYS OZ./TON	OZ./TON
0 - 1.0	Cs.				
1.0 - 8.0	20% qutz, minor min	2299	7.0	.14	.980
8.0 - 14.0	As above; tr gry min	2300	6.0	.86	5.160
14.0 - 20.5	Ser sch, minor qutz & neg min	2351	6.5	.19	1.235
20.5 - 25.0	As above, minor min	2352	4.5	.02	7.375
25.0 - 30.0	As above	2353	5.0	.04	
30.0 - 36.0	20% qutz-carb, minor min	2354	6.0	.06	
36.0 - 42.5	As above, part silicif	2355	6.5	.07	
42.5 - 46.5	30% qutz; py aspy	2356	4.0	.28	1.120
46.5 - 52.0	As above	2357	5.5	.12	.660
52.0 - 56.0	50% zutz & as above	2358	4.0	.45	1.800
56.0 - 67.0	dk chl-ser sch, neg qutz				3.580
67.0 - 73.5	40% qutz-carb, minor min	2359	6.5	.26	
73.5 - 84.0	dk gry chl-ser sch, minor qutz-carb				

LOGGED BY JDB

HOLE No. U-B667

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
176.0 - 228.0	gry & buff ser sch, becom gry and comp towards 228.0				
228.0 - 237.0	gry comp chl-ser sch becom grn towards 237.0				
237.0 - 252.5	f.g. gry-grn grs sch. calc.				
252.5 - 342.0	f.g. grn grs, ep threads, possible p.l. becom sch after 328.0				

From	To	C.L.	Grade
144.0	173.0	29.0	.48

Dip Tests

Depth	Read	Correct	
150	73	70	67
300	67	63	59½

SHEET No. 2

HOLE No. U-B666

N.M P.-F3742-3

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B666
BEARING S60E
DIP AT COLLAR -75
LENGTH 342.0

LAT. 13342.96
DEP. 7755.91
ELEV. 5436.5

DATE COMPLETED
PURPOSE - Lower orebody
Expl.

SHAFT 2
LEVEL 575
WORKING B-403N
SECTION 1600N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLDS ASSAYS OZ./TON	OZ./TON
0 - 2.0	cs.				
2.0 - 64.0	f.g. sch grs. calc., epstrs., hem fract. bxtx 36.0 - 64.0, dk fl, becom gry towards 64.0				
64.0 - 69.0	grad int grs sch.				
69.0 - 84.5	gry-buff chl-ser sch, grad into ser sch,				
84.5 - 104.0	buff ser sch, some mot bx tx.,				
104.0 - 113.0	dk chl-ser sch				
113.0 - 144.0	gry-buff ser sch w qutz lenses & carb				
1440 - 148.0	30% qutz carb, sparing min	2292	4.0	.43	1.720
148.0 - 153.0	as above	2293	5.0	.32	1.600
153.0 - 158.0	40% qutz-carb & as above	2294	5.0	.94	4.700
158.0 - 163.0	30% & as above	2295	5.0	.38	1.900
163.0 - 168.0	As above	2296	5.0	.46	2.300
168.0 - 173.0	As above	2297	3/5.0	.39	1.950
173.0 - 176.0	buff ser sch. minor min	2298	3.0	.07	14.170

LOGGED BY JDB

HOLE No. U-B666

N.M.P.-F3742-3

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B665 | SHAFT 2

BEARING N60W | LAT. 12062.5 | DATE COMPLETED | LEVEL 250

DIP AT COLLAR -45 | DEP. 7469.5 | PURPOSE B-306 stope | WORKING B-209E

LENGTH 94.0 | ELEV. 5749 | Def. | SECTION 350N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLDS ASSAYS OZ./TON	OZ./TON
0 - 2.0	Cs				
2.0 - 4.0	40% qutz, minor min	2281	2.0	.15	
4.0 - 13.0	grn-buff ser sch, minor qutz				
13.0 - 15.0	qutz lenses in ser sch, minor min	2282	2.0	.05	
15.0 - 20.0	60% qutz-carb; aspy; speck v.g.	2283	5.0	.84) .63)	3.650
20.0 - 25.0	As above	2284	5.0	.33	1.650
25.0 - 31.0	As above, speck v.g.	2285	6.0	1.57) 1.69)	9.780
31.0 - 38.0	As above, speck v.g.	2286	7.0	1.69	11.830
38.0 - 43.0	Ser sch, qutz strs, local min	2287	5.0	.09	.450
43.0 - 48.5	As above	2288	5.5	.05	.275
48.5 - 55.0	30% qutz, py, aspy	2289	5.5/6.5	.46	2.990
55.0 - 62.0	70% qutz-carb, py, aspy, gry min, sp, v.g.	2290	7.0	2.88) 2.66)	19.390
62.0 - 64.0	qutz lenses in ser sch; minor min	2291	2.0	.25	.500
64.0 - 73.0	dk chl-ser sch				50.515

LOGGED BY JDB

HOLE No. U-B665

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
73.0 - 87.0	grn chl sch				
87.0 - 94.0	Lt gtn grs sch				

From	To	C.L.	Grade
15.0	64.0	49.0	1.03

SHEET No. JDB

HOLE No. U-B665

N.M.P.-F3742-3

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B664 | SHAFT 2

BEARING N60W | LAT. 13347.54 | DATE COMPLETED | LEVEL 575

DIP AT COLLAR -61 | DEP. 7747.93 | PURPOSE Lower Orebody | WORKING B-403N

LENGTH ~~294.0~~ 391 | ELEV. | Expl. | SECTION 1600N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLDS ASSAYS OZ./TON	OZ./TON
0 - 2.0	Cs.				
2.0 - 20.0	f.g. dk grn grs sch; chty bx tx				
20.0 - 141.0	f.g. - m.g. grs sch, calc strs, becom gry towards 141.0				
141.0 - 258.5	gry-buff ser sch w chty bx tx, increas carb. after 146.0				
	t.s. 186.5 - 188.0	2266	1.5	.49	
	t.s. 202.0 - 205.0	2267	3.0	.29	
	t.s. 209.5 - 212.0	2268	2.5	.04	
258.5 - 262.5	30% qutz in partly silic ser sch py, aspy	2269	4.0	.25	1.000
262.5 - 266.0	60% qutz carb & as above, tr gry min	2270	3.5	.64	2.240
					3.240
266.0 - 285.0	gry chl-ser sch; t.s. 281.0 - 283.5	2271	2.5	.88	
285.0 - 294.0	chl-ser schw tan lent alt Fl., merg w grs sch, t.s. 290 - 291.0	2272	1.0	.22	

From	To	C.L.	Grade
186.5	188.0	1.5	.49
202.0	205.0	3.0	.29
258.5	266.0	7.5	.43
281.0	283.5	2.5	.88
290.0	291.0	1.0	.22

LOGGED BY JDB

HOLE No. U-B664

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
294.0-297.5	ground 3.5'				
297.5-325.5	dk grn grs sch w tan lent alt fl				
325.5-331.0	gry to buff ser sch w qutz-carb lenses min w py, aspy	10425	5.5	1.27	6.985
331.0-334.5	qutz-carb lens in gry ser sch min w py, aspy	10426	3.5	.56	1.960
334.5-337.5	gry chl-ser sch w qutz-carb lenses min w py, aspy	10427	3.0	1.56	4.680
			12.0		13.625
337.5-351.5	dk grn chl-ser w tan lent alt fl merg w grs sch: t.s. 320.5-335.5	10428	5.0	.01	
	t.s. 337.5-342.0	10429	4.5	.02	
351.5-355.0	20% qutz-carb lenses in chl-ser sch w tan lent alt fl min w py, aspy	10430	3.5	.07	
355.0-360.0	20% qutz min w py, aspy	10431	5.0	1.36	6.800
360.0-365.0	70% qutz min w py, aspy	10432	5.0	1.71	8.550
365.0-369.0	40% qutz min w py, aspy	10433	4.0	.25	1.000
			14.0		16.350
369.0-378.0	grn chl-ser sch w tan alt fl merg w grs sch t.s. 369.0-370.0	10434	1.0	.02	
378.0-391.0	mg dk grn grs sch min w py, from 329.0-360.5	10434	1.5	.02	

Acid Test

Depth	Read	Correct.
300	-41.99	32.89
390	-36.58	29.99

From	To	Cl	Grade
325.5	337.5	12.0	1.14
355.0	369.0	14.0	1.17

SHEET No. deadlined

HOLE No. U-8 664

N.M.P.-F3742-3

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B 663
BEARING ∠ 90
DIP AT COLLAR 106.0
LENGTH

LAT. 13132.5
DEP. 7419.5 597W
ELEV. 5446.7

DATE COMPLETED
PURPOSE No. 1 Shoot Def.

SHAFT 2
LEVEL 575
WORKING B-408S
SECTION 1250N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLDS ASSAYS OZ./TON	OZ./TON
0 - 1.0	Cs.				
1.0 - 11.0	dk gry chl-ser sch merg w grs sch				
11.0 - 16.5	ser sch w qutz lenses & minor min	6978	5.5	.03	
16.5 - 26.0	dk gry chl-ser sch				
26.0 - 31.0	qutz lenses in ser sch, py	6979	5.0	.26	1.300
31.0 - 36.0	20% qutz, py, aspy	6980	5.0	.12	.600
36.0 - 41.0	30% qutz & as above	6981	5.0	.24	1.200
41.0 - 46.0	40% qutz & as above	6982	5.0	.40	2.000
46.0 - 49.5	As above	6983	3.5	.53	1.855
					6.955
49.5 - 76.0	gry ser sch, minor qutz & Min	6987	4.0	.31	1.240
76.0 - 80.0	70% qutz-carb. minor min				
80.0 - 85.0	30% qutz-carb, local min	6988	5.0	.18	.900
					2.180
85.0 - 106.0	gry chl-ser sch, fault (HZO) (carb) 101.0				

From	To	C. L.	Grade
26.0	49.5	23.5	.29
76.0	85.0	9.0	.24

LOGGED BY J. D. B.

HOLE No. U-B 663

N.M P.-F3742-3

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B662
BEARING S60E
DIP AT COLLAR -60
LENGTH 408.0

LAT. 13342.96
DEP. 7755.91
ELEV. 5436

DATE COMPLETED
PURPOSE Lower Orebody

SHAFT 2
LEVEL 575
WORKING B-403N
SECTION 1600N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLDS ASSAYS OZ./TON	OZ./TON
0 - 2.0	Cs.				
2.0 - 52.0	f.g. grn sch grs, hem fract, ep threads				
52.0 - 78.0	as above merging into grs sch,				
78.0 - 89.5	gry-buff chl-ser schw qutz lenses, chiefly ser'c				
89.5 - 180.0	grn-gry chl-ser sch, merg w grs sch; merg into ser sch at 180.0				
180.0 - 194.0	gry ser sch				
194.0 - 201.0	20% mosaic bx qutz, tr sp & gry min, py	6984	7.0	.25	1.750
201.0 - 207.0	30% qutz & as above, aspy; tr sp & gry min	6985	6.0	.63	3.780
207.0 - 213.0	40% & as above	6986	5/6.0	.50	3.000
213.0 - 218.0	30% qutz, py, aspy	6989	5.0	.41	2.050
					10.580
218.0 - 280.0	gry ser sch				
280.0 - 285.0	qutz lenses; py, aspy	6990	5.0	.45	2.250
285.0 - 290.0	20% qutz, py, aspy	6991	5.0	1.26	6.300
290.0 - 296.0	20% qutz, py, aspy	6992	6.0	.28	1.680

LOGGED BY JDB

HOLE No. U-B662

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
296.0 - 301.0	50% qutz & as above, tr gry min	6993	5.0	.91	4.550
301.0 - 303.5	As above; tr gry min	6994	2.5	.96	2.400
303.5 - 308.5	qutz lenses in ser sch, py, aspy	6995	5.0	.29	1.450
308.5 - 312.5	as above	2258	4.0	.08	.320
312.5 - 319.0	30% qutz-carb, py, aspy	2259	6.5	1.17	7.605
319.0 - 325.0	20% qutz & as above	2260	6.0	.43	2.580
325.0 - 329.0	gry-buff ser sch	2273	4.0	.04	29.135
					.160
329.0 - 337.0	20% qutz lenses in ser sch, py, aspy	2274	6/8.0	.28	2.240
337.0 - 350.0	gry buff ser sch, no min				31.535
350.0 - 357.0	qutz lenses in ser sch, minor min	2275	7.0	.43	3.010
357.0 - 364.0	50% qutz carb, py, aspy, tr sp	2276	7.0	1.24	8.680
364.0 - 371.0	as above, speck v.g.	2277	7.0	1.06)	
				)	
371.0 - 379.0	40% qutz & as above	2278	7/8.0	1.01)	
379.0 - 387.0	30% qutz & as above	2279	7/8.0	1.52	12.160
		2280	4.0	.16	1.280
391.0 - 396.0	dk buff gry chl-ser sch			.28	1.120
					33.480
396.0 - 408.0	f.g. grn grs sch				

From	To	C. L.	Grade
194.0	218.0	24.0	.44
280.0	337.0	57.0	.55
350.0	391.0	41.0	.81

SHEET No. 2

HOLE No. U-B662

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON

Dip Tests

Depth	Read	Correct	
150	58	54	49½
300	52	47½	43½

SHEET No. 3

HOLE No. I-B662

N.M.P.-F3742-3

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B661
BEARING --
DIP AT COLLAR -90
LENGTH 142.0

LAT. 13164.5
DEP. 7665.5
ELEV. 5437

DATE COMPLETED 500 Ret. / 150E
PURPOSE Lower orebody def.

SHAFT 2
LEVEL 575
WORKING B-406W
SECTION 1400N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLDS ASSAYS OZ./TON	OZ./TON
0 - 2.0	Cs				
2.0 - 18.5	buff ser sch chty bx tx				
18.5 - 24.0	20% qutz lenses, minor min	6976	5.5	.05	
24.0 - 38.0	buff ser sch				
38.0 - 66.0	dk gry chl-ser sch				
66.0 - 71.0	20% qutz lenses, minor min	6977	5.0	.16	
71.0 - 76.0	As above	6996	5.0	.01	
76.0 - 82.5	qutz lenses in ser sch & as above	6997	6.5	.11	
82.5 - 89.5	As above	6998	7.0	.01	
89.5 - 94.0	As above	6998	4.5	.01	
94.0 - 101.0	As above, less min	7000	7.0	.05	
101.0 - 108.0	As above	2251	7.0	.03	
108.0 - 115.0	As above	2252	7.0	.09	
115.0 - 119.0	50% qutz-carb, gry min, sp, v.g.	2253	4.0	.55) .53)	2.160

LOGGED BY JDB

HOLE No. U-B 661

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
119.0 - 122.0	30% qutz, py aspy	2254	3.0	.97	2.910
122.0 - 126.0	70% qutz-carb, richly min w sp	2255	4.0	1.49) .97)	4.920
126.0 - 132.0	30% qutz-carb, py aspy	2256	6.0	1.68	10.080
132.0 - 135.5	As above	2257	3.5	2.23	7.805
					27.875
135.5 - 142.0	dk gry chl-ser sch.				

From	To	C.L.	Grade
115.0	135.5	20.5	1.36

SHEET No. 2

HOLE No. U-B661

N.M.P.-F3742-3

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-3660

BEARING -

DIP AT COLLAR -90

LENGTH 271.0

LAT. 13344.5

DEP. 7752

ELEV. 5437

DATE COMPLETED

PURPOSE ~~Lower Orebody~~ Expl.

SHAFT 2

LEVEL 575

WORKING B-405N

SECTION 1600N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLDS ASSAYS OZ./TON	OZ./TON
0 - 2.0	Os.				
2.0 - 68.0	f.g. grn grs sch, qutz-carb lenses				
68.0 - 104.0	dense comp gry-buff chl-ser sch, (ser sch 80.5 - 87.5)				
104.0 - 127.5	comp buff ser sch, minor qutz lenses & local min, t.s. 105.0 - 110.0	6965	5.0	.24	
119.0 - 124.5	t.s.	6966	5.5	.21 .43	2.365
127.5 -133.0	Ser sch w minor qutz & scat py	6973	5.5		
133.0 - 138.5	As above	6967	5.5	.54	2.970
138.5 - 142.0	As above	6968	5.5	1.50	7.250 10.535
142.0 - 160.0	gry-buff ser sch, minor qutz- carb & min t.s. 150.0 - 152.0	6969	2.0	.27	
160.0 - 206.5	buff comp ser sch. chty tx (tuff)				
206.5 - 224.0	f.g. dense comp gry chl-ser sch, could be f.g. basic dike.				
224.0 - 271.0	f.g. sch gr; varied towards 271.0				

LOGGED BY JDP

HOLE No. U-3660

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
	Additional t.s.				
	103.5 - 105.0	6970	1.5	.07	
	110.0 - 114.5	6971	4.5	.01	
	114.5 - 119.0	6972	4.5	.07	
	119.0 - 124.5	6973	5.5	.21	
	124.5 - 127.5	6974	3.0	.06	
	142.0 - 145.0	6975	3.0	--	

From	To	C. I.	Grade
105.0	110.0	5.0	.24
119.0	124.5	5.5	.21
127.5	142.0	14.5	.73
150.0	152.0	2.0	.27

SHEET No. 3

HOLE No. U-2460

N.M P.-F3742-3

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8659

BEARING -

DIP AT COLLAR -90

LENGTH 230.0

LAT. 13175.5

DEP. 7444.5

ELEV. 5438

DATE COMPLETED

PURPOSE Expl. Tunnel

Ore body

SHAFT 2

LEVEL 575

WORKING B-4055

SECTION 1300W

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLDS ASSAYS OZ./TON	OZ./TON
0-2.0	Os.				
2.0 - 95.0	m.g. grn grs sch, local snfl.,				
95.0 - 107.0	chl schv quts & carb lenses, minor py				
107.0 - 198.5	mass m.g.- c.g. grs, p & s sm tn, snflalt, some allig fst, minor quts-carb 151.0-152.0				
198.5 - 230.0	dk grn grs sch w tan lent alt fl.				

LOGGED BY [illegible]

HOLE No. U-8659

N.M.P.-F3742-3

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B658

BEARING ---

DIP AT COLLAR -90

LENGTH 186.0

LAT. 13189

DEP. 7622

ELEV. 5437

DATE COMPLETED 500 Ref. T100E

PURPOSE Lower Orebody

Def.

SHAFT 2

LEVEL 575

WORKING B-406W

SECTION 1400N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLDS ASSAYS OZ./TON	OZ./TON
0 - 2.0	Cs.				
2.0 - 21.0	gry-grn chl-ser sch w qutz lenses				
21.0 - 27.0	60% qutz-carb, no min				
27.0 - 67.5	buff compact ser sch, some chty tx	6951	6.0	.01	
67.5 - 71.5	ser sch w qutz lenses min w py	6952	4.0	.15	
71.5 - 77.0	As above, more min	6953	5.5	.07	
77.0 - 83.0	As above	6954	6.0	.12	
83.0 - 97.0	gry ser sch, minor qutz & min				
97.0 - 102.0	20% qutz lenses, py, tr sp & gry min	6955	5.0	.15	.750
102.0 - 107.0	30% qutz & as above	6956	5.0	1.52	7.600
107.0 - 112.0	40% qutz-carb & as above	6957	5.0	1.55	7.750
112.0 - 117.0	30% & as above	6958	5.0	1.88	9.400
117.0 - 122.0	20% & as above	6959	5.0	1.78	8.900
122.0 - 125.0	60% qutz, sparing min	6960	3.0	2.13	6.390

LOGGED BY JDB

HOLE No. U-B 658

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
125.0 - 130.0	90% qutz richly min w sp & gry min, v.g.	6961	5.0	1.58) 1.73)	8.250
130.0 - 135.0	As above	6962	5.0	1.14) 1.35)	6.200
135.0 - 139.0	As above, V.G.	6963	4.0	2.51) 2.04)	9.080
139.0 - 144.0	As above; V.g.	6964	5.0	2.94) 3.10)	15.100
deepen					
144.0 - 148.0	70% qutz; aspy, sp, tr gry min, V.g.(?)	2261	4.0	1.28) 1.44)	5.440
148.0 - 153.0	20% qutz lenses well min w py; aspy	2262	5.0	2.11	10.550
153.0 - 158.0	As above	2263	5.0	2.76	13.800
153.0 - 163.0	30% qutz & as above	2264	5.0	3.02	15.100
163.0 - 168.0	70% qutz; part sparing min, sp	2265	5.0	1.83	9.150
168.0 - 186.0	Comp gry-buff ser sch				133.460

From	To	C.L.	Grade
97.0	168.0	71.0	1.88

SHEET No. 2

HOLE No. U-B 658

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B 657
BEARING --
DIP AT COLLAR -90
LENGTH 155.0

LAT. 12313.5
DEP. 7578.5450
ELEV. 5437

DATE COMPLETED
PURPOSE Lower Fourth
Ore Def.

SHAFT 2
LEVEL 575
WORKING B-4062
SECTION 1400N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 2.0	Cs.				
2.0 - 4.0	grn grs sch				
4.0 - 77.0	gry-grn comp chl-ser schw chty bx sect suggest tuff				
77.0 - 80.5	gry ser sch				
80.5 - 84.0	ser sch w minor gutz	6938	3.5	.08	
84.0 - 91.0	30% gutz, minor min	6939	7.0	.46	3.220
91.0 - 96.0	gutz lenses in ser sch, py, minor aspy	6940	5.0	.63	3.156
96.0 - 100.0	as above	6941	4.0	.05	.200
100.0 - 105.0	30% gutz-carb, py, minor aspy	6942	5.0	.62	3.100
105.0 - 112.0	60% and as above; mostly carb, sparing min	6943	7.0	.84	5.880
112.0 - 117.0	30% and as above	6944	5.0	.48	2.400
117.0 - 121.0	40% and as above	6945	4.0	.22	.880
121.0 - 126.5	dk gry ser sch, py	6946	5.5	.40	2.200
					21.030
126.5 - 155.0	dk gry shr-ser sch				

From	To	S.L.	Grade
84.0	126.5	42.5	.49

Logged by JDB

Hole No. U-B657

N.M.P.-F3742-3

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B 656 | SHAFT 2

BEARING 5608 | LAT. 13,233.5 | DATE COMPLETED | LEVEL 575

DIP AT COLLAR -40 | DEP. 7736.0 | PURPOSE Lower Fourth | WORKING B-403N

LENGTH 405.0 | ELEV. 5437 | Ore Def. | SECTION 1500N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLDS ASSAYS OZ./TON	OZ./TON
0 - 59.0	grn-gry chl-ser sch w minor ser'c sect,				
59.0 - 90.0	m.g. grn gb sch; trans into sch grs at 90.0				
90.0 - 152.5	f.g. gry-grn sch grs. possib amyg., variol resid at 139.0				
152.5 - 225.0	gry grs sch approach chl-ser in sect.				
225.0 - 242.0	grn sch grs, ep threads, variol sect,				
242.0 - 288.5	compact gry-grn grs sch, calc.				
288.5 - 295.0	gry chl sch, possible flow bx; variol resid.				
295.0 - 305.0	grs sch, bx tx (flow bx)				
305.0 - 340.0	mass grn variol p.l.				
340.0 - 405.0	F.g. grn grs sch; devel frm amyg p.l.				

Dip Tests

Depth	Read	Correct.
150	42	37½
300	38	34

LOGGED BY JHP

HOLE No. U-B656

N.M.P.-F3742-3

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-2655

BEARING --

DIP AT COLLAR -90

LENGTH 305.0

LAT. 12404

DEP. 7440.5

ELEV. 5130

DATE COMPLETED

PURPOSE No. 1 Shoot Def.

SHAFT 2

LEVEL 575

WORKING P-407W

SECTION 1500W

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLDS ASSAYS OZ./TON	OZ./TON
0 - 2.0	Cs.				
2.0 - 6.5	40% qtz., gr aspy	6924	4.5	.21	
6.5 - 11.0	dk chl-ser sch, minor qtz & min	6925	4.5	.10	
11.0 - 39.0	grn gb sch, snfl slt, sp aft 34.0				
39.0 - 79.0	m.g. sp grn grs; snfl, sp, sch after 79.0 v no sp.				
79.0 - 147.0	m.g. grn grs sch				
147.0 - 153.0	m.g. grn (sp) sch grs				
153.0 - 215.5	m.g. dk grn grs sch				
215.5 - 233.5	dk gry-grn chl-ser sch				
233.5 - 261.5	chty & blk slaty tuffac sch; part heavily pin v po. (slaty 239.0-261.5) t.s. minsect, t. sp & gry pin, V.G. (?)	6949	3.5	.14	
	255.5 - 259.0				
	t.s. 260.0 - 265.0	6950	5.0	.01	
261.5 - 305.0	Compact gry-buff ser sch; local po (buff?)				

From	To	C.L.	Grade
2.0	6.5	4.5	.21
255.5	259.0	3.5	.14

LOGGED BY JCP

HOLE No. U-2655

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
	Dip Test				
	Depth 300 — Read 31 — Correct 73½				

SHEET No. 170

HOLE No. U-B455

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
	Dip Tests				
	Depth / Read / Correct				
	150 / 60 / 56				
	290 / 47½ / 43				
deepened 304.0 - 332.0	dk grn-gry chl-ser sch				
332.0 - 356.0	dk grn chl grs sch				

SHEET No. 2

HOLE No. U-B655

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B 654
BEARING --
DIP AT COLLAR +90
LENGTH 124.0
LAT. 13404
DEP. 7449.5
ELEV. 5446
DATE COMPLETED
PURPOSE Ore Def.
SHAFT 2
LEVEL 575
WORKING 407W Dr.
SECTION 1500W

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 1.0	Cs.				
1.0 - 6.0	50% qutz, py, aspy	6909	5.0	.61	
6.0 - 10.0	qutz lenses in partly silic ser sch minor min	6910	4.0	.05	
10.0 - 29.0	dk gry chl-ser sch, local qutz & py				
29.0 - 33.5	20% qutz, minor min	6911	4.5	.13	
33.5 - 38.0	As above	6912	4.5	.11	
38.0 - 42.5	As above	6913	4.5	.11	
42.5 - 61.0	gry chl-ser sch				
61.0 - 66.0	black carb slaty sch				
66.0 - 77.0	silic sch impreg w py (tuffac.)				
77.0	f.g. gry grn grs sch merg into gis after 89.0; last two ft allig fab.				

From	To	C.L.	Grade
1.0	6.0	5.0	.61
29.0	42.5	13.5	.11

Logged by JDB

Hole No. U-B654

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B 653
BEARING S 60°E
DIP AT COLLAR -60°
LENGTH 180.0

LAT. 12416.61
DEP. 7559.62
ELEV. 5432:5

DATE COMPLETED Nov. 21/49
PURPOSE Ore Def.

SHAFT 2
LEVEL 575
WORKING 404N Dr.
SECTION 700N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 2.0	Cs.				
2.0 - 17.0	m.g. grs sch w qutz stingers & lenses				
17.0 - 83.0	m.g. gry chl-ser sch w qutz carb stingers				
83.0 - 90.0	Lt gry ser sch w qutz carb stingers & lenses				
90.0 - 96.0	qutz carb lenses in ser sch min w py	6914	6.0	.11	
96.0 - 102.0	As above	6915	6.0	.01	
102.0 - 108.0	20% qutz carb lenses spar min w py & aspy	6916	6.0	.01	
108.0 - 111.5	As above	6917	3.5	.05	
111.5 - 115.0	30% qutz carb spar min w py & aspy	6918	3.5	.09	
115.0 - 120.0	qutz carb lenses in ser sch.	6919	5.0	.04	
120.0 - 142.5	Lt gry ser sch w qutz carb lenses				
142.5 - 147.5	20% qutz carb spar min w. py. & aspy	6920	5.0	.16	
147.5 - 152.5	As above	6912	5.0	.09	
152.5 - 157.5	30% qutz carb & as above	6922	5.0	.11	

Logged by E.A.

Hole No. U-B653

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
157.5 - 161.0	As above	6923	3.5	.11	
161.0 - 162.0	Lt. gry chl ser w qutz carb lenses				
162.0 - 180.0	f.g lt grn grs sch w qutz stingers				

From	To	C.L.	Grade
142.5	161.0	18.5	.10

Dip Test

Depth	Read	Correct.
150	61½	57½

SHEET No. E.A.

HOLE No. U-B 653

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B 652 | SHAFT 2

BEARING - | LAT. 13175.5 | DATE COMPLETED | LEVEL 575

DIP AT COLLAR +90 | DEP. 7444.5 | PURPOSE No. 1 Shoot Def. | WORKING 408S Dr.

LENGTH 127.0 | ELEV. 5446 | SECTION 1300

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 1.0	Casing				
1.0 - 7.0	mg grs sch				
7.0 - 19.5	dk gry chl-ser sch				
19.5 - 25.0	qutz carb lenses in ser sch min w py	6881	5.5	0.22	1.21
25.0 - 30.0	20% qutz carb lenses min w py aspy	6882	5.0	1.13	5.66
30.0 - 33.0	80% qutz carb min w py aspy	6883	3.0	0.46	1.38
33.0 - 39.0	20% qutz carb lenses min w py aspy	6884	6.0	0.28	1.68
					9.93
39.0 - 44.0	ser sch w qutz carb lenses w section at banded py 41.5 - 43.0	6885	5.0	0.01	
44.0 - 50.0	20% qutz carb lenses min w. py	6886	6.0	0.11	
50.0 - 57.0	buff ser sch w qutz carb lenses min w py	6887	7.0	0.02	
57.0 - 64.0	chl-ser sch w qutz carb lenses w banded py 57.5 - 59.0	6888	7.0	0.02	
64.0 - 70.0	gry chl-ser sch	[illegible]	[illegible]	[illegible]	
70.0 - 77.0	chl-ser sch w qutz carb lenses min w py	6889	7.0	0.04	

Logged by E.J. | Hole No. U-B 652

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
77.0 - 81.0	As above	6890	4.0	.13	
81.0 - 85.0	gry ser sch w qutz carb lenses w py aspy	6891	4.0	.08	
85.0 - 86.5	80% bx qutz carb min w py	6892	1.5	.09	
86.5 - 97.0	gry com ser sch				
97.0 - 101.0	30% qutz carb lenses min w py	6893	4.0	.01	
101.0 - 105.5	80% qutz carb min w py	6894	4.5	.04	
105.5 - 108.0	30% qutz carb lenses min w py	6895	2.5	.03	
108.0 - 113.0	gry ser sch				
113.0 - 115.0	30% bx qutz carb lenses spar min w. py	6896	2.0	.06	
115.0 - 127	gry ser sch q qutz carb stingers & lenses				

SHEET No. 2

HOLE No. II-B 652

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B 651 | SHAFT 2
BEARING - | LAT. 13262.5 | DATE COMPLETED | LEVEL 575
DIP AT COLLAR -90 | DEP. 7492.0 | PURPOSE Ref. 500 ≠ 50W | WORKING B-406W
LENGTH 230.0 | ELEV. 5438 | SECTION 1400N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 2.0	Cs.				
2.0 - 37.0	bx qutz-carb in slaty chl-ser sch, py, cp, large xls aspy, po (?) dk coarse carb				
	t.s. 5.0 - 8.0	6858	3.0	0.06	
	t.s. 9.0 - 13.0	6859	4.0	0.06	
	t.s. 22.0 - 27.0	6860	5.0	0.08	
37.0 - 42.0	70% dk qutz-carb, large xls aspy	6861	5.0	0.07	
42.0 - 49.0	As above	6862	5.0/7.0	0.08	
49.0 - 55.0	gry chl-ser sch, dissem carb., py	6863	6.0	0.24	1.44
55.0 - 61.0	50% qutz-carb, sp, cy, py	6864	6.0	0.54	3.24
61.0 - 68.0	gry ser sch, dissem carb, py	6865	7.0	0.28	1.96
68.0 - 74.0	As above	6866	6.0	0.12	0.72
					7.36
74.0 - 88.0	dk gry chl-ser sch				
88.0 - 125	dk gry chl-ser sch, local qutz-carb & scat py				
	t.s. 97.5 - 100.5	6867	3.0	0.09	
	t.s.118.0 - 124.0	6868	6,0	0.02	

Logged by JDB | Hole No. U-B 651

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
125.0 - 173.0	dk gry chl-ser sch w brn alt. fl				
173.0 - 203.0	grn grs sch w brn alt fl 1 ft. ground 174.0 - 175.0				
203.0 - 208.0	60% qutz carb lenses w py + aspy	6872	5.0	0.37	1.85
208.0 - 210.5	As above	6873	2.5	0.39	0.98
					2.83
210.5 - 216.0	dk gry chl-ser sch				
216.0 - 218.0	90% qutz w. py	6874	2.0	0.45	0.90
218.0 - 220.0	qutz carb lenses in ser sch min w py	6875	2.0	0.18	0.36
					1.26
220.0 - 230.0	grs sch w brn alt th				

From	To	C.L.	Calc. Grade
49.0	74.0	25.0	0.28
203.0	210.5	7.5	0.38
216.0	220.0	4.0	0.32

Dip Test

At	Angle Read	Corrected Angle
150'	93°	92°

SHEET No. 2

HOLE No. M-8651

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B650
BEARING 560W
DIP AT COLLAR -60
LENGTH 136.U

LAT. 12453.08
DEP. 7597.04
ELEV. 5433

DATE COMPLETED
PURPOSE Ore Def.

SHAFT 2
LEVEL 575
WORKING B-404N
SECTION 750N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 2.0	Cs.				
2.0 - 8.5	20% qutz lenses, minor min	6392	6.5	.05	
8.5 - 69.5	it grn chl-ser sch w qutz-carb lenses,				
69.5 - 74.5	20% qutz-carb, minor min, tr gry min	6855	5.0	0.19	0.95
74.5 - 80.0	As above	6856	5.5	0.22	1.21 / 2.16
80.0 - 87.0	qutz lenses in ser-sch, minor min	6857	7.0	0.07	
87.0 - 94.0	As above	6876	7.0		
94.0 - 117.5	buff banded ser sch; minor local qutz, silic, & min				
117.5 - 121.0	30% qutz, sp & gry min	6870	3.5	0.22	
121.0 - 124.0	grn chl sch				
124.0 - 128.5	30% qutz-carb, minor min, fault cx at 128.5	6871	4.5	0.06	
128.5 - 136.0	f.g. grs sch				

Logged by JOB

Hole No. U-B650

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
94.0 - 101.0	buff banded ser sch; minor local qutz silic & min	6877	7.0	0.01	
101.0 - 108.0	As above	6878	7.0	0.05	
108.0 - 115.0	As above	6879	7.0	0.02	
115.0 - 117.5	As above w aspy	6880	2.5	0.02	

SHEET No. 2

HOLE No. U-B650

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
151.0 - 155.0	As above	6897	4.0	.28	1.120
155.0 - 160.0	As above	6898	5.0	.13	.650
160.0 - 165.0	50% qutz carb min w py aspy	6899	5.0	.16	.800
165.0 - 169.0	As above	6900	4.0	.35	1.400
169.0 - 172.0	As above	6901	3.0	.30	.900
172.0 - 175.0	20% qutz carb min w py	6902	3.0	.09	.360
175.0 - 179.5	60% qutz carb min w py aspy	6903	4.5	.37	1.665
179.5 - 184.0	gry ser sch w qutz carb lense	6904	4.5	.03	.135
184.0 - 189.0	60% qutz carb w py aspy & minor gry min	6905	5.0	.22	1.100
189.0 - 195.0	As above	6906	6.0	1.16	6.960
195.0 - 200.0	qutz carb lenses in gry ser sch	6907	5.0	.13	.650
200.0 - 206.0	70% qutz carb w py aspy	6908	6.0	1.62	9.720
					26.790
206.0 - 236.0	gry ser sch				

From	To	C.L.	Grade
86.0	95.0	9.0	.31
109.0	137.0	28.0	.45
144.0	206.0	62.0	.43

SHEET No. 2

HOLE No. U-3 169

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B 649 | SHAFT 2
BEARING -- | LAT. 13238 | DATE COMPLETED | LEVEL 575
DIP AT COLLAR -90 | DEP. 7534.5 | PURPOSE Ref Line 500 | WORKING B-406W
LENGTH 236.0 | ELEV. 5438 | SECTION 1400N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 2.0	Cs				
2.0 - 109.0	gry-buff ser sch, qutz lenses, minor local min; py				
	t.s. 19.0 - 23.0	6393	4.0	.20	
	t.s. 23.0 - 26.5	6869	3.5	.01	
	t.s. 26.5 - 32.5	6394	6.0	.30	
	t.s. 49.0 - 55.5	6395	6.5	.03	
	t.s. 79.0 - 86.0	6396	7.0	.13	
	t.s. 86.0 - 91.0	6397	5.0	.24)	1.200
	t.s. 91.0 - 95.0	6398	4.0	.40)	1.600
109.0 - 114.0	20% qutz-carb, py	6399	5.0	.52)	2.600
114.0 - 117.5	gry ser sch, minor qutz & min	6400	3.5	.06)	.210
117.5 - 123.0	30% qutz-carb, py, sp, tr gry min	6851	5.5	1.02)	5.610
123.0 - 130.0	qutz lenses in ser sch, py	6852	7.0	.49)	3.430
130.0 - 137.0	As above	6853	7.0	.12)	.840
137.0 - 144.0	ser sch w neg qutz & min				
144.0 - 151.0	30% qutz-carb, py, minor aspy, relative abund dissem py throughout hole suggests tuffac schist.	6854	7.0	.19	1.330

Logged by JRS | Hole No. U-B 649

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B 648
BEARING N60W
DIP AT COLLAR ∠ 70
LENGTH 139.0
LAT. 12478.99
DEP. 7602.75
ELEV. 5441
DATE COMPLETED
PURPOSE Ore Def.
SHAFT 2
LEVEL 575
WORKING B-404W
SECTION 775W

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.- 1.0	Cs				
1.0 - 17.5	Gry ser sch w qutz lenses				
17.5. - 34.5	Grn chl-ser sch				
34.5 - 38.5	90% wte qutz well min w py aspy gry min, V.G.	6382	4.0	.92) 1.55)	4.920
38,5 - 43.0	As above, V. G.	6383	4.5	1.23) 1.37)	5.850
43.0 - 50.5	Gry ser sch, minor qutz min	6384	7.5	.01	.075
50.5 - 58.0	As above	6385	7.5	.08	.600
58.0 - 64.0	90% qutz-carb, py, aspy, gry min, V.G.(?)	6386	6.0	.48	2.880
64.0 - 70.0	80% qutz & as above	6387	6.0	1.14	6.840
70.0 - 75.5	50% qutz-carb py aspy	6388	5.5	.80	4.400
75.5 - 81.0	30% qutz-carb & as above	6389	5.5	.33	1.815
81.0 - 87.5	As above	6390	6.5	.50	3.250
					19.185
87.5 - 139.0	Gry buff ser sch, t.s. 131.0 - 133.0	6391	2.0	..29	
					30.630

Logged by JDB

Hole No. U-B 648

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON

From	To	C. L.	Grade
34.5	43.0	8.5	1.26
58.0	87.5	29.5	.65
34.5	87.5	53.0	.57

SHEET No. 2

HOLE No. U-B648

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B 647
BEARING --
DIP AT COLLAR -90
LENGTH 2070
LAT. 13389.0
DEP. ~~7448.5~~ 6
ELEV. 5438
DATE COMPLETED
PURPOSE 500 Ref. Line
/ 100 W
SHAFT 2
LEVEL 575
WORKING B-406W
SECTION 1400N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 2.0	Cs				
2.0 - 7.5	Ser sch w qutz lenses				
7.5 - 9.0	30% qutz-carb, minor min				
9.0 - 19.0	Dk chl-ser sch, tan lent alf fl.	6370	1.5	.24	
19.0 - 23.5	40% qutz, py aspy tr gry min, sp, V.g.	6371	4.5	1.14 1.28	
23.5 - 51.0	Dk gry c.g. gran chl-ser sch, essent chl & merg w grs sch.				
51.0 - 77.0	grs sch, otherwise as above				
77.0 - 83.5	mass grn m.g. p & s grs becoming F.g. towards 83.5				
83.5 - 112.5	Distinct c.g. gab w allig fab, finer grained w snfl alt towards 112.5, ep grn.				
112.5 - 121.0	f.g. dense grs w chll'd contacts (basic dike)				
121.0 - 136.0	m.g. dk grn grs sch w snfl alt				
136.0 - 139.0	slaty schw bx tx				
139.0 - 162.0	dk gry-grn gls sch merg w chl-ser sch				

Logged by JOB

Hole No. U-B647

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
162.0 - 170.5	gran grn-buff chl-ser sch				
170.5 - 207.0	dk buff ser sch; miner qutz-carb after 202.0				

Hole abandoned at 207.0 when rods stuck (possible fault).

From	To	C. L.	Grade
7.5	9.0	1.5	.24
19.0	23.5	4.5	1.21

SHEET No. 2

HOLE No. U-B 647

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B 646
BEARING ---
DIP AT COLLAR +90
LENGTH 126.0
LAT. 12577.0
DEP. 7605.0 109'W
ELEV. 5441
DATE COMPLETED
PURPOSE Ore Def.
SHAFT 2
LEVEL 575
WORKING B-404N
SECTION 775N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 1.0	Cs.				
1.0 - 11.0	Gry ser sch, qutz lenses to 3.0 & 7.0 to 8.5				
11.0 - 52.5	Dk gry chl-ser sch				
52.5 - 57.5	30% qutz, local min	6372	5.0	.17	
57.5 - 65.5	Grn ser sch				
65.5 - 70.5	Qutz lenses in ser sch, minor min	6373	5.0	.29	1.450
70.5 - 73.5	As above	6374	3.0	.17	.510
73.5 - 79.0	30% qutz, in part silic; py, aspy	6375	5.5	.36	1.980
79.0 - 85.0	20% qutz in silic ser sch, py, aspy	6376	6.0	.18	1.080
85.0 - 91.0	As above	6377	6.0	.26	1.560
91.0 - 98.0	Silic ser sch; qutz lenses & minor min	6378	7.0	.03	6.580
98.0 - 104.0	As above	6379	6.0	.03	
104.0 - 107.5	As above	6380	3.5	.05	
107.5 - 115.5	30% qutz, py, aspy, Sp	6381	8.0	.48	

Logged by

Hole No.

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
115.5 - 126.0	gry ser sch				

From	To	C. L.	Grade
52.5	57.5	5.0	.17
65.5	91.0	25.5	.25
107.5	115.5	8.0	.48

SHEET No. JDB

HOLE No. U-B646

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B 645
BEARING -
DIP AT COLLAR +90
LENGTH 113.0
LAT. 13337.0
DEP. 7465.0 610W.
ELEV. 5446
DATE COMPLETED
PURPOSE Ore Def.
SHAFT 2
LEVEL 575
WORKING B-407N
SECTION 1450N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 1.0	Cs				
1.0 - 5.5	Chl-ser sch w slaty streaks				
5.5 - 8.0	20% qutz, py, aspy	6362	2.5	1.52	3.800
8.0 - 14.0	90% qutz, sparing min	6361	6.0	.28	1.680
14.0 - 19.0	30% qutz py, aspy	6363	5.0	.41	2.050
19.0 - 26.0	As above	6364	7.0	.26	1.820
					9.350
26.0 - 67.0	Dk gry chl-ser schw ton lent alt fl				
67.0 - 72.0	30% qutz, minor min	6365	5.0	.13	
72.0 - 92.5	qutz lenses in ser sch, no min				
92.5 - 98.5	90% qutz-carb minor min	6366	6.0	.06	.360
98.5 - 106.0	30% qutz, minor min	6367	7.5	.71	5.325
106.0 - 110.0	20% qutz-carb, minor min	6368	4.0	.42	1.680
					7.365
110.0 - 113.0	dk chl-ser sch				

From	To	C.L.	Grade
5.5	26.0	20.5	.45
92.5	110.0	17.5	.42

Logged by JDB

Hole No. U-B 645

GIANT YELLOWKNIFE GOLD MINES LIMITED

CORE RECORD

HOLE No. U-B 644
BEARING N60W
DIP AT COLLAR +70
LENGTH 82.0

LAT. 12434.59
DEP. 7579.09
ELEV. 5441

DATE COMPLETED
PURPOSE Fourth Level
ASD Zone Def.

SHAFT 2
LEVEL 575
WORKING B-404N
SECTION 725N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 1.0	Cs				
1.0 - 12.0	dk grn gry chl-ser sch, merg w grs sch				
12.0 - 24.5	gry ser sch w minor qutz lenses				
24.5 - 30.5	20% qutz lenses, aspy	6360	6.0	.10	
30.5 - 55.0	gry ser sch w qutz lenses, minor min				
55.0 - 62.0	20% qutz py aspy	6369	7.0	.10	
62.0 - 82.0	gry ser sch				

Logged by JDB

Hole No. U-B 644

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B 643
BEARING -----
DIP AT COLLAR ∠ 90
LENGTH 117.0

LAT. 13221.0
DEP. 7466.5 55' W
ELEV. 5446

DATE COMPLETED
PURPOSE Fourth Level
No. 1 Shoot Def.

SHAFT 2
LEVEL 575
WORKING B-408S
SECTION 1350N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 1.0	Cs.				
1.0 - 13.0	Dk gry grs sch w snfl slt merg w chl-ser sch				
13.0 - 17.5	Gry chl-ser sch w qutz lenses; T.S. 90% qutz 13.0-14.0	6354	1.0	.02	
17.5 - 24.5	20% qutz lenses, py aspy	6355	7.0	.54	
24.5 - 30.0	gry-buff ser sch, minor qutz-carb	6356	5.5	.01	
30.0 - 35.0	qutz-carb lenses followed by schist impreg w py	6357	5.0	.01	
35.0 - 42.0	sch impreg w py	6358	7.0	.06	
42.0 - 45.5	70% qutz-carb, sparing min	6359	3.5	.98	
45.5 - 117.0	dk gry chl-ser sch w local gry silic to 70.0				

From	To	C.L.	Grade
17.5	24.5	7.0	.54
42.0	45.5	3.5	.98

Logged by JDB

Hole No. U-B 643

GIANT YELLOWKNIFE GOLD MINES LIMITED

CORE RECORD

HOLE No. U-B642
BEARING --
DIP AT COLLAR -90
LENGTH 134.0
LAT. 12432.3
DEP. 7582.0
ELEV. 5441
DATE COMPLETED
PURPOSE N ASD Zone Def.
SHAFT 2
LEVEL 575
WORKING B404N
SECTION 725N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 1.0	Casing				
1.0 - 51.0	Dk gry chl-ser sch w qutz-carb lenses				
51.0 - 57.5	70% qutz carb, py aspy gry min v.g	6840	6.5	1.32) 1.37)	8.710
57.5 - 63.0	qutz stb in ser sch local min	6841	5.5	.24	1.320
63.0 - 70.0	As above	6842	7.0	.03	.210
70.0 - 77.0	20% qutz and as above local gry min	6843	7.0	.05	.350
77.0 - 82.0	30% qutz-carb, py aspy	6844	5.0	.13	.650
82.0 - 89.0	70% qutz-carb, py aspy sp, gry min v.g.	6845	7.0	.61	4.270
89.0 - 96.0	As above	6846	7.0	.42	2.940
96.0 - 101.0	30% qutz lenses, py aspy	6847	5.0	.29	1.450
101.0 - 106.0	40% and as above gry min	6848	5.0	1.38	6.900
106.0 - 112.0	50% qutz and as above	6849	6.0	.45	2.700
1112.0 - 113.5	70% qutz richly min w gry min	6850	1.5	.59	.885
113.5 - 117.5	40% qutz; py aspy	6851	4.0	.45	1.800

Logged by JDB

Hole No. U-B 642

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
117.5 - 123.5	70% dk qutz sp gry min	6852	6.0	.86	5.580
123.5 - 127.5	20% qutz lenses, minor min	6853	4.0	1.00	
127.5 - 134.0	qutz lenses in ser sch no min			.12	4.80
					38.245

From	To	C.L.	Grade
51.0	127.5	76.5	.50

SHEET No. 2

HOLE No. ~~U-B 642~~

GIANT YELLOWKNIFE GOLD MINES LIMITED

CORE RECORD

HOLE No. U-B 641
BEARING 560E
DIP AT COLLAR -70
LENGTH 87.0

LAT. 12453.08
DEP. 7597.04
ELEV. 5441

DATE COMPLETED
PURPOSE Ore Zone Def.

SHAFT 2
LEVEL 575
WORKING B-404N
SECTION 750N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 2.0	cs.				
2.0 - 33.5	Grn-buff chl-ser sch w qutz lenses				
	t.s. 23.0 - 25.0	6836	2.0	.04	
	t.s. 28.0 - 31.0	6837	3.0	.01	
33.5 - 87.0	Dk gry chl-ser sch minor qutz				
	t.s. chty silic sect 65.0 - 69.0	6838	4.0	.02	

Logged by J.D.B.

Hole No. U-B641

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B 640
BEARING N 60W
DIP AT COLLAR +60
LENGTH 114.0

LAT. 12457.25
DEP. 7589.83
ELEV. 5441

DATE COMPLETED
PURPOSE Ore Definition

SHAFT 2
LEVEL 575
WORKING B404N-Dr.
SECTION 750N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 1.0	Casing				
1.0 - 6.0	20% qutz-carb lenses in ser sch spar min with py	6832	5.0	.23	
6.0 - 18.0	Fg gray-grn chl-ser sch				
18.0 - 22.0	30% qutz-carb lenses in ser sch min with py and aspy	6833	4.0	.22	.880
22.0 - 25.0	As above but with increased qutz	6834	3.0	.41	1.230
25.0 - 49.0	Qutz-carb lenses in ser sch in part spar min - very short local sections of marginal ore				2.110
49.0 - 52.5	30% blue qutz and carb lenses in ser sch min with py and aspy	6835	3.5	.42	
52.5 - 80.0	Fg light gray ser sch				
80.0 - 84.0	Fg gray-grn compact ser sch				
84.0 - 96.5	Dk gry chl-ser sch				
96.5 - 114.0	Buff mottled ser-sch w qutz lenses				

From	To	C.L.	Grade
1.0	6.0	5.0	.23
18.0	25.0	7.0	.30
49.0	52.5	3.5	.42

Logged by JAH

Hole No. U-B640

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B 639
BEARING ---
DIP AT COLLAR +90°
LENGTH 38.0

LAT. 12402.1
DEP. 7385.9
ELEV. 5923.0

DATE COMPLETED Oct. 30, 1949
PURPOSE Ore Definition

SHAFT 2
LEVEL Stope
WORKING B214 Stope
SECTION 600N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 1.0	Casing				
1.0 - 5.0	50% qutz-carb lenses in ser sch min with py and minor aspy	6826	4.0	.07	.280
5.0 - 11.0	30% qutz-carb lenses and as above	6827	6.0	.08	.480
11.0 - 17.0	As above but with increased min	6828	6.0	.13	.780
17.0 - 23.0	As above, mass py from 18.0 - 19.0, fault breccia and hematite stain 21.5 - 23.0	6829	6.0	.20	1.200
23.0 - 27.0	40% qutz-carb lenses in ser sch, py and minor aspy min	6830	4.0	.12	.480
27.0 - 31.5	As above	6831	4.5	.19	.855
31.5 - 38.0	Fg gray to gray-grn ser sch grading to chl-ser sch forward 38.0				4.075

From	To	C.L.	Grade
1.0	31.5	30.5	.13

Logged by JAH

Hole No. U-B 639

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B 638
BEARING ------
DIP AT COLLAR +90°
LENGTH 37.0

LAT. 12394.0
DEP. 7399.5
ELEV. 5922.4

DATE COMPLETED Oct. 29, 1949
PURPOSE Ore Definition

SHAFT 2
LEVEL Stope
WORKING B214 Stope
SECTION 600N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 1.0	Casing				
1.0 - 8.0	20% qutz-carb lenses in ser sch min with py and aspy	6823	7.0	.07	
8.0 - 13.0	50% qutz-carb in ser sch in part well min with py aspy gray min and sph	6824	5.0	1.66 1.20	
13.0 - 16.0	Qutz-carb lenses in ser sch min with py and aspy	6825	3.0	.14	
16.0 - 26.0	Fg gray ser sch				
26.0 - 37.0	Fg gray-grn chl-ser sch				

From	To	C.L.	Grade
8.0	13.0	5.0	1.43

Logged by JAH

Hole No. U-B 638

GIANT YELLOWKNIFE GOLD MINES LIMITED

CORE RECORD

HOLE No. U-B 637

BEARING ------

DIP AT COLLAR +90°

LENGTH 42.0

LAT. 12380.1

DEP. 7423.0

ELEV. 5922.1

DATE COMPLETED Oct. 28, 1949

PURPOSE Ore Definition

SHAFT 2

LEVEL Stope

WORKING B214 Stope

SECTION 600N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 1.0	Casing				
1.0 - 6.0	40% qutz-carb lenses in ser sch min with py and aspy	6814	5.0	.12	
6.0 - 38.0	Fg highly schistose gray sil ser sch				
38.0 - 42.0	Fg gray-grn chl-ser sch				

Logged by JAH

Hole No. U-B 637

GIANT YELLOWKNIFE GOLD MINES LIMITED

CORE RECORD

HOLE No. U-B 636
BEARING -------
DIP AT COLLAR +90°
LENGTH 39.0

LAT. 12370.6
DEP. 7390.0
ELEV. 5914.4

DATE COMPLETED Oct. 27 /49
PURPOSE Ore Definition

SHAFT 2
LEVEL Stope
WORKING B214 Stope
SECTION 575N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 1.0	Casing				
1.0 - 6.0	Qutz-carb lenses in ser sch spar min with py and aspy	6810	5.0	.03	
6.0 - 12.0	As above	6811	6.0	.04	
12.0 - 17.0	30% qutz-carb lenses in ser sch min with py and aspy	6812	5.0	.23	
17.0 - 22.0	As above	6813	5.0	.11	
22.0 - 30.0	Fg gray ser sch				
30.0 - 32.0	Zone of faulting with hematite stains				
32.0 - 39.0	Fg gray-grn chl-ser sch				

From	To	G.L.	Calc Grade
12.0	17.0	5.0	.23

Logged by JAH

Hole No. U-B 636

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B 635
BEARING ---
DIP AT COLLAR +90°
LENGTH 48.0
LAT. 12381.4
DEP. 7372.3
ELEV. 5921.6
DATE COMPLETED Oct. 26, 1949
PURPOSE Ore Definition
SHAFT 2
LEVEL Stope
WORKING 214 Stope
SECTION 575N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 1.0	Casing				
1.0 - 7.0	30% qutz-carb lenses in ser sch min with py and aspy	6799	6.0	.44	
7.0 - 13.0	As above	6800	6.0	.11	
13.0 - 19.0	As above	6801	6.0	.02	
19.0 - 23.0	60% carb with minor qutz min with py and aspy	6802	4.0	.07	
23.0 - 29.0	Qutz-carb lenses in ser sch	6803	6.0	.01	
29.0 - 35.0	As above	6804	6.0	.03	
35.0 - 37.5	30% qutz-carb lenses in ser sch min with py, indication of fault (hematite and calcite) at 37.5	6805	2.5	.09	
37.5 - 41.0	Fg gray ser sch				
41.0 - 44.0	20% qutz-carb lenses in ser sch	6806	3.0	.12	
44.0 - 48.0	Fg gray-grn chl-ser sch				

From	To	Cl.	Calc. Grade
1.0	7.0	6.0	.44

Logged by JAH

Hole No. U-B 635

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B 634
BEARING ----
DIP AT COLLAR -90°
LENGTH 122.0
LAT. 12455.5
DEP. 7593.0
ELEV. 5439.5
DATE COMPLETED October 30, 1949
PURPOSE Ore Definition
SHAFT 2
LEVEL 575
WORKING B404N-Dr.
SECTION 750N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 1.0	Casing				
1.0 - 4.0	Fg gray ser sch				
4.0 - 10.0	30% qutz-carb lenses spar min with py and aspy	6783	6.0	.22	
10.0 - 32.0	Fg gray-grn chl-ser sch				
32.0 - 39.0	Qutz-carb lenses in ser sch	6784	7.0	.08	
39.0 - 45.0	80% qutz-carb min with py aspy and minor gray min, VG at 40.0 and 44.0	6785	6.0	2.91 2.29	15.600
45.0 - 50.0	60% carb lenses in ser sch min with py and aspy, minor qutz.	6786	5.0	.37	1.850
50.0 - 56.0	40% qutz-carb lenses in ser sch min with py and aspy with sections of mosak carb	6787	6.0	.18	1.080
56.0 - 61.0	As above	6788	5.0	.54	2.700
61.0 - 67.0	As above	6789	6.0	.70	4.200
67,0 - 72.0	80% qutz-carb min with py and aspy Fine V.G. at 70.0	6790	5.0	3.88 1.79	14.150

Logged by JAH

Hole No. U-B 634

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
72.0 - 77.0	80% qutz-carb min with aspy and minor py	6794	5.0	1.40	7.000
77.0 - 80.0	As above, 1 ft. core ground	6795	2.0/3.0	.93	2.790
80.0 - 85.0	Qutz-carb lenses in ser sch spar min with py	6796	5.0	.03	.150
85.0 - 90.0	70% qutz-carb lenses in ser sch min with py and aspy	6797	5.0	.91 1.22	5.250
90.0 - 95.0	30% qutz-carb lenses and as above	6798	5.0	.22	1.100
95.0 - 100.0	80% qutz and minor carb well min with py and aspy	6807	5.0	1.48 1.09	6.400
100.0 - 104.0	40% qutz-carb lenses in ser sch min with py and aspy	6808	4.0	.39	1.560
104.0 - 108.0	As above	6809	4.0	.27	1.080
108.0 - 113.0	40% qutz-carb lenses in ser sch min with py and aspy	6815	5.0	.20	1.000
113.0 - 118.0	As above -- Ground 2 ft. core	6816	3.0/5.0	.37	1.850
118.0 - 122.0	80% blue qutz with carb min with py and aspy	6817	4.0	1.12 1.00	4.240 72.000

From	To	C.L.	Grade
39.5	122.0	82.5	.87

SHEET No. 2

HOLE No. U-B 634

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B633
BEARING S60E
DIP AT COLLAR -55°
LENGTH 301.0

LAT. 12371.7
DEP. 7436.9 26 W
ELEV. 5431.8

DATE COMPLETED October 23, 1949
PURPOSE Ore Exploration

SHAFT 2
LEVEL 575
WORKING B404N-Dr
SECTION 600N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0-2.0	Casing				
2.0-43.0	M to fg grn mass to sch grs with epidote and lematite and faint traces of pillow structure between 10.0 and 20.0				
43.0-95.0	Fg light grn grs sch with a few local carb lenses				
95.0-156.0	Fg sch grs with numerous retic carbonate and epidote threads, possibility of local pillow structure or flow bx.				
156.0-188.0	Fg mass grn grs with possible pillow structure, schistose forwards 188.0.				
188.0-215.0	Fg gray-grn chl-ser sch with local sections of grs sch.				
215.0-234.0	Fg gray ser sch				
234.0-238.0	Qutz-carb lenses in ser sch min with py	6776	4.0	.04	
238.0-243.0	As above but with increasing min and qutz.	6777	5.0	.06	
243.0-249.0	Fg ser sch with local qutz-carb lenses	6778	6.0	.08	
249.0-255.0	As above	6779	6.0	.09	

Logged by JAH

Hole No. U-B 633

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
255.0-261.0	As above	6780	6.0	.15	.900
261.0-267.0	As above, 2' core ground	6781	4.0/6.0	.12	.480
267.0-272.0	30% qutz-carb lenses in ser sch min with py and aspy	6782	5.0	.21	1.050
272.0-301.0	Fg gray-grn grs sch, remarkably sharp contact between 30% qutz-carb lenses and grs sch at 272.0 with no intermediate chl-ser sch-sequence is similar to HW and FW contact in A5D zone (306 Stope) around Section 400 N				2.430

From	To	C.L.	Calc. Grade
255.0	272.0	17.0	.14
or 267.0	272.0	5.0	.21

Dip Tests

At	Angle Read	Corrected Angle
150	590	570
300	570	550

SHEET No. 2

HOLE No. T-B 633

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B632
BEARING N60W
DIP AT COLLAR -77½
LENGTH ~~110.0~~ 112.0

LAT. 12499.9
DEP. 7615.7 52W
ELEV. 5440

DATE COMPLETED Oct. 24/49
PURPOSE Ore Definition

SHAFT 2
LEVEL 575
WORKING B404N-Dr
SECTION 800N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 17.0	Fg gray ser sch with local carb lenses and neg min, in part chl-ser sch.				
17.0 - 54.0	Fg gray-grn chl-ser sch with local carb lenses				
54.0 - 58.0	Fg gray ser sch				
58.0 - 62.0	20% qutz-carb lenses in ser sch min with py	6770	4.0	.25	1.000
62.0 - 66.0	50% qutz-carb lenses and as above	6771	4.0	.81	3.240
					4.240
66.0 - 68.0	20% qutz-carb lenses spar min	6772	2.0	.07	
68.0 - 84.0	Fg gray ser sch with qutz-carb lenses				
84.0 - 88.0	30% qutz-carb lenses in ser sch min with py and aspy	6773	4.0	.24	.960
88.0 - 94.0	As above but with increased min	6774	6.0	.29	1.740
94.0 - 98.0	As above	6775	4.0	.16	.640
98.0 - 112.0	Fg gray compact ser sch				3.340

From	To	C.L.	Calc. Grade
58.0	66.0	8.0	0.53
84.0	98.0	14.0	0.23

Logged by JAH

Hole No. U-B 632

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B 631
BEARING ---
DIP AT COLLAR -90°
LENGTH 270
LAT. 12455.5
DEP. 7593.0
ELEV. 5433.0
DATE COMPLETED
PURPOSE Deep Ore Exploration
SHAFT 2
LEVEL 575
WORKING B404N-Dr
SECTION 750N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 2.0	Casing				
2.0 - 37.0	Fg grn chl-ser sch				
37.0 - 61.0	Fg gray ser sch with local carb lenses				
61.0 - 80.0	Fg gray-grn chl-ser sch in part ser sch				
80.0 - 99.0	Fg gray compact ser sch				
99.0 - 101.0	Qutz-carb lenses in ser sch spar min with py	6759	2.0	.28	
101.0 - 116.0	Fg gray compact ser sch				
116.0 - 120.0	20% qutz-carb lenses in ser sch well min with py and aspy	6760	4.0	.09	
120.0 - 124.0	40% qutz-carb lenses and as above	6761	4.0	.35	1.400
124.0 - 129.0	As above	6762	5.0	.22	1.100
129.0 - 131.0	60% qutz-carb lenses min with py aspy grey min and sph	6763	2.0	.41	.820
					3.320

Logged by JAH

Hole No. U-B 631

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
131.0 - 155.0	Fg gray ser sch with local qutz-carb lenses and traces of banding throughout				
155.0 - 214.0	Fg gray ser sch				
214.0 - 221.0	Very fg dark gray compact ser sch				

From	To	C.L.	Calc. Grade
99.0	101.0	2.0	.28
120.0	131.0	11.0	.30

Dip Test

At	Angle Read	Corrected Angle
150°	87°	86°

221.0 - 244.0	f.g. grn grs sch				
244.0 - 270.0	m.g. sch grs w. epid				

SHEET No. 2

HOLE No. U-8 631

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B 631
BEARING ------
DIP AT COLLAR -900
LENGTH 221.0

LAT. 12455.5
DEP. 7593.0
ELEV. 5433.0

DATE COMPLETED
PURPOSE Deep Ore Exploration

SHAFT 2
LEVEL 575
WORKING B404N-Dr
SECTION 750N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 2.0	Casing				
2.0 - 37.0	Fg grn chl-ser sch				
37.0 - 61.0	Fg gray ser sch with local carb lenses				
61.0-- 80.0	Fg gray grn chl-ser sch in part ser sch				
80.0 - 99.0	Fg gray compact ser sch				
99.0 - 101.0	Qutz-carb lenses in ser sch spar min with py	6759	2.0	.28	
101.0 - 118.0	Fg gray compact ser sch				
116.0 - 120.0	20% qutz-carb lenses in ser sch well min with py and aspy	6760	4.0	.09	
120.0 - 124.0	40% qutz-carb lenses and as aoove	6761	4.0	.35	1.400
124.0 - 129.0	As above	6762	5.0	.22	1.100
129.0 - 131.0	60% qutz-carb lenses min with py aspy gray min and sph	6763	2.0	.41	.820
					3.320

Logged by JAH

Hole No. U-B 631

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
131.0 - 155.0	Fg gray ser sch with local qutz-carb lenses and traces of banding throughout				
155.0 - 214.0	Fg gray ser sch				
214.0 - 221.0	Very fg dark gray compact ser sch				

From	To	C.L.	Calc. Grade
99.0	101.0	2.0	.28
120.0	131.0	11.0	.30

Dip Test

At	Angle Read	Corrected Angle
150'	87°	86°

SHEET No. 2

HOLE No. U-B 631

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B 630
BEARING S60E
DIP AT COLLAR -45°
LENGTH 130.0

LAT. 12496.0
DEP. 7621.8 53W
ELEV. 5433.1

DATE COMPLETED
PURPOSE Ore Definition

SHAFT 2
LEVEL 575
WORKING B404N-Dr.
SECTION 800N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	GOLD ASSAYS OZ./TON
0.0 - 21.0	Fg gray-grn chl-ser sch with local pink calcite lenses				
21.0 - 29.5	Fg gray ser sch				
29.5 - 34.5	Highly sil ser sch well min with py and minor aspy	6756	5.0	.03	
34.5 - 40.0	30% qutz-carb lenses in ser sch spar min with py and aspy, traces of sph	6757	5.5	.16	.885
40.0 - 45.0	40% qutz-carb lenses and as above	6758	5.0	.11	.550
45.0 - 50.0	20% qutz-carb lenses in ser sch spar min with py	6764	5.0	.31	1.550
50.0 - 55.0	As above but with traces of gray min	6765	5.0	.26	1.300
55.0 - 60.0	30% qutz-carb lenses in ser sch min with py and aspy	6766	5.0	.34	1.700
60.0 - 66.0	As above	6767	6.0	.35	2.100
66.0 - 72.0	As above with decreasing min	6768	6.0	.15	.900
					8.985

Logged by JAH

Hole No. D-B 630

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
72.0 - 76.0	Qutz-carb lenses in ser sch	6769	4.0	.05	
76.0 - 95.0	Fg grey-grn chl-ser sch				
95.0 - 130.0	M to fg grn grs sch				

From	To	C.L.	Calc Grade
34.5	72.0	37.5	.24

SHEET No. 2

HOLE No. U-E 630

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
67.0 - 70.5	Qutz-carb lenses in ser sch	6739	3.5	.46	1.610
70.5 - 75.0	80% blue-black qutz with some carb min with py aspy and traces of Sph and gray min	6740	4.5	.61 -61	2.745
75.0 - 80.0	30% qutz-carb lenses in ser sch min with py and minor aspy-1 ft. core ground	6741	4.0/5.0	.51	2.550
80.0 - 85.0	As above	6742	5.0	.20	1.000
85.0 - 89.0	Qutz-carb lenses in ser sch, spor min	6743	4.0	.09	.360
89.0 - 93.0	As above	6444	4.0	.31	1.240
93.0 - 100.0	Fg gray ser sch				
					14.970

From	To	C.I.	Calc. Grade
53.5	93.0	39.5	.38

SHEET No. 2

HOLE No. U-B 629

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B 629
BEARING ------
DIP AT COLLAR +90
LENGTH 100.0

LAT. 13262.5
DEP. 7492.0
ELEV. 545.7

DATE COMPLETED Oct. 16/49
PURPOSE No. 1 Shoot Definition

SHAFT 2
LEVEL 575
WORKING B406W-XC
SECTION 1400N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 1.0	Casing				
1.0 - 6.0	Fg gray ser sch				
6.0 - 10.0	40% qutz-carb lenses in ser sch with short sections of sch replaced by mass py, minor sph and aspy	6733	4.0	.05	
10.0 - 17.0	Qutz-carb lenses in ser sch min with py	6734	7.0	.02	
17.0 - 19.0	Fg black slate-like material similar to slate of 303W-XC., marks sharp contact between ser and chl-ser sch.				
19.0 - 29.0	Fg gray green chl-ser sch, possibly an intrusive with brown alt flecks and reasonably sharp contacts				
29.0 - 49.0	Fg light gray sil ser sch				
49.0 - 53.5	Qutz-carb lenses in ser sch	6735	4.5	.08	
53.5 - 58.0	30% qutz-carb lenses in ser sch min with py (mass in part) and aspy	6736	4.5	.39	1.755
58.0 - 63.0	As above	6737	5.0	.61	3.050
63.0 - 67.0	20% qutz-carb lenses and as above	6738	4.0	.16	.640

Logged by JAH

Hole No. U-B629

GIANT YELLOWKNIFE GOLD MINES LIMITED

CORE RECORD

HOLE No. U-B 628
BEARING S44E
DIP AT COLLAR -15½°
LENGTH 37.0

LAT. 12443N
DEP. 7420E
ELEV. 5395.5

DATE COMPLETED Oct. 16/49
PURPOSE B213 Stope Foot Wall Definition

SHAFT 2
LEVEL Stope
WORKING B213 Stope
SECTION 652 N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON		GOLD ASSAYS OZ./TON
0.0 - 4.0	20% qutz-carb lenses in ser sch min with py and aspy	6751	4.0	.05		.200
4.0 - 10.0	90% qutz-carb min with py aspy gray min and sph, V.G. between 8.0 and 9.0, fault bx and calcite at 5.5 indicating possible fault	6752	6.0	6.00	7.22	30.000
10.0 - 15.0	90% blue qutz with minor carb well min with py and aspy, minor sph and gray min	6753	5.0	.70	.78	3.700
15.0 - 20.0	50% qutz-carb lenses and as above	6754	5.0	1.05	1.02	5.150
20.0 - 23.5	As above but with decreasing min	6755	3.5	.64	.69	2.310
23.5 - 37.0	Fg gray ser sch with local carb lenses					413.60

From	To	C.L.	Calc. Grade
0	23.5	23.5	1.76

Logged by JAH

Hole No. U-B 628

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B627
BEARING S44E
DIP AT COLLAR Hor
LENGTH 400

LAT. 12,443 N
DEP. 7,420 E
ELEV. 5,896.5

DATE COMPLETED Oct. 16/49
PURPOSE B 213 Stope Foot Wall Definition

SHAFT 2
LEVEL Stope
WORKING B 213 Stope
SECTION 652 N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	GOLD ASSAYS OZ./TON
0.0 - 5.0	60% qutz-carb in ser sch min with py and aspy, fault bx at 1.0	6745	5.0	.93	4.650
5.0 - 10.0	90% blue qutz with minor carb min with py aspy and minor gray min, V G at 7.0	6746	5.0	3.92 2.36	15.700
10.0 - 15.0	As above but min with aph	6747	5.0	1.16 .83	4.950
15.0 - 21.0	As above with V G in three short sections	6748	6.0	8.61 9.42	30.000
21.0 - 25.0	80% carbonate with minor blue qutz spar min with py aspy and gray min, fine V G at 22.0	6749	4.0	4.55 4.12	17.320
25.0 - 29.0	20% qutz-carb lenses in ser sch min with py and aspy	6750	4.0	.12	.480
29.0 - 40.0	Fg gray ser sch with local carb lenses and neg min.				73.100

From	To	G.L.	Calc. Grade
0	29.0	29.0	2.52

Logged by JAH

Hole No. U-B 627

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B626
BEARING ------
DIP AT COLLAR -90°
LENGTH 229.0

LAT. 12414.5N
DEP. 7,563.4E
ELEV. 5,432.7

DATE COMPLETED October 15, 1949
PURPOSE Deep Ore exploration

SHAFT 2
LEVEL 575
WORKING B404N-Dr.
SECTION 700N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 2.0	Casing				
2.0 - 63.0	Fg gray-grn chl-ser sch, in part grs sch, with local carb lenses				
63.0 - 73.0	Fg gray ser sch with numerous pink calcite lenses, neg min, possible fault at 68.5'				
73.0 - 130.0	Fg grey ser sch with local qutz-carb lenses				
130.0 - 135.0	20% qutz-carb lenses in ser sch spar min with py	6730	5.0	.08	
135.0 - 142.0	Qutz-carb lenses and as above	6731	7.0	.04	
142.0 - 149.0	As above	6732	7.0	.05	
149.0 - 229.0	Fg gray-grn compact ser sch in part chl-sch sch, fairly uniform throughout becoming less schistose foward 229.0				

Dip Test

At	Angle Read	Corrected Angle
229.0	79°	76°

Logged by J.A.H.

Hole No. U-B626

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B 625
BEARING N60W
DIP AT COLLAR -45°
LENGTH 129.0

LAT. 12499.9N
DEP. 7616.0E
ELEV. 5439.0

DATE COMPLETED
PURPOSE Ore Definition

SHAFT 2
LEVEL 575
WORKING B404N-Dr.
SECTION 800N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 160	Fg gray-green chl-ser sch				
16.0 - 35.0	Mg grn grs scl, in part chl-ser sch				
35.0 - 42.0	Fg chl-ser sch with gradation to ser sch				
42.0 - 47.0	Qutz-carb lenses in ser sch min with py	6726	5.0	22.21	1.050
47.0 - 53.0	40% qutz-carb lenses in ser sch min with py and minor aspy	6727	6.0	.07	.420
53.0 - 57.0	As above but with increasing min	6728	4.0	.35	1.400
57.0 - 59.0	As above	6729	2.0	.35	.700
59.0 - 69.0	Fg gray grn chl-ser sch				3.570
69.0 - 98.0	Fg grn grs sch				
98.0 - 129.0	Fg grey grn chl-ser sch, in part ser sch				

From	To	C.I.	Calc. Grade
42.0	59.0	17.0	.21

Logged by JAH

Hole No. U-B 625

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B 624
BEARING S60E
DIP AT COLLAR -45°
LENGTH 225.0

LAT. 12,716.0 N
DEP. 7,541.0 E 2 NW
ELEV. 5,433.0

DATE COMPLETED October 15, /49
PURPOSE Ore exploration

SHAFT 2
LEVEL 575
WORKING B403N-Dr.
SECTION 950N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON		OZ./TON
0.0 - 2.0	Casing					
2.0 - 24.0	Fg dark gray chl-ser sch					
24.0 - 39.0	Fg gray ser sch with brown alt flecks					
39.0 - 44.0	30% qutz-carb in ser sch min with py and aspy.	6714	5.0	.21		
44.0 - 47.0	As above	6715	3.0	.05		
47.0 - 75.0	Fg dark gray chl-ser sch					
75.0 - 80.0	Qtz carb lenses in ser sch. spar min	6716	5.0	.03		
80.0 - 84.0	As above	6717	4.0	.06		
84.0 - 93.0	Fg gray ser sch with fair banding exhibited					
93.0 - 96.5	60% qutz-carb lenses in ser sch min with py and aspy	6723	3.5	.81	1.07	3.290
96.5 - 100.5	40% qutz-carb and as above	6724	4.0	.04	.08	.240
100.5 - 107.0	20% qutz-carb lenses and as above	6725	6.5		.25	1.625
						5.155

Logged by J.A.H.

Hole No. U-B624

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
107.0 - 147.0	Fg gray ser sch with local carb lenses, 3' core ground at 121.0				
147.0 - 207.0	M to fg gray grn chl-ser sch, in part grs sch				
207.0 - 225.0	Fg gray ser sch				

From	To	C.L.	Calc. Grade Uncut
39.0	44.0	5.0	.21
93.0	107.0	14.0	.37

At.	Dip Tests Angle Read	Corrected Angle
150.	48°	~~43½~~ 10 39

SHEET No. 2

HOLE No. ~~UB 624~~

GIANT YELLOWKNIFE GOLD MINES LIMITED

CORE RECORD

HOLE No. U-B 623
BEARING N60W
DIP AT COLLAR -60°
LENGTH 186.0

LAT. 12,957.0
DEP. 7,625.2
ELEV. 5,434

DATE COMPLETED October 11/49
PURPOSE Deep Level Expl.

SHAFT 2
LEVEL 575
WORKING B403N-Dr
SECTION 1200N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON		OZ./TON
0.0 - 2.0	casing					
2.0 - 14.0	Fg gray grn chl-ser sch					
14.0 - 31.0	Fg gray highly sil ser sch with minor py and local carb lenses					
31.0 - 46.0	Fg gray-grn chl-ser sch					
46.0 - 54.0	Fg gray ser sch with local carb lenses					
54.0 - 59.0	80% qutz-carb min with py, aspy, minor gray min and sph	6698	5.0	.35	.28	1.550
59.0 - 61.5	As above with fine V.G. at 60.0	6699	2.5	6.05	6.47	12.500
61.5 - 68.0	30% qutz-carb lenses in ser sch min with py and aspy	6700	6.5	.05		.325
68.0 - 74.0	as above					
74.0 - 77.0	as above	6701	6.0	.18		1.080
77.0 - 82.0	60% qutz-carb spar min with py aspy and fine gray min, speck of fine V.G. at 80.0	6702	3.0	.20		.600
82.0 - 88.0	30% qutz-carb lenses in ser sch min with py and aspy	6703	5.0	.19	.19	.950
88.0 - 94.0	as above	6704	6.0	.12		.720
94.0 - 99.0	50% qutz-carb lenses and as above, speck of V.G. at 95.0	6705	5.0	.66	.90	3.900

Logged by J.A.H.

Hole No. U-B 623

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
99.0 - 105.0	30% qutz-carb lenses in ser sch min with py and aspy	6706	5.0	.66 .90	3.900
105.0 - 111.0	as above	6707	6.0	.16	.960
111.0 - 117.0	as above	6708	6.0	.20	1.200
117.0 - 122.0	60% qutz-carb lenses in ser sch spar min with py aspy	6709	6.0	.28	1.680
122.0 - 128.0	as above	6710	5.0	.32	1.600
128.0 - 133.0	as above	6711	6.0	.30	1.800
133.0 - 138.0	as above	6712	5.0	.09	.450
138.0 - 178.0	Fg gray-grn ser sch, in part chl-ser with local carb lenses	6713	5.0	.63	3.150
					32.585
178.0 - 186.0	Fg light-gray ser sch with possibly banding				

	From	To	C.L.	Calc.Grade
	54.0	61.5	7.5	1.87
	94.0	138.0	44.0	.33
or	54.0	138.0	84.0	.38

Dip test

At.	Angle Read.	Corrected Angle
186'	61°	57°

SHEET No. 2

HOLE No. U-B 623

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B 622
BEARING --
DIP AT COLLAR -90°
LENGTH 361.0

LAT. 13,029.0
DEP. 7,698.5
ELEV. 5,434.5

DATE COMPLETED October 12, 1949
PURPOSE Deep Ore Exploration

SHAFT 2
LEVEL 575
WORKING B405E X-C
SECTION 1300N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 2.0	casing				
2.0 - 20.0	Fg gray-grn chl-ser sch				
20.0 - 46.0	Fg gray ser sch				
46.0 - 62.0	Fg gray-grn ser sch with local carb lenses				
62.0 - 103.0	Fg light gray ser sch with local qutz-carb lenses and neg min				
103.0 - 123.5	M to fg gray ser sch				
123.5 - 128.0	80% qutz-carb spar min with py aspy and traces of sph	6681	4.5	.38	1.710
128.0 - 135.0	20% qutz-carb lenses in ser sch spar min with py and aspy	6682	7.0	.13	.910
135.0 - 140.0	70% qutz with minor carb spar min with py aspy and sph	6683	5.0	.93	4.650
140.0 - 145.0	as above	6684	5.0	.77	3.850
145.0 - 150.0	40% qutz-carb lenses and as above	6685	.29	5.0	1.450
150.0 - 156.0	as above	6686	.44	6.0	2.640
156.0 - 162.0	as above	6687	.08	6.0	.480
162.0 - 167.0	60% qutz with minor carb min with py and aspy	6688	5.0	.55	2.750

Logged by J.A.H.

Hole No. U-B 622

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
167.0 - 172.0	40% qutz-carb lenses and as above	6689	5.0	.54	2.700
172.0 - 178.0	as above	6690	6.0	.34	2.040
					23.230
178.0 - 185.5	Fg gray ser sch				
185.5 - 187.0	40% bx qutz well min with aspy and minor py	6691	1.5	.56	
187.0 - 197.0	Fg gray ser sch				
197.0 - 202.0	50% qutz in ser sch min with py and aspy	6692	5.0	.31	1.550
202.0 - 208.0	as above but with increasing carb	6693	6.0	.11	.660
					2.210
208.0 - 232.0	Fg dark gray ser sch with local qutz-carb lenses				
232.0 - 254.0	Fg light gray ser sch with numerous qutz-carb lenses				
254.0 - 296.5	Very fg light gray chert-like ser sch 4' ground at 285.0				
296.5 - 303.0	50% by qutz-carb min with py and aspy	6694	6.5	.78	5.070
303.0 - 314.0	Fg gray-grn ser sch				
314.0 - 319.0	30% qutz-carb lenses in ser sch min with py and aspy	6695	5.0	.12	
319.0 - 325.0	Fg light gray ser sch with local qutz-carb lenses spar min	6696	6.0	.04	
325.0 - 330.0	40% qutz in ser sch very well min with fine aspy, in part mass aspy for short sections, minor py, sph and gray min	6697	5.0	.46 .48	2.350
330.0 - 334.5	60% qutz in ser sch very well min with aspy and minor py, short sections of mass aspy as above	6718	4.5	.91 1.07	4.455
334.5 - 339.5	90% blue qutz, minor carb well min with py, aspy, sph and gray min, possible V.G. at 339.0	6719	5.0	.39 .46	2.100
339.5 - 345.0	40% qutz-carb lenses in ser sch min with py, aspy, gray min and sph	6720	5.5	.17 .21	1.045
					9.950

SHEET No. 2

HOLE No. U-B 622

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
345.0 - 349.5	20% qutz-carb lenses in ser sch spar min with py and aspy	6721	4.5	.07	
349.5 - 353.0	as above	6722	3.5	.04	
353.0 - 361.0	Fg light gray ser sch				

From	To	C.L.	Calc.Grade
123.5	178.0	54.5	.42
185.5	187.0	1.5	.56
197.0	208.0	11.0	.22
296.5	303.0	6.5	.78
325.0	345.0	20.0	.50

Dip tests

At.	Angle Read.	Corrected Angle
150'	80°	77°
300'	72°	68½°

SHEET No. 3

HOLE No. U-B 622

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B 621
BEARING 360B
DIP AT COLLAR Hor.
LENGTH 423.0

LAT. 13,233.5
DEP. 7,736.0
ELEV. 5,438.5

DATE COMPLETED October 7/49
PURPOSE Ore exploration

SHAFT 2
LEVEL 575
WORKING 3403N-Dr.
SECTION 1495N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 29.0	M to fg grey-grn chl-ser sch with gradation to grs sch after 20.0				
29.0 - 69.0	M grained grey-grn mass grs, in part coarse grained with possible spherulitic (?) pillow structure, characterized by prominent epidote and minor pink calcite				
69.0 - 85.0	M to fg dark grn sch grs with only slight traces of pillow structure				
85.0 - 131.0	Med grained grn grs (porphyritic) with concentration of feldspar phenocrysts between 90.0 and 100.0, general appearance of an intrusive with a fair contact at 131.0				
131.0 - 141.0	Fg grn sch grs with local epidote sections				
141.0 - 168.0	Med to coarse grained gabbro with a prominent contact at 168.0				
168.0 - 209.0	Fg slightly sch grs				
209.0 - 242.0	Fg mass grs with well developed spherulitic pillow structure displayed throughout				
242.0 - 282.0	Fg gray-grn grs sch (in part sch grs) with local carb lenses, with faint indications of spherulitic from 261.0 to 282.0				
282.0 - 344.0	Fg grn mass to sch grs				
344.0 - 370.0	Fg grey-grn sch grs, in part grs sch with local carb lenses and minor epidote				

Logged by J. A. F.

Hole No. U-B621

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
370.0 - 402.0	Fg grn grs sch with local carb lenses				
402.0 - 423.0	M to fg grn mass to sch grs				

SHEET No. 2

HOLE No. U-B 621

GIANT YELLOWKNIFE GOLD MINES LIMITED

CORE RECORD

HOLE No. U-B 620
BEARING S60E
DIP AT COLLAR -60°
LENGTH 366.0

LAT. 13,138.0
DEP. 7,702.8
ELEV. 5,436.0

DATE COMPLETED October 5, 1949
PURPOSE Deep Level Exploration

SHAFT 2
LEVEL 575
WORKING B403N-Dr
SECTION 1400N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 3.0	casing				
3.0 - 12.5	Fg gray ser sch				
12.5 - 17.0	30% qutz-carb lenses in ser sch min with py	6634	4.5	.32	1.440
17.0 - 22.0	60% qutz with minor carb min with py aspy and traces of gray min, V.G. at 20.0	6635	5.0	.80	4.000
22.0 - 27.5	Fg ser sch with local qutz-carb lenses spar min with py and aspy	6636	5.5	.47	2.585
27.5 - 29.5	30% qutz-carb lenses min with py and aspy, V.G. at 28.0	6637	2.0	.96	1.920
					9.945
29.5 - 35.0	Qutz-carb lenses in ser sch spar min with py	6638	5.5	.01	
35.0 - 40.0	As above	6639	5.0	.11	
40.0 - 44.0	As above	6640	4.0	.03	
44.0 - 55.0	Fg gray ser sch with local carb lenses				
55.0 - 64.0	Gradual gradation through chl-ser sch to grs sch				
64.0 - 118.0	Fg grn grs sch with local epid & sections				
118.0 - 149.0	Fg gray-grn chl-ser sch (in part ser sch)				
149.0 - 157.0	Fg gray ser sch				

Logged by U-B 620 Hole No. J.A.H.

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
157.0 - 161.0	Qutz-carb lenses in ser sch spar min with py	6661	4.0	.13	
161.0 - 165.0	as above but with local traces of sph	6662	4.0	.09	
165.0 - 201.0	Fg gray ser sch with local carb lenses, local sections of chl-ser sch				
201.0 - 205.0	30% qutz-carb lenses in ser sch spar min with py	6663	4.0	.81	
205.0 - 209.5	Fg gray ser sch				
209.5 - 214.0	40% qutz with minor carb min with py and aspy	6664	4.5	.43	1.935
214.0 - 221.0	20% qutz-carb lenses spar min with py	6665	7.0	.20	1.400
					3.335
221.0 - 235.0	Fg gray ser-sch				
235.0 - 241.0	30% qutz-carb lenses in ser sch spar min with py, minor sph & gray min	6666	6.0	.28	1.680
241.0 - 247.0	Qutz-carb lenses in ser sch min with py and aspy	6667	6.0	.04	
247.0 - 250.0	60% qutz with minor carb min with py aspy and minor sph	6668	3.0	.94	2.820
250.0 - 256.0	Qutz-carb lenses spar min with py and aspy	6669	6.0	.17	1.020
					3.840
256.0 - 304.0	Fg gray ser sch with local carb lenses in part well sil				
304.0 - 313.0	Fg gray-grn ser sch in part chl-ser sch				
313.0 - 317.0	30% qutz-carb lenses in ser sch	6670	4.0	.16	.640
317.0 - 322.0	50% qutz-carb and as above	6671	5.0	.69	3.450
322.0 - 324.5	80% blue qutz with minor carb min with py, aspy and traces of sph	6672	2.5	3.72	9.300
324.5 - 328.0	Qutz-carb lenses in ser sch spar min with py	6673	3.5	.05	.175
328.0 - 333.0	70% qutz with minor carb well min with py and aspy	6674	5.0	1.69	8.450
					22.015

SHEET No. 2

HOLE No. U-B 620

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
333.0 - 340.0	Qutz-carb lenses in ser sch spar min with py	6675	7.0	.02	
340.0 - 347.0	As above	6676	7.0	.02	
37.0 - 354.0	As above but with increasing min	6677	7.0	.02	
354.0 - 359.0	50% qutz-carb lenses in ser sch min with py aspy and traces of sph	6678	5.0	.55	2.750
359.0 - 364.0	20% qutz-carb lenses in ser sch min with py and minor aspy	6679	5.0	.68	3.400
364.0 - 366.0	30% qutz-carb and as above	6680	2.0	.92	1.840
					7.990

Hole stopped at 366.0 due to insufficient supply of 5 foot rods

	From	To	C.L.	Calc.Grade
	12.5	29.5	17.0	.58
	201.0	205.0	4.0	.81
	209.5	221.0	11.5	.29
	235.0	241.0	6.0	.28
	247.0	256.0	9.0	.42
or	201.0	256.0	55.0	.22
	313.0	333.0	20.0	1.10
	354.0	366.0	12.0	.66

Dip Tests

Att.	Angle Read.	Corrected Angle
150°	44°	40°
290°	41°	36°

SHEET No. 3

HOLE No. U-B 620

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON		OZ./TON
	Deepending at U-B 620					
366.0 - 371.0	Qutz-carb lenses in ser sch min with py and aspy	6791	5.0	.26		1.300
371.0 - 377.0	As above	6792	6.0	.20		1.200
377.0 - 383.0	As above	6793	6.0	2.28	2.27	13.620
						24.110
383.0 - 405.0	Fg gray ser sch, in part chl-ser sch					
405.0 - 416.0	Fg grn grs sch					

N-B. - Check assay run on No. 6793 ran 2.27- possibly explained by fine V.G. in qutz lense not being observed.

From	To	CL.	Calc. Grade
354.0	383.0	29.0	.83

SHEET No. 4

HOLE No. U-B 620

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-3619
BEARING 360°
DIP AT COLLAR -60°
LENGTH 255.0

LAT. 13,323.5
DEP. 7,736.0
ELEV. 5,436.6

DATE COMPLETED October 3/49
PURPOSE Deep Level Expl.

SHAFT 2
LEVEL 575
WORKING 8-403N
SECTION 1495N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 2.0	as				
2.0 - 57.0	grn-buff chl-ser sch w numerous qutz-carb len.,				
57.0 - 87.0	dk grn comp grs sch				
87.0 - 122.0	grn compact chl-ser sch				
122.0 - 131.5	Fg grey ser sch				
131.5 - 137.5	Qutz-carb lenses in ser sch	6641	6.0	.05	
137.5 - 150.5	Fg dark grey ser sch				
150.5 - 156.0	20% qutz-carb lenses in ser sch	6642	5.5	.02	
156.0 - 161.0	as above but min with py and minor aspy	6643	5.0	.03	
161.0 - 163.0	as above	6644	2.0	.09	
163.0 - 168.0	Fg grey sil ser sch	6645	5.0	.02	
168.0 - 172.0	30% qutz with minor carb min with py and minor aspy	6646	4.0	.05	
172.0 - 177.0	20% qutz-carb lenses in ser sch spar min.	6647	5.0	.05	
177.0 - 182.0	as above but well min with py and minor aspy	6648	5.0	.11	
182.0 - 187.0	as above (in sil ser sch)	6649	5.0	.30	1.500

Logged by J.W.F.

Hole No. U-3 619

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
187.0 - 192.0	as above	6650	5.0	.25	1.250
192.0 - 196.0	30% qutz with minor carb min with py and sspy	6653	4.0	.23	.920
196.0 - 201.0	90% blue qutz with minor carb min with py, sspy and minor sph and grey min, fine V.G. in several spots	6654	5.0	.70	3.500
201.0 - 205.0	70% blue qutz and as above, V.G. at 202.0	6655	4.0	.66	2.640
205.0 - 210.0	50% qutz-carb lenses in ser sch min with py and sspy	6656	5.0	.34	1.700
210.0 - 215.0	30% qutz-carb lenses in ser sch min with py and minor sspy, traces of sph	6657	5.0	.21	1.050
215.0 - 221.0	as above	6658	6.0	.26	1.560
221.0 - 225.0	as above but with decreasing min	6659	4.0	.38	1.520
225.0 - 228.0	as above	6660	3.0	.34	.700
					16.890
228.0 - 232.0	Fg light-grey ser sch				
232.0 - 255.0	Fg grey-grn chl-ser sch (tuff) with gradual gradation toward grn sch				

	From	To	C.L.	Calc. Grade Uncut
	182.0	228.0	46.0	.36
Including	196.0	210.0	14.0	.56

Ft.	Dip Angle Read.	Corrected Read.
255'	57°	53°

SHEET No. 2

HOLE No. U-P 612

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
255.0 - 262.0	f.g. grs sch, variol resid				
262.0 - 286.0	gry comp chl-ser sch				
286.0 - 311.5	Lt gry ser sch, few qutz strs				
311.5 - 318.0	40% qutz, silic, py, aspy, sp, retic carb	6926	6.5	.93	6.045
318.0 - 323.0	30% and as above	6927	5.0	.12	.600
323.0 - 328.0	40% and as above	6928	5.0	1.02	5.100
328.0 - 332.0	As above; gry min	6929	4.0	1.27	5.080
332.0 - 339.0	qutz lenses in ser sch, minor min	6930	7.0	1.05	7.350
339.0 - 346.0	30% qutz, silic, py, aspy	6931	7.0	1.83	12.810
346.0 - 351.0	60% qutz, py, aspy, sp	6932	5.0	.24	1.200
351.0 - 356.0	As above	6933	5.0	.64	3.200
					41.385
356.0 - 362.0	gry ser sch	6934	4/6.0	.06	
362.0 - 366.0	As above	6935	4.0	.02	
366.0 - 371.5	As above	6936	5.5	.07	
371.5 - 375.5	20% qutz, py, aspy	6937	4.0	.99	
375.5 - 405.0	gry ser sch, becoming grn towards 4050				

From	To	C.L.	Grade
311.5	356.0	44.5	.93
371.5	375.5	4.0	.99

SHEET No. Deepened

HOLE No. U-8619

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-2 618
BEARING W60°
DIP AT COLLAR -30°
LENGTH 278.0

LAT. 12,237
DEP. 7,739
ELEV. 5,436.6

DATE COMPLETED Sept. 29/49
PURPOSE Deep Level Expl.

SHAFT 2
LEVEL 575
WORKING B403W-Dr.
SECTION 1495W

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 74.0	Fg grey-grn chl-ser sch with carb lenses and traces of epidote				
74.0 - 161.0	Fg grey-grn grs sch with local sections of epidote and carbonate				
161.0 - 201.0	Fg dark grey ser sch (tuff) with fair local banding, scattered qutz-lenses, min. with py T. S. 191.0 - 195.0	6625	4.0	.28	
201.0 - 220.0	Mg granular ser sch with carbonate disseminated throughout				
220.0 - 242.0	Very fg. slatey ser sch, 1 ft. core ground at 231.0, section from 233.0 to 242.0 is almost identical to slate band in B303W-XC on 435 Level (highly developed) - remaining 13 ft. of section has disseminated slate-like material T. S. -- 222.0 - 228.0 228.0 - 242.0	6651 6652	6.0 4.0	.05 .06	
242.0 - 248.0	30% blue qutz with minor carb, min with py aspy and minor sph, local sections slate-like and barren of quartz	6632	6.0	.23	
247.0 - 278.0	dk grey ser sch., bx tx., local impreg py (tuffac.)				

From	To	C.L.	Calc. Grade Uncut
191.0	195.0	4.0	.28
242.0	248.0	6.0	.23

Dip Tests

Depth	Reading	Corrected Read.
150	29°	25°
270	23°	20°

Logged by T.A.H.

Hole No. U-2 618

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B 617
BEARING N60W
DIP AT COLLAR -60°
LENGTH 328.0

LAT. 13,143.6
DEP. 7,692.7
ELEV. 5,435.0

DATE COMPLETED
PURPOSE Deep Level Expl.

SHAFT 2
LEVEL 575
WORKING 2403W-Ex.
SECTION 1400W

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 1.0	casing				
1.0 - 32.0	Fg gray ser sch with local qutz-carb lenses				
32.0 - 37.0	40% qutz-carb in ser sch min with py and minor aspy	6620	5.0	.36	
37.0 - 42.5	60% qutz with minor carb in ser sch well min with py aspy and sph	6621	5.5	.42	
42.5 - 48.0	Qutz-carb lenses in ser sch spar min with py	6622	5.5	.03	
48.0 - 104.0	Fg light grey cherty-like (local banding) ser sch				
104.0 - 115.0	Fg grey-grn ser sch				
115.0 - 118.0	30% qutz-carb lenses in ser sch well min,with py and aspy	6623	3.0	.51	
118.0 - 122.0	as above	6624	4.0	.14	
122.0 - 128.0	20% qutz-carb lenses in ser sch min with py	6626	6.0	.44	
128.0 - 133.0	as above but with minor aspy and sph	6627	5.0	.03	
133.0 - 137.0	as above	6628	4.0	1.51	
137.0 - 142.0	40% qutz-carb lenses and as above	6629	5.0	1.70	
142.0 - 144.5	70% qutz with min carb spar min with py, aspy and minor sph	6630	2.5	1.13	

Logged by J.A.F.

Hole No. U-B 617

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
144.5 - 173.0	Tg grey cherty like (tuff?) ser sch with local carb lenses				
173.0 - 177.0	20% bx like qutz with carb rim with py	6631	4.0	.21	
177.0 - 201.0	Tg dark grey ser sch				
201.0 - 225.0	Tg grey mottled ser sch				
225.0 - 312.0	Tg grey-grn ser sch; grun tx., silic 298.0 to 309.0.,				
312.0 - 314.5	30% qutz-carb., py, sery	6633	2.5	.23	
314.5 - 328.0	grun chl grs sch w tan lent alt fl				

Dip Tests

Depth	Angle Read.	Corrected Angle
200'	58°	55°
300'	44°	40°

From	To	C.L.	Calc. Grade Uncut
32.0	42.5	10.5	.39
115.0	144.5	29.5	.76
173.0	177.0	4.0	.21
312.0	314.5	2.5	.23

SHEET No. 2

HOLE No. U-3617

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8 616
BEARING N60W
DIP AT COLLAR -60
LENGTH 315.0

LAT. 13,237
DEP. 7,730 330W
ELEV. 5,436.6

DATE COMPLETED Sept. 26, 1949
PURPOSE Deep Level Expl.

SHAFT 2.
LEVEL 575
WORKING B-403N
SECTION 1495N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 2.0	as				
2.0 - 59.0	grn grs sch., local chl-ser., mottled w qutz to 37.0.,				
59.0 - 107.0	gry ser sch; buff & chty tx after 71.0				
107.0 - 111.0	Qutz-carb lenses in ser sch mod with py	6594	4.0	.13	.520
111.0 - 116.5	70% qutz-with minor carb min with py, sspy and minor gray min and sph	6595	5.5	.47	2.585
116.5 - 121.0	20% qutz-carb lenses in ser sch well min with py and minor sspy	6596	4.5	.23	1.035
121.0 - 126.0	as above	6597	5.0	.38	1.900
126.0 - 131.0	as above	6598	5.0	.23	1.150
131.0 - 136.0	as above	6599	5.0	.29	1.450
136.0 - 142.0	as above but with minor sph	6600	6.0	.34	2.040
142.0 - 146.0	20% qutz-carb leases spar min with py and minor sspy	6601	5.0	.19	.950
146.0 - 151.0	as above	6602	5.0	.14	.700
151.0 - 156.0	as above	6603	5.0	.06	.300
156.0 - 161.0	as above	6604	5.0	.07	.350
161.0 - 166.0	as above	6605	5.0	.17	.850

Logged by J.D.B.

Hole No. U-8 616

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
166.0 - 171.0	as above but with minor sph	6606	5.0	.68	3.400
171.0 - 176.0	as above	6607	5.0	.07	.350
176.0 - 181.0	40% qutz-carb min, with py and aspy	6608	5.0	.18	.900 / 18.480
181.0 - 187.0	Fg ser sch with local qutz-carb lenses	6609	6.0	.01	
187.0 - 193.0	Qutz-carb lenses in ser sch spar min with py	6610	6.0	.01	
193.0 - 200.0	as above	6611	7.0	.03	
200.0 - 204.0	60% qutz-carb in ser sch min with py aspy and minor sph	6612	4.0	.37	
204.0 - 210.0	20% qutz-carb lenses and as above, 1 ft. core ground	6613	5.0/6.0	.01	
210.0 - 215.0	as above but spar min	6614	5.0	.07	
215.0 - 236.0	Mg gray compact ser sch with local qutz-carb lenses and mag min				
236.0 - 265.0	Very fg gray ser sch with traces of banding throughout				
265.0 - 283.0	Fg gray-grn chl-ser sch				
283.0 - 285.0	20% bx like qutz in ser sch min with py	6615	2.0	.05	
285.0 - 295.0	Fg gray-grn chl-ser sch				
295.0 - 315.0	Fg gray-grn chl-ser sch with local brown alt. flecks, fine fragments in spots suggestive of possible tuff				

From	To	C.L.	Calc. Grade Uncut
107.0	[illegible]	[illegible]	[illegible]
200.0	204.0	4.0	.37

SHEET No. 2

HOLE No. U-7 616

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B 615
BEARING ---
DIP AT COLLAR [illegible]
LENGTH [illegible]

LAT. 13,141.0
DEP. 7,698.0
ELEV. 5,436.3

DATE COMPLETED Sept. 26, 1949
PURPOSE Deep Level Expl.

SHAFT 2
LEVEL 575
WORKING B-40SW
SECTION 1400W

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
[illegible] - 19.0	buff-gxy chl-ser sch., loc mot w qutz.,				
19.0 - 24.5	60% dk qutz richly min in places w sp & gxy min	6575	5.5	1.23	
24.5 - 30.0	qutz lenses in buff ser sch., py; minor aspy	6576	6.5	.31	
30.0 - 35.0	as above	6577	5.0	.09	
35.0 - 40.0	30% qutz-carb & as above	6578	5.0	2.29	
40.0 - 45.0	as above	6579	5.0	.61	
45.0 - 50.0	as above	6580	5.0	.26	
50.0 - 55.0	as above	6581	5.0	.40	
55.0 - 60.0	as above but with increasing py min	6582	5.0	.19	
60.0 - 66.0	20% qutz-carb lenses in ser sch min with py	6583	6.0	.28	
66.0 - 72.0	as above	6584	6.0	.26	
72.0 - 77.0	as above but with increased py min and minor sph	6585	5.0	.18	
77.0 - 82.0	as above	6586	5.0	.18	
82.0 - 87.0	as above	6587	5.0	.41	

Logged by J.D.B.

Hole No. U-B615

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
87.0 - 91.0	60% qutz with minor carb sper min with py aspy and sph., speck of V.G. at 90.0	6588	4.0	1.05	
91.0 - 97.0	50% qutz-carb leases min with py and aspy	6589	6.0	1.28	
97.0 - 103.0	as above but with decreasing min	6590	6.0	.63	
103.0 - 109.0	as above, possibly fault at 104.5 bx like qutz-carb	6591	6.0	.29	
109.0 - 113.0	20% qutz-carb and as above	6592	4.0	.02	
113.0 - 117.0	V fg dark gray compact ser sch min with py, minor bx qutz (tuff?)	6593	4.0	.06	
117.0 - 122.0	as above	6616	5.0	.08	
122.0 - 128.0	as above	6617	6.0	.02	
128.0 - 134.0	as above but with increasing py min	6618	6.0	.08	
134.0 - 139.0	30% qutz-carb leases min with py and minor aspy and sph	6619	5.0	.13	
139.0 - 200.0	V fg light gray ser sch with cherty texture and with fine local banding, lenses of qutz-carb in sections with neg min				
200.0 - 233.0	Fg gray ser sch				
233.0 - 258.0	gradual gradation from ser sch to chl ser sch				

	From	To	C.L.	Calc. Grade Uncut
	19.0	109.0	90.0	.58
incl.	(19.0	45.0	26.0	1.29
	(82.0	109.0	27.0	.72

SHEET No. 2

HOLE No. U-8615

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
	Deepening of U - B 615				
258.0 - 370.0	Fg gray compact ser sch with a few local carb lenses, local short sections of chl-ser sch.				
370.0 - 400.0	F to mg gray-grn ser sch				
400.0 - 409.0	Fg light-gray ser sch.				
403.0 - 413.0	40% qutz lenses in ser sch min with py aspy and minor gray min and sph	6818	4.0	.06	
413.0 - 421.0	30% qutz-carb lenses and as above, 4 ft. of core lost.	6819	4.0/8.0	.11	.880
421.0 - 424.0	As above but with increased min	6820	3.0	.16	.480
424.0 - 427.0	50% qutz-carb in ser sch well min with py and minor aspy	6821	3.0	.14	.420
427.0 - 430.0	30% qutz-carb and as above	6822	3.0	.07	
430.0 - 442.0	Fg dark gray compact chl-ser sch				
442.0 - 503.0	Dk buff mottled chty tx compact ser-sch T.S. 498.0 - 499.0	6839	1.0		

From	To	C.L.	Grade
413.0	427.0	14.0	.12

Dip Tests

At	Angle Read	Corrected Angle
150'	80	77
300'	77	74
450'	75	73

SHEET No._____ HOLE No. U-B615

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B 614
BEARING --
DIP AT COLLAR -90°
LENGTH 248.0

LAT. 12235.1
DEP. 7732.5
ELEV. 5436.6

DATE COMPLETED Sept. 22, 1949
PURPOSE Exploration

SHAFT 2
LEVEL 575
WORKING B403N-Dr
SECTION 1495N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 11.0	Fg gray ser sch				
11.0 - 32.0	Fg grey-grsn chl-ser sch				
32.0 - 60.0	M to fg grn grs sch with local carb lenses				
60.0 - 67.0	Fg chl-ser sch				
67.0 - 95.0	Fg grey ser sch with local carb lenses				
95.0 - 100.0	20% qutz-carb lenses in ser sch spar min with py	6558	5.0	.10	
100.0 - 105.0	As above with increased min				
105.0 - 110.0	50% qutz with minor carb in ser sch min with py and minir aspy	6559	5.0	.71	
110.0 - 116.0	as above	6560	5.0	.47	
116.0 - 120.0	30% qutz-carb lenses in ser sch well min with py and minor aspy	6561	6.0	.13	
120.0 - 124.0	as above	6562	4.0	.06	
124.0 - 128.0	as above but with increasing carb	6563	4.0	.73	
128.0 - 132.0	as above	6564	4.0	.44	
132.0 - 136.0	Qutz-carb lenses in ser sch	6565	4.0	1.18	
136.0 - 190.0	Fg gray ser sch, banded appearance around 140.0, local carb lenses with neg min	6566	4.0	.09	

Logged by J.A.H.

Hole No. U-B 614

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
190.0 - 208.0	Fg grey-grn chl-ser sch				
208.0 - 229.0	Fg grn grs sch				
229.0 - 242.0	M to fg grn sch to mass grs				
242.0 - 248.0	dk buff comp ser sch				

From	To	C.L.	Calc.Grade
100.0	110.0	10.0	.59
120.0	132.0	12.0	.78

SHEET No. 2

HOLE No. U-B 614

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B 613
BEARING --
DIP AT COLLAR -90°
LENGTH 220.0

LAT. 13191.2
DEP. 7717.2 3/9W
ELEV. 5436.5

DATE COMPLETED Sept. 22, 1949
PURPOSE Exploration

SHAFT 2
LEVEL 575
WORKING B403N-Tr
SECTION 1450N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 2.0	casing				
2.0 - 22.0	F g gray ser sch				
22.0 - 41.0	F g gray chl-ser sch				
41.0 - 76.0	F g gray ser sch with local carb lenses				
76.0 - 90.0	F g gray-grn chl-ser sch				
90.0 - 97.0	Qutz-carb lenses in ser sch, 1 ft. core ground min with py and aspy	6567	6.0/7.0	.49	
97.0 - 102.0	30% qutz lenses with minor carb min with py and aspy	6568	5.0	.30	
102.0 - 109.0	as above, 2' core ground	6569	5.0/7.0	.42	
109.0 - 115.0	as above	6570	6.0	.04	
115.0 - 119.0	as above but with increasing min	6571	4.0	.15	
119.0 - 122.0	80% blue qutz min with py, aspy and minor sph	6572	3.0	.39	
122.0 - 125.0	20% qutz-carb lenses in ser sch	6573	3.0	.09	
125.0 - 129.0	F g gray ser sch with local carb lenses	6574	4.0	.01	
129.0 - 153.0	F g gray ser sch with local qutz-carb lenses, suggestion of banding throughout				

Logged by J.A.H.

Hole No. U-B 613

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
153.0 - 180.0	F g gray-white ser sch				
180.0 - 205.0	F g gray-grn chl-ser sch				
205.0 - 220.0	M to fg grn gra sch				

From	To	C.L.	Calc.Grade
90.0	109.0	19.0	.34
115.0	122.0	7.0	.25

SHEET No. 2

HOLE No. U-B 613

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B 612
BEARING S60E
DIP AT COLLAR +45°
LENGTH 71.0

LAT. 12496.04
DEP. 7622.59
ELEV. 5439.0

DATE COMPLETED Sept. 16, 1949
PURPOSE 4th Level Expl.

SHAFT 2
LEVEL 575
WORKING B404N-Dr
SECTION 800N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 5.5	20% qutz-carb leases in ser sch min with py	6556	5.5	.01	
5.5 - 11.0	as above	6557	5.5	.10	
11.0 - 29.0	Fg gray-grn chl-ser sch				
29.0 - 50.0	Fg gray ser sch with local carb leases and neg min				
50.0 - 71.0	Fg gray-grn chl-ser sch approaching grs sch around 71.0				

Logged by J.A.H.

Hole No. U-B 612

GIANT YELLOWKNIFE GOLD MINES LIMITED

CORE RECORD

HOLE No. U-B 611
BEARING --
DIP AT COLLAR +90
LENGTH 75.0

LAT. 12498.8
DEP. 7619.0
ELEV. 5441.0

DATE COMPLETED Sept. 15/49
PURPOSE 4th Level Expl.

SHAFT 2
LEVEL 575
WORKING B-404N
SECTION 800N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 54.0	dk gry chl-ser sch., local qutz strs & lenses				
54.0 - 66.0	Fg gray ser sch with local carb lenses and neg min				
66.0 - 75.0	Fg gray-grn chl-ser sch; 1 ft. core ground at 63.0				

Logged by J.D.B.

Hole No. U-B 611

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B 610
BEARING N60W
DIP AT COLLAR -65
LENGTH 69.0

LAT. 12629.90
DEP. 7391.53 3Z0W.
ELEV. 5900

DATE COMPLETED
PURPOSE B-218 Stope Def.

SHAFT 2
LEVEL 100
WORKING B-110N
SECTION 800N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 30.0	m.g. gry-grn grs sch				
30.0 - 69.0	m.g. gry-grn chl-ser sch				

Logged by J.D.B.

Hole No. U-B 610

GIANT YELLOWKNIFE GOLD MINES LIMITED

CORE RECORD

HOLE No. U-B 609

BEARING --

DIP AT COLLAR -90°

LENGTH 57.0

LAT. 12628.0

DEP. 7394.5 3/8W

ELEV. 5900.8

DATE COMPLETED Sept. 9/49

PURPOSE Ore Definition

SHAFT 2

LEVEL 100'

WORKING B110N-Dr.

SECTION 800N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 20.0	F g grn grs sch				
20.0 - 49.0	F g gray-grn chl-ser sch, 2' core ground around 49.0				
49.0 - 57.0	F g gray ser sch with carb lenses and neg min, 2' core ground around 57.0				

Logged by J. A. H.

Hole No. U-B 609

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B 608
BEARING N60W
DIP AT COLLAR +50°
LENGTH 86.0

LAT. 12640.0
DEP. 7424.0
ELEV. 5758.0

DATE COMPLETED Sept. 13/49
PURPOSE Ore Definition

SHAFT 2
LEVEL 250
WORKING B202N-Dr.
SECTION 825N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 1.0	casing				
1.0 - 5.0	50% qutz and minor carb well min with py and aspy	6527	4.0	.99	3.960
5.0 - 11.0	30% qutz-carb min with py aspy and minor sph	6528	6.0	.25	1.500
11.0 - 17.0	As above	6529	6.0	3.66	21.960
17.0 - 22.0	As above	6530	5.0	1.30	6.500
22.0 - 28.0	50% qutz-carb in ser sch well min with py and minor aspy	6531	6.0	.46	2.760
28.0 - 34.0	As above	6532	6.0	.64	3.840
34.0 - 39.0	As above	6533	5.0	.41	2.050
39.0 - 43.0	As above	6534	4.0	.69	2.760
43.0 - 48.0	80% blue qutz with minor carb min with py, minor aspy, sph and gray min, fine V.G. at 47.0	6535	5.0	3.37 4.04	18.500
48.0 - 52.0	As above	6536	4.0	.25 .26	1.000
52.0 - 56.0	As above	6537	4.0	.25	1.000
56.0 - 60.0	30% qutz-carb lenses spar min with py and aspy	6538	4.0	.05	

Logged by J.A.H.

Hole No. U-B 608

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
60.0 - 65.0	Qutz-carb lenses in ser sch spar min with py and aspy	6539	5.0	.06	
65.0 - 86.0	Fg gray ser sch with local carb lenses and neg min				

From	To	C.L.	Grade
1.0	56.0	55.0	1.19

SHEET No. 2

HOLE No. U-B 608

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B 607
BEARING --
DIP AT COLLAR -90°
LENGTH 226.0

LAT. 12498.8
DEP. 7619.0
ELEV. 5433.1

DATE COMPLETED Sept. 15, 1949
PURPOSE Ore Exploration below 575 Level

SHAFT 2
LEVEL 575
WORKING B404N-Dr.
SECTION 800N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 2.0	casing				
2.0 - 5.5	20% qutz-carb lenses in ser sch min with py and aspy	6524	3.5	.04	
5.5 - 10.0	As above	6525	4.5	.02	
10.0 - 12.5	As above but with increasing min	6526	2.5	.21	
12.5 - 54.0	Fg gray ser sch with local carb lenses and neg min				
54.0 - 58.0	Qutz-carb lenses in ser sch min with py	6540	4.0	.01	
58.0 - 91.0	Fg gray ser sch with local sections of chl-ser sch				
91.0 - 95.0	Qutz-carb lenses in ser sch minwith py	6541	4.0	.05	
95.0 - 100.0	As above but with increasing min	6542	5.0	.06	
100.0 - 106.0	As above	6543	6.0	.11	
106.0 - 112.0	20% qutz-carb lenses in ser sch min with py and aspy	6544	6.0	.07	
112.0 - 118.0	As above	6545	6.0	.74	
118.0 - 121.0	Fg ser sch with local carb lenses	6546	3.0	.04	
121.0 - 148.0	Fg gray ser sch				
148.0 - 153.0	20% qutz-carb lenses in ser sch min with py and minor aspy	6547	5.0	.32	

Logged by J.A.H.

Hole No. U-B 607

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
163.0 - 159.0	As above	6548	6.0	.50	
159.0 - 163.0	70% qutz with minor carb well min with py and minor aspy and sph	6549	4.0	.38	
163.0 - 168.0	As above	6550	5.0	.25	
168.0 - 173.0	40% qutz-carb lenses in ser sch spar min with py and aspy	6551	5.0	.07	
173.0 - 177.0	20% qutz-carb lenses and as above	6552	4.0	.02	
177.0 - 188.0	Fg gray ser sch				
188.0 - 193.0	Qutz-carb lenses in ser sch min with py	6553	5.0	.03	
193.0 - 197.0	As above	6554	4.0	.02	
197.0 - 201.0	As above	6555	4.0	.01	
201.0 - 226.0	Dk gry to buff chl-ser sch				

From	To	C.L.	Grade
10.0	12.5	2.5	.21
112.0	118.0	6.0	.74
148.0	168.0	20.0	.37

SHEET No. 2

HOLE No. U-B 607

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B 606
BEARING N63W
DIP AT COLLAR Hor.
LENGTH 40.0

LAT. 12222.52
DEP. 7482.96
ELEV. 5664.8

DATE COMPLETED Sept. 10/49
PURPOSE B306 Stope ore Def.

SHAFT 2
LEVEL 425' +
WORKING B306 Stope
SECTION 493N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 5.0	40% qutz-carb lenses min with py, aspy and minor sph	6520	5.0	.36	
5.0 - 7.5	20% qutz-carb lenses spar min with py and aspy	6521	2.5	.02	
7.5 - 30.0	F g gray ser sch with local carb lenses				
30.0 - 40.0	F g gray-grn chl-ser sch				

From	To	C.L.	Grade
0.0	5.0	5.0	.36

Logged by J.A.H.

Hole No. U-B 606

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B 605
BEARING N60W
DIP AT COLLAR -45°
LENGTH 134.0

LAT. 12542.62
DEP. 7642.11
ELEV. 5433.5

DATE COMPLETED
PURPOSE Fourth level Expl.

SHAFT 2
LEVEL 575
WORKING B404N-Dr.
SECTION 850N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 23.0	F g gray-grn chl-ser sch				
23.0 - 52.0	F g gray ser sch with local carb lenses and neg min, ground 1' of core at 50.0				
52.0 - 77.0	F g gray-grn chl-ser sch				
77.0 - 116.0	As above but with carb lenses and neg min				
116.0 - 134.0	F g gray ser sch with two short qutz-carb sections spar min with py				
	126.0 - 127.5	6522	1.5	.04	
	131.0 - 132.5	6523	1.5	.01	

Logged by J. A. H.

Hole No. U-B 605

GIANT YELLOWKNIFE GOLD MINES LIMITED

CORE RECORD

HOLE No. U-B 604
BEARING N69W
DIP AT COLLAR -60°
LENGTH 40.0

LAT. 12262.82
DEP. 7498.41
ELEV. 5645.13

DATE COMPLETED Sept. 10/49
PURPOSE B306 Stope Ore def.

SHAFT 2
LEVEL 425+
WORKING B306 Stope
SECTION 536N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 40.0	F g gray ser sch with short local sections of chl-ser sch, scattered carb lenses with neg min; 2' of core ground at 22.0 and 1' ground at 29.0				

Logged by J. A. H.

Hole No. U-B 604

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B 603
BEARING S60E
DIP AT COLLAR -60°
LENGTH 133.0

LAT. 12,538.26
DEP. 7,649.66
ELEV. 5,433.5

DATE COMPLETED
PURPOSE eth Level Expl.

SHAFT 2
LEVEL 575
WORKING B404N-Dr.
SECTION 850N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 3.0	casing				
3.0 - 10.0	Fg gray chl-ser sch				
10.0 - 15.0	Qutz-carb lenses in ser sch spar min with py	6509	5.0	.01	
15.0 - 21.0	As above	6510	6.0	.06	
21.0 - 26.0	20% qutz-carb in ser sch min with py and aspy				
26.0 - 31.0	As above with increasing min	6511	5.0	.06	
31.0 - 37.0	40% qutz-carb well min with py and minor aspy				
37.0 - 42.0	As above	6515	5.0	.18	
42.0 - 48.0	As above	6516	6.0	.17	
48.0 - 52.0	As above	6517	4.0	.59	
52.0 - 55.5	70% qutz with minor carb min with py, aspy and minor sphalerite	6518	3.5	1.05	
55.5 - 59.0	30% bx-like qutz with minor carb min with py and aspy	6519	3.5	.25	
59.0 - 67.0	Fg gray ser sch				
67.0 - 87.0	Fg gray-grn chl-ser sch				

Logged by J.A.H.

Hole No. U-B 603

N.M.P.-F3741-S

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
87.0 - 120.0	M to fg grn grs-sch				
120.0 - 133.0	M to fg grn sch to massive grs with prominent snfl alteration				

	From	To	C.L.	Calc.Grade
	31.0	48.0	17.0	.15
	48.0	59.0	11.0	.63
alt.-	31.0	59.0	28.0	.33

SHEET No. 2

HOLE No. U-B 603

NOTE: #601 & #602 MISSING!