

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-C1163
BEARING S60E
DIP AT COLLAR 64
LENGTH 182

LAT. 11216
DEP. 7042.5
ELEV. 5258
DATE COMPLETED _____
PURPOSE Dev

SHAFT 3
LEVEL 750
WORKING C-704N
SECTION 600S

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS	
				OZ./TON	OZ./TON
0-1.0	cs				
1.0-69.0	v.f.g. lt grn grs w retic ep threads; suggest of variol after 42.0				
69.0-88.0	f.g. lt grn grs sch				
88.0-95.5	f.g. gry chl-ser sch merg w above				
95.5-132.0	gry-buff ser sch; 1/4" gouge 110.0				
132.0-138.0	40% qtz in yellow silic ser sch; py, local heavy gry min & sp	12260	6.0	1.20	
138.0-143.0	buff ser sch				
143.0-150.0	buff ser sch; qtz carb lenses, minor py	12262	7.0	.05	
150.0-155.0	25% qtz-carb; py, minor aspy	12263	5.0	.27	1.35
155.0-162.0	20% qtz-carb; py, minor aspy	12264	7.0	.26	1.82
					3.17
162.0-168.0	buff-gry ser-sch; qtz-carb lenses; py	12265	6.0	.13	
168.0-174.0	gry ser-sch; minor qtz-carb lenses, no py				
174.0-182.0	grn-gry ser-sch w add streak chl				

DIP TEST

From	To	C.L.	Grade	Depth	Read	Correct
132.0	138.0	6.0	1.20	150'	64°	60°
150.0	162.0	12.0	0.26			

Logged by MR. JDB

Hole No. U-C1163