GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B855
BEARING -
DIP AT COLLAR + 90
LENGTH 36.0
LAT. 12593.5
DEP. 7652.5
ELEV. 5442
DATE COMPLETED
PURPOSE A.S.D. Zone Def.
SHAFT 2
LEVEL 575
WORKING B-404 N
SECTION 900 N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 1.0	Cs.				
1.0 - 10.0	gry ser sch w gutz lenses				
10.0 - 23.0	f.g. grn-gry chl-ser sch				
23.0 - 36.0	f.g. grn grs sch				

Logged by JDB

Hole No. U-B855

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B854
BEARING N60W
DIP AT COLLAR -18½
LENGTH 234.0

LAT. 13510.76
DEP. 7565.54
ELEV. 5440

DATE COMPLETED
PURPOSE B-409 Ore Def.

SHAFT 2
LEVEL 575
WORKING B-403N
SECTION 1650N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 128.0	f.g. sch grs; chty-ep hem sect; local flow bxtx.				
128.0 - 133.0	f.g. grn grs sch				
133.0 - 138.5	dk buff-gry ser sch				
138.5 - 142.0	dk qutz lenses in ser sch, minor min (py)	8285	3.5	.20	
142.0 - 147.0	As above	8286	5.0	.20	
147.0 - 154.0	As above w short ore-type sect	8287	7.0	.22	
154.0 - 161.0	20% qutz & as above	8288	7.0	.26	
161.0 - 166.0	qutz & mosaic carb lenses in ser sch; minor min (py)	8289	5.0	.05	
166.0 - 168.0	As above	8301	2.0	.47	
168.0 - 175.0	dk ser sch; neg qutz & min	8302	7.0	.01	
175.0 - 182.0	As above	8303	7.0	.08	
182.0 - 189.0	50% dk qutz; gry min, sp, tr. v.g.	8304	7.0	(1.47 (1.42	
189.0 - 196.0	qutz bands in ser sch; local min	8305	7.0	0.20	

Logged by JOH

Hole No. U-B854

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
196.0 - 203.0	As above	8306	7.0	0.24	
203.0 - 210.0	As above	8307	7.0	0.40	
210.0 - 217.5	60% qutz richly min w gry min, sp; & v.g.	8308	5.5/7.5	(2.61) (2.94)	
217.5 - 223.5	Silic ser sch, py, po	8309	6.0	0.50	
223.5 - 228.5	70% wte gran qutz; sparing min; tr. v.g.	8310	5.0	(0.96) (1.05)	
228.5 - 234.0	gry ser sch				

From	To	C.L.	Grade
138.5	168.0	29.5	.21
160.0	162.0	14.0	.04
162.0	228.5	[illegible]	.86

Dip Tests

Depth	Read	Correct
150	21	18
230	18	15

SHEET No. 2

HOLE No. [illegible]

GIANT YELLOWKNIFE GOLD MINES LIMITED

CORE RECORD

HOLE No. U - B 854
BEARING N 60 W
DIP AT COLLAR - 18½
LENGTH 334

LAT. 13510.76
DEP. 7565.54
ELEV. 5440

DATE COMPLETED
PURPOSE Ore Def.

SHAFT B
LEVEL 575
WORKING B - 403 N
SECTION 1650 N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
234.0 - 236.0	ser sch w qtz carb lenses: minor min	10864	2.0	.11	
236.0 - 242.0	qtz carb lenses in ser sch: py minor aspy	10875	5.0	.08	
			6.0		
242.0 - 246.0	lt gry ser sch w tan fl				
246.0 - 278.0	dk gry grs sch w numerous small carb lenses				
278.0 - 298.0	dk gry sch grs w ep				
298.0 - 334.0	as above but w lt gry fl				

Dip Test

Depth	Read	Corr.
330	18	14

Logged by A.M.

Hole No. U B 854

GIANT YELLOWKNIFE GOLD MINES LIMITED

CORE RECORD

HOLE No. U-B853

BEARING --

DIP AT COLLAR -90

LENGTH 65.0

LAT. 12651

DEP. 7654.5 /03W

ELEV. 5433

DATE COMPLETED

PURPOSE ASD Zone Def.

SHAFT 2

LEVEL 575

WORKING B-404N

SECTION 950N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 2.0	Cs.				
2.0 - 9.0	Silic ser sch; sparing min	8271	7.0	.01	
9.0 - 16.0	20% qutz; py, aspy; tr gry min	8272	7.0	.24	
16.0 - 23.0	qutz leases in ser sch; minor min	8273	7.0	.02	
23.0 - 30.0	As above w less qutz	8274	7.0	.02	
30.0 - 37.0	As above	8275	7.0	.02	
37.0 - 44.0	Fissile ser sch; abrupt cont. 44.0				
44.0 - 65.0	Comp dk gran chl-ser sch				

From	To	C.L.	Grade
9.0	16.0	7.0	.24

Logged by JDB

Hole No. U-B853

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B352
BEARING -
DIP AT COLLAR + 90
LENGTH 63.0
LAT. 12651
DEP. 7654.5 103W
ELEV. 5441
DATE COMPLETED
PURPOSE ASD Zone Def.
SHAFT 2
LEVEL 575
WORKING B-404 N
SECTION 950 N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 1.0	Cs.				
1.0 - 63.0	dk ser'c chl sch; sect gutz-carb				
	chty sect; t.s. 21.0 - 22.0	8269	1.0	.06	
	t.s. 32.0 - 35.0	8270	3.0	.03	
	merg w grs sch after 37.0				

Logged by JDB

Hole No. U-B852

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8851
BEARING N 60 W
DIP AT COLLAR - 30
LENGTH 181.0

LAT. 13347.54
DEP. 7747.93
ELEV. 5438

DATE COMPLETED
PURPOSE Ore Def.

SHAFT 2
LEVEL 575
WORKING B-403 N
SECTION 1600 N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 146.0	f.g. sch grs; hem fract; minor ep; chty ep sect after 50.0				
146.0 - 157.0	f.g. gry-grn grs sch				
157.0 - 169.5	f.g. dk buff ser sch				
169.5 - 177.0	minor gutz w py in dk ser sch	8263	7.5	.18	1.350
177.0 - 182.0	as above w increas gutz	8264	5.0	.30	1.500
182.0 - 187.0	as above w short sect ore type	8265	5.0	.22	1.100
187.0 - 193.0	as above	8266	6.0	.29	1.740
193.0 - 199.0	as above	8267	6.0	.30	1.800
199.0 - 205.5	20% gutz; sparing py; tr gry min	8268	6.5	(.50 (.40	3.185
205.5 - 210.0	40% gutz; gry min, spy	8276	4.5	.89	4.005
210.0 - 217.0	gutz lenses in dk gry ser sch; local min	8277	7.0	.23	1.610
217.0 - 222.0	as above	8278	5.0	.23	1.150
222.0 - 228.0	as above	8279	6.0	.22	1.320

Logged by JDB

Hole No. U-8851

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
228.0 - 233.0	20% gutz; local min	8280	5.0	.38	1.900
233.0 - 238.0	as above	8281	5.0	.05	.250
238.0 - 245.0	as above	8232	7.0	.35	2.450
245.0 - 273.0	buff comp ser sch t.s. 245.0 - 248.0	8283	3.0	.07	23.360
273.0 - 281.0	f.g. grn gran grs sch				

From	To	C.L.	Grade
169.5	245.0	75.5	.30

Dip Test

Depth	Read.	Correct.
150'	28½	~~25~~ 22½

SHEET No. 2

HOLE No. U-B851

GIANT YELLOWKNIFE GOLD MINES LIMITED

CORE RECORD

HOLE No. U - B 851
BEARING N 60 W
DIP AT COLLAR -30
LENGTH 387

LAT. 13510.76
DEP. 7565.54
ELEV. 5440

DATE COMPLETED
PURPOSE Dev.

SHAFT B
LEVEL 575
WORKING B - 403 N
SECTION 1600 N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
281.0 - 294.0	dk grn grs sch w a few scattered gry fl				
294.0 - 352.0	dk grn sch grs w considerable ep				
352.0 - 365.0	dk grn grs sch w lt gry fl				
365.0 - 387.0	dk grn sch gr w ep and lt gry fl				

Dip Test

Depth	Read	Corr
385	11	8½

Logged by Deepened

Hole No. U-B 851

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B850
BEARING -
DIP AT COLLAR - 90
LENGTH 99.0

LAT. 12709
DEP. 7554.5 132W
ELEV. 5434

DATE COMPLETED
PURPOSE ASD Zone Def.

SHAFT II
LEVEL 575
WORKING B-404 N
SECTION 1000 N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 2.0	Cs				
2.0 - 5.0	20 % gutz well min w aspy	8253	3.0	.22	.660
5.0 - 10.0	30% and as above	8254	5.0	1.08	5.400
10.0 - 17.0	as above	8255	7.0	Lost (.38)	2.660
17.0 - 24.0	20% and as above	8256	7.0	.38	2.660
24.0 - 31.0	30% and as above	8257	7.0	.37	2.590
31.0 - 38.0	gutz lenses in silic ser sch; py	8258	7.0	.09	13.970
38.0 - 45.0	as above	8259	7.0	.07	
45.0 - 50.0	20% gutz; aspy	8260	5.0	.19	
50.0 - 56.0	gutz lenses in ser sch; minor min	8261	6.0	.05	
56.0 - 59.0	as above; decreas gutz	8262	3.0	.09	
59.0 - 77.0	gry chl-ser sch; broken core (fault?) 77.0; abrupt contact of shear zone				
77.0 - 99.0	grn grs sch				

From	To	C.L.	Grade
2.0	31.0	29.0	.48

Logged by JDB

Hole No. U-B850

GIANT YELLOWKNIFE GOLD MINES LIMITED

CORE RECORD

HOLE No. U-8849

BEARING S60E

DIP AT COLLAR + 45

LENGTH 42.0

LAT. 12706.68

DEP. 7658.26 12 7W

ELEV. 5441

DATE COMPLETED

PURPOSE A.S.D. Zone Def.

SHAFT 2

LEVEL 575

WORKING B-404N

SECTION 1000 N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 7.0	gutz lenses in ser sch; minor min	8252	7.0	.05	
7.0 - 21.0	gry-grn chl-ser sch;				
21.0 - 42.0	grn grs sch				

Logged by JDB

Hole No. U-8849

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B848
BEARING N 60 W
DIP AT COLLAR ∠ 45
LENGTH 42.0

LAT. 12711.08
DEP. 7550.64
ELEV. 5441

DATE COMPLETED
PURPOSE ASD Zone Def.

SHAFT II
LEVEL 575
WORKING B-404 N.
SECTION 1000 N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	GOLD ASSAYS OZ./TON
0 - 3.0	gry ser sch	8246	3.0	.03	
3.0 - 8.0	20% gutz; minor aspy	8247	5.0	.28	1.400
8.0 - 13.0	as above	8248	5.0	.29	1.450
13.0 - 17.0	as above	8249	4.0	.06	.240
17.0 - 22.0	gry ser sch; gutz lenses; neg min	8250	4.0	.01	3.090
22.0 - 42.0	gry ser sch; t.s. 36.0 - 39.5	8251	3.5	.10	

From	To	C.L.	Grade
3.0	17.0	14.0	.22

Logged by JDB

Hole No. U-B848

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B847
BEARING N 60 W
DIP AT COLLAR -50
LENGTH 75.0

LAT. 13716.44
DEP. 7708.10
ELEV. 5440

DATE COMPLETED
PURPOSE Ore Def.

SHAFT 2
LEVEL 575
WORKING B-409 N
SECTION 1900 N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 2.0	Cs				
2.0 - 8.0	30% gutz-carb; local heavy aspy	7232	6.0	.93	5.880
8.0 - 15.0	50% gutz carb; local dense aspy, gry min; sp	8238	7.0	(2.21 (2.38	16.030
15.0 - 20.0	as above	8239	5.0	18.54 (5.00)	25.000
20.0 - 25.0	dense grn-gry sch impreg wpy + po	8240	5.0	.11	.550
25.0 - 30.5	as above	8241	5.5	.11	.605
30.5 - 35.0	20 % gutz, aspy, py, po	8242	4.5	.31	1.395
35.0 - 40.0	as above	8243	5.0	.33	1.650
40.0 - 44.0	gutz lenses & as above	8244	4.0	.07	51.110
44.0 - 75.0	f.g. grn clastic sch t.s. 55.0 - 59.0	8245	4.0	.14	

From	To	C.L.	Grade
2.0	40.0	38.0	1.34

Logged by JDB

Hole No. U-B847

GIANT YELLOWKNIFE GOLD MINES LIMITED

CORE RECORD

HOLE No. U-B846
BEARING -
DIP AT COLLAR + 90
LENGTH 69.0
LAT. 12709
DEP. 7554.5
ELEV. 5442
DATE COMPLETED
PURPOSE A.S.D. Zone Def.
SHAFT 2
LEVEL 575
WORKING B-404 N
SECTION 1000 N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	GOLD ASSAYS OZ./TON
0 - 2.0	Cs				
2.0 - 7.0	buff ser sch; minor gutz	8233	5.0	.03	.04
7.0 - 12.5	20% gutz-carb; py, aspy	8234	5.5	.34	.29
12.0 - 23.0	buff ser sch; gutz-carb lenses; no min				
23.0 - 69.0	gry chl-ser sch; gutz-carb lenses; no sig min				

From	To	C.L.	Grade
7.0	12.5	5.5	.31

Logged by JDB

Hole No. U-B846

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8845 | SHAFT 2
BEARING 360N | LAT. 13710.99 | DATE COMPLETED | LEVEL 575
DIP AT COLLAR -70 | DEP. 7717.54 | PURPOSE Ore Def. | WORKING 8-409N
LENGTH 86.0 | ELEV. 5440 | SECTION 1900W

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 2.0	Os.				
2.0 - 9.0	40% qutz; py, aspy; local sp & gry min	8220	7.0	.86	6.020
9.0 - 16.0	60% qutz & as above	8221	7.0	1.86	12.810
16.0 - 23.0	50% qutz & as above, retic carb	8222	7.0	.69	4.830
23.0 - 30.0	20% qutz; aspy, heavy py	8223	7.0	.82	5.835
30.0 - 35.5	30% qutz; py	8224	5.5	.89	4.895
35.5 - 42.0	dk buff ser sch w qutz lenses; minor min	8225	6.5	.09	.585
42.0 - 47.5	As above	8226	5.5	.04	.220
47.5 - 52.0	20% qutz lenses, aspy	8227	4.5	1.24	5.580
52.0 - 58.0	30% qutz & as above	8228	6.0	1.89	11.340
58.0 - 65.0	qutz lenses in ser sch well min w aspy	8229	7.0	.78	5.460
65.0 - 72.0	silic ser sch; py, aspy	8230	7.0	.25	1.750
72.0 - 76.0	As above	8231	4.0	.63	2.520
76.0 - 86.0	grn chl-ser sch				61.750

Logged by MHS

From	To	C.L.	Grade
2.0	76.0	74.0	.83

Hole No. U-8845

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B844
BEARING N 60 W
DIP AT COLLAR - 70
LENGTH 111'

LAT. 13716.44
DEP. 7717.54
ELEV. 5439.5

DATE COMPLETED
PURPOSE Ore Def.

SHAFT 2
LEVEL 575
WORKING B-409 N
SECTION 1900 N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 2.0					
2.0 - 9.0	70% gutz; aspy, sp; gry min	8201	7.0	(1.67 (1.48	10.990
9.0 - 14.5	90% gutz & as above	8202	5.5	(.30 (.34	1.760
14.5 - 19.5	gutz lenses in silic ser sch; minor py	8203	5.0	(.10 (.08	.450
19.5 - 26.0	80% gutz richly min w dense aspy, gry min & sp	8204	6.5	(1.79 (1.61	12.750
26.0 - 34.0	gutz lenses in grn-buff ser sch; local dense aspy	8205	8.0	(.48 (.54	4.080
34.0 - 40.0	80% gutz; dense aspy; sparing sp & gry min	8206	6.0	(2.19 (2.48	13.980
40.0 - 45.0	20% gutz; py, minor aspy	8207	5.0	(.41 (.41	2.050
45.0 - 48.0	30% gutz & as above	8208	3.0	(3.60 (5.25	12.900
48.0 - 53.0	70% gutz; dense aspy; fine v.g.	8209	5.0	(3.42 (6.16	21,050

Logged by JDB

Hole No. U-B844

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
53.0 - 58.0	as above w coarser v.g.	8230	5.0	(3.27 (3.98	18.100
58.0 - 63.0	as above we gry min; sp, & coarse v.g.	8231	5.0	(3.18 (2.85	17.550
63.0 - 67.0	30% gutz; dense aspy; fine v.g., resid grn clastic sch	8232	4.0	(3.94 (4.34	16.560
67.0 - 70.0	80% gutz; sparing min	8213	1/3.0	(2.68 (4.81	11.220
70.0 - 76.0	60% gutz; dense aspy	8214	3/6.0	(1.80 (1.93	11.160
76.0 - 83.0	gutz lenses in grn sch; py, po	8215	7.0	(.11 (.08	.630
83.0 - 90.0	as above; more po	8216	7.0	(.11 (.11	.770
90.0 - 93.0	grn ser sch; po	8217	3.0	1.95	5.850
93.0 - 97.0	30% gutz lenses; aspy, po; pt well min w sp & gry min	8218	4.0	.76	3.040
97.0 - 101.5	20% gutz; aspy, po	8219	4.5	.11	.495
					164.385
101.5 - 111.0	comp grn ser sch w tan alt. fl.				

From	To	C.L.	Grade
2.0	101.5	99.5	1.65

SHEET No. 2

HOLE No. U-8844

N.M.P.-F3742-3 G-11

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8843 | SHAFT 2
BEARING S60E | LAT. 13670.03 | DATE COMPLETED | LEVEL 575
DIP AT COLLAR -30 | DEP. 7681.63 | PURPOSE Ore Def. | WORKING B-409N
LENGTH 50.0 | ELEV. 5442 | SECTION 1850N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 5.0	qutz lenses in silic ser sch, py	8199	5.0	.14	.700
5.0 - 12.0	30% qutz, py, aspy	8200	7.0	1.18	8.260
12.0 - 20.0	20% & as above	8153	7/8.0	1.04	8.320
20.0 - 25.0	qutz lenses in ser sch, minor min	8154	5.0	.20	1.000
25.0 - 30.0	As above	8155	5.0	.16	.800
30.0 - 35.0	As above	8156	5.0	.32	1.600
35.0 - 40.5	As above; 12" ore	8157	5.5	.70	3.850
40.5 - 43.0	buff ser sch				24.530
43.0 - 48.0	grn chl-ser sch merg w grs sch				
48.0 - 50.0	grn grs sch				

From	To	C.L.	Grade
0	40.5	40.5	.60

Logged by JDS

Hole No. U-8843

GIANT YELLOWKNIFE GOLD MINES LIMITED

CORE RECORD

HOLE No. U-8842 | SHAFT 2

BEARING N60W | LAT. 12319.11 | DATE COMPLETED | LEVEL 100

DIP AT COLLAR ∠20 | DEP. 7223.89 | PURPOSE Low angle ore Def. | WORKING B-205 st.

LENGTH 105.0 | ELEV. 5854 | SECTION 4460

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 6.0	80% qutz; sparing min, v.g.	8175	6.0	(1.82	1.71
6.0 - 11.0	qutz lenses in ser sch, minor min	8176	5.0	(1.63 .03	
11.0 - 31.0	dk chl-ser sch w barren qutz-carb lenses				
31.0 - 35.0	qutz lenses in ser sch, py aspy	8191	4.0	.16	.640
35.0 - 40.5	50% qutz; sparing min, v.g.	8192	5.5	(.07	.330
40.5 - 45.5	20% qutz; py, aspy	8193	5.0	(.06 .22	1.100
45.5 - 50.0	qutz lenses in ser sch; minor min	8194	4.5	.03	2.070
50.0 - 81.5	ser sch w qutz lenses; neg min				
81.5 - 86.0	60% qutz-carb; nls aspy	8195	5.5	.04	
86.0 - 91.0	40% & as above	8196	5.0	.03	
91.0 - 98.0	ser sch w sect barren qutz-carb	8197	7.0	.05	
98.0 - 105.0	50% qutz; aspy; local sp & gry min	8198	7.0	.19	

From	To	C.L.	Grade
0	6.0	6.0	1.71
31.0	45.5	14.5	.14
98.0	105.0	7.0	.19

Logged by JDR

Hole No. U-8842

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8841 | SHAFT 2

BEARING S60W | LAT. 13629.31 | DATE COMPLETED | LEVEL 575

DIP AT COLLAR -55 | DEP. 7659.50 | PURPOSE Ore Def. | WORKING S-4091

LENGTH 101.0 | ELEV. 5439 | Rejects saved | SECTION 1800W

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 2.0	Os.				
2.0 - 7.5	30% qutz; py, po, dense aspy	8168	5.5	(1.33 (1.49	7.755
7.5 - 12.0	40% & as above; red sp; cubes py	8169	4.5	(1.09 (1.12	4.950
12.0 - 19.0	70% & as above	8170	7.0	(.62 (.68	4.550
19.0 - 26.0	50% & as above	8171	7.0	(.56 (.55	3.150
26.0 - 33.0	40% & as above in grn clastic sch	8172	7.0	(.25 (.35	2.100
33.0 - 40.0	60% & as above	8173	7.0	(1.38 (1.58	10.360
40.0 - 45.0	grn clastic sch, impact soaked w qutz; py	8174	5.0	(.68 (.52	3.000
45.0 - 48.0	30% qutz in grn clastic sch	8185	3.0	(.84 (.99	2.730
48.0 - 53.0	80% grn qutz w chl; dense aspy, cubes py, v.g.	8186	5.0	(.59 (.52	2.750
53.0 - 60.5	30% qutz; py, dense aspy	8187	7.5	(1.02 (1.15	2.750
60.5 - 63.0	grn clastic sch w bands py	8188	2.5	(.11 (.06	8.100
63.0 - 68.0	grn clastic sch, neg min	8189	5.0	(.17 (.13	

Logged by JDB | Hole No. U-8841

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
68.0 - 75.0	As above	8190	7.0	.09	
75.0 - 80.0	grn clastic sch, no min				
80.0 - 101.0	F.g. grn grs				

From	To	C.L.	Grade
2.0	60.5	58.5	.81

SHEET No. [illegible]

HOLE No. U-8841

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8840 | SHAFT 2
BEARING N60W | LAT. 13633.71 | DATE COMPLETED | LEVEL 575
DIP AT COLLAR -60 | DEP. 7651.50 | PURPOSE Ore Def. | WORKING 8-409N
LENGTH 81.0 | ELEV. 5440 | SECTION 1800E

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 2.0	Cs.				
2.0 - 8.0	50% qutz w chl, cubes py; dense aspy; v.g. in one place	8154	6.0	(1.37 (1.32	8.100
8.0 - 15.0	30% qutz in grn clastic sch, py, dense aspy, po, local sp & gry min	8155	7.0	3.40	23.800
15.0 - 20.0	grn clastic sch, bands py	8156	5.0	.16	.800
20.0 - 27.0	grn clastic sch, neg py & po	8157	7.0	.15	1.050
27.0 - 34.0	As above	8158	7.0	.04	.280
34.0 - 41.0	As above	8159	7.0	.18	1.260
41.0 - 43.0	grn clastic sch	8177	2.0	.61	1.220
43.0 - 48.0	80% qutz; sparing min; v.g. throughout	8178	5.0	(14.54 (14.59	72,800 (25.000)
48.0 - 53.0	As above; heavy v.g.	8179	5.0	(8.61 (5.99	36.500 (25.000)
53.0 - 60.0	20% qutz in grn clastic sch; speck v.g.	8180	7.0	2.17	15.190
60.0 - 65.0	30% mottled qutz; py; heavy v.g. in one place	8181	5.0	(3.02 (2.24	10.650

Logged by JDB | Hole No. U-8840

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
65.0 - 70.0	grn clastic sch, po, py	8182	5.0	.08	171.650
70.0 - 75.0	As above; well min aspy & po	8183	5.0	.09	112.350
75.0 - 81.0	grn clastic sch; po	8184	6.0	.12	

From	To	C.L.	Grade Uncut	Grade Cut
2.0	65.0	63.0	2.72	1.78

SHEET No. 3

HOLE No. U-8840

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8839 | SHAFT 2
BEARING N60W | LAT. 12245.45 | DATE COMPLETED | LEVEL 100
DIP AT COLLAR +30 | DEP. 7207.61 | PURPOSE Silling B-205 stope | WORKING B-205 St.
LENGTH 136.0 | ELEV. 5849 | SECTION 375N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	GOLD ASSAYS OZ./TON
0 - 9.5	grn chl-ser sch				
9.5 - 15.0	50% qutz; py, aspy, v.g.	8138	5.5	(.69 (.80	
15.0 - 21.0	30% qutz & as above	8139	6.0	.75	
21.0 - 26.0	qutz lenses in ser sch; aspy	8145	5.0	.03	7.89 .9
26.0 - 78.0	grn chl-ser sch merg w grs sch (class as grs sch 31.0 to 70.0)				
78.0 - 80.5	60% qutz; v.g.	8146	2.5	(1.73 (2.16	4.850
80.5 - 85.0	chl-ser sch, neg min	8147	4.5	.03	.135
85.0 - 89.5	qutz lenses in ser sch; aspy	8148	4.5	.14	.630
89.5 -96.5	20% qutz sect, py, aspy	8149	7.0	.18	1.260
96.5 - 103.0	40% qutz; py, aspy, Fine v.g.	8150	6.5	(.79 (.71	4.875
103.0 - 108.0	20% qutz; minor min	8151	4/5.0	.08	11.750
108.0 - 113.0	As above	8152	4/5.0	.05	
113.0 - 120.0	70% coarse qutz-carb, no min	8153	7.0	.03	

Logged by JDB | Hole No. U-8839

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
120.0 - 131.0	chl-ser sch; minor qutz sect				
131.0 - 136.0	f.g. grn grs sch				

From	To	C.L.	Grade
9.5	21.0	11.5	.75
78.0	103.0	25.0	.47

SHEET No. JDB

HOLE No. U-P839

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8838 | SHAFT 2
BEARING 360° | LAT. 13586.64 | DATE COMPLETED | LEVEL 575
DIP AT COLLAR -48 | DEP. 7633.62 | PURPOSE Ore Def. | WORKING B-409N
LENGTH 75.0 | ELEV. 5439 | SECTION 1750N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 2.0	Os.				
2.0 - 7.0	30% qutz well min aspy	8128	5.0	1.29	6.450
7.0 - 12.0	70% qutz; py, gran aspy, tr v.g.	8129	5.0	(1.23 (1.69	7.300
12.0 - 16.0	As above, gry min & v.g.	8130	4.0	1.65	6.600
16.0 - 21.0	50% qutz & as above	8131	5.0	1.75	8.750
21.0 - 25.0	grn clastic sch, py	8132	4.0	.66	2.640
25.0 - 30.0	gry clastic sch; neg py	8133	5.0	.08	.400
30.0 - 36.0	as above w py	8134	6.0	1.11	6.660
36.0 - 43.0	As above	8135	7.0	.52	3.640
43.0 - 49.0	As above w qutz sect,	8136	6.0	.20	1.200
49.0 - 52.0	30% qutz; chl, cubes py;	8137	3.0	1.18	3.540
52.0 - 55.0	F.G. di; x-c ore 52.0; py	8140	3.0	.01	.030
55.0 - 62.0	grn clastic sch, minor py	8141	7.0	.06	.420

Logged by JOB | Hole No. U-8838

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
62.0 - 68.0	grn clastic sch; py; minor sect soaked w grn qutz; v.g.	8142	6.0	(1.03 (.93	5.880
68.0 - 71.0	grn clastic sch; py	8143	3.0	.27	.810
71.0 - 75.0	grn clastic sch	8144	4.0	.01	54.320

From	To	C.L.	Grade
2.0	71.0	69.0	.78

SHEET No. JDB

HOLE No. U-8838

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B837 | SHAFT 2

BEARING N60W | LAT. 12245.45 | DATE COMPLETED | LEVEL 100

DIP AT COLLAR Hor. | DEP. 7207.61 | PURPOSE Silling B-205 stope | WORKING B-205

LENGTH 41.0 | ELEV. 5247 | SECTION 375E

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 13.0	grn chl-ser sch				
13.0 - 24.0	60% qutz, py, aspy; tr sp & gry min; v.g. (fine)	8127	9/11.0	(5.51 (4.15	
24.0 - 26.0	banded ser sch			1.16	
26.0 - 41.0	grn chl-ser sch merg w grs sch towards 41.0			4.4	

From	To	C.L.	Grade
13.0	24.0	11.0	4.83

Logged by JDB

Hole No. U-B837

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B836
BEARING N 60 W
DIP AT COLLAR -60
LENGTH 109.0

LAT. 13593.09
DEP. 7622.45
ELEV. 5439

DATE COMPLETED
PURPOSE Ore Def.

SHAFT 2
LEVEL 575
WORKING B-409 N
SECTION 1750 N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 2.0	Cs				
2.0 - 9.0	grn clastic sch; py; 6" gutz w speck v.g.	8118	7.0	(1.02 (1.64	9.310
9.0 - 16.0	as above; no gutz	8119	7.0	.69	4.830
16.0 - 23.0	as above, some sp; no gutz	8120	7.0	.05	.350
23.0 - 30.0	as above	8121	7.0	.04	.280
30.0 - 37.0	as above; 8" gutz w cubes py	8122	7.0	.17	1.190
37.0 - 44.0	30% gutz sect w cubes py	8123	7.0	.28	1.960
44.0 - 50.0	grn clastic sch; mass py; 8" gutz w cubes py	8124	6.0	.42	2.520
50.0 - 57.0	as above	8125	7.0	.09	.630
57.0 - 64.0	as above	8126	7.0	.51	3.570
64.0 - 72.0	grn clastic sch; local py	8235	8.0	.74	5.920
72.0 - 77.0	grn clastic sch partly soaked w gutz; py	8236	5.0	.08	.400
77.0 - 81.5	grn sch; minor py	8237	4.5	.13	30.960
81.5 - 109.0	f.g. di				

From	To	C.L.	Grade
2.0	77.0	75.0	.41

Logged by JDB

Hole No. U-B836

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8835 | SHAFT 2
BEARING N60W | LAT. 12319.11 | DATE COMPLETED | LEVEL 100
DIP AT COLLAR Hor | DEP. 7223.59 | PURPOSE Silling B-205 st. | WORKING B-205 st.
LENGTH 81.0 | ELEV. 5852 | SECTION 446N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	GOLD ASSAYS OZ./TON
0 - 6.5	40% qutz, speck v.g.	8111	6.5	(2.37 (2.15	14.690
6.5 - 12.0	20% qutz lenses, minor min	8112	5.5	.04	.220
12.0 - 15.5	As above	8113	3.5	.37	1.295
15.5 - 43.5	grn chl-ser sch merg w grs sch				16.205
43.5 - 48.5	30% qutz in parcel ser sch, minor min	8114	5.0	.14	.700
48.5 - 53.5	20% and as above	8115	5.0	.13	.650
53.5 - 58.0	30% & as above, V.g.	8116	4.5	(3.49 (1.40	10.980
58.0 - 65.0	20% qutz; minor min	8117	7.0	.33	2.310
65.0 - 68.0	qutz lenses in ser sch; aspy	8160	3.0	.81	2.430
68.0 - 74.0	grn-buff chl-ser sch				17.070
74.0 - 81.0	V.g. grn grs sch				

From	To	C.L.	Grade
0	15.5	15.5	1.04
43.5	68.0	24.5	.69

Logged by JDB | Hole No. U-8835

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8834 | SHAFT 2
BEARING - | LAT. 13549.5 | DATE COMPLETED | LEVEL 525
DIP AT COLLAR -90 | DEP. 7597.0 | PURPOSE Ore Def. | WORKING B-409N
LENGTH 151.0 | ELEV. 5438 | SECTION 1700N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	GOLD ASSAYS OZ./TON
0 - 2.0	Cs.				
2.0 - 9.0	qutz lenses in it buff ser sch, py	8093	7.0	.03	.210
9.0 - 13.0	As above	8094	4.0	.12	.480
13.0 - 19.5	20% qutz in gran ser sch, py, local sp & gry min	8095	6.5	.59	3.835
19.5 - 25.0	70% dk qutz well min w sp & gry min; local v.g.	8096	5.5	(1.47 (1.47	8.085
25.0 - 30.0	As above, v.g. throughout	8097	5.0	(4.16 (6.03	25.000
30.0 - 36.5	As above, local v.g.	8098	6.5	(1.79 (1.87	11.895
36.5 - 44.0	qutz-carb lenses in ser sch, local min	8099	7.5	.35	2.625
44.0 - 48.0	40% qutz: pt. richly min, v.g.	8100	4.0	(1.93 (2.52	8.880
48.0 - 50.0	gry ser sch, minor min	8101	2.0	.05	61.010
50.0 - 92.5	dk chl-ser sch	8102	6.0	1.71	10.260
92.5 - 98.5	40% qutz; py, qutz soaked w sp	8103	5.5	1.61	8.855
98.5 - 104.0	20% qutz: py	8104	5.0	.81	4.050

Logged by JDB | Hole No. U-8834

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
104.0 - 109.0	As above	8105	5.0	.22	1.100
109.0 - 114.0	As above				
114.0 - 121.0	30% & as above	8106	7.0	1.05	7.350
121.0 - 128.0	90% qutz; sp, gry min; copper-coloured v.g. throughout	8107	7.0	(10.95 (10.90	76.440 (35.000
128.0 - 133.0	50% qutz; py; local sp & gry min	8108	5.0	1.86	9.300 3.100
133.0 - 138.0	90% qutz well min w sp & gry min	8109	5.0	.62	
138.0 - 141.0	dk ser sch; local py	8110	3.0	.05	
141.0 - 151.0	dk gry chl-ser sch				120.455
					79.015

	From	To	C.L.	Grade Uncut	Grade Cut
	2.0	48.0	46.0	1.32	--
	92.5	138.0	45.5	2.64	1.73
alt	2.0	138.0	136.0	1.35	1.04

T.S.				
50.0 - 55.0	8167	5.0	.03	.150
55.0 - 62.0	8166	7.0	.04	.280
62.0 - 69.0	8165	7.0	.03	.210
69.0 - 76.0	8164	7.0	.03	.210
76.0 - 81.0	8163	5.0	.09	.450
81.0 - 88.0	8162	7.0	.12	.040
88.0 - 92.5	8161	4.5	.06	.270
				2.410
				183.875
				142.435

SHEET No. 2

HOLE No. U-B834

GIANT YELLOWKNIFE GOLD MINES LIMITED

CORE RECORD

HOLE No. U-B833 | SHAFT 2

BEARING N60W | LAT. 12296.56 | DATE COMPLETED | LEVEL 100

DIP AT COLLAR Hor. | DEP. 7218.96 | PURPOSE Silling B-205 St. | WORKING B-205 St.

LENGTH 54.0 | ELEV. 5852 | SECTION 4250

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 5.0	60% qutz; py, aspy	8091	5.0	1.11	
5.0 - 10.0	qutz lenses in ser sch, minor min	8092	5.0	.06	
10.0 - 54.0	gran grn chl-ser sch merg w grs sch				

From	To	C.L.	Grade
0	5.0	5.0	1.11

Logged by JHB

Hole No. U-B833

GIANT YELLOWKNIFE GOLD MINES LIMITED

CORE RECORD

HOLE No. U-B832 | SHAFT 2

BEARING N60W | LAT. 12270.03 | DATE COMPLETED | LEVEL 100

DIP AT COLLAR Hor. | DEP. 2214.79 | PURPOSE Silling B205 St. | WORKING B-205 St.

LENGTH 37.0 | ELEV. 5850 | SECTION 400W

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 8.0	grn-gry banded ser sch				
8.0 - 16.0	60% qutz, py, tr gry & min, v.g.	8089	8.0	(1.80 (2.12	1.92 1.96
16.0 - 23.0	qutz-carb in contort ser sch; neg min	8090	7.0	.03	
23.0 - 37.0	grn chl-ser sch merg w grs sch towards 37.0				

From	To	C.L.	Grade
8.0	16.0	8.0	1.96

Logged by JDB

Hole No. U-B832

GIANT YELLOWKNIFE GOLD MINES LIMITED

CORE RECORD

HOLE No. U-8831 | SHAFT 2

BEARING N60W | LAT. 13510.76 | DATE COMPLETED | LEVEL 575

DIP AT COLLAR -45 | DEP. 7565.54 (1010) | PURPOSE Ore Def. | WORKING B-409W

LENGTH 64.0 | ELEV. 5438 | SECTION 1650W

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 7.0	gry ser sch	8085	7.0	.08	
7.0 - 13.0	60% qutz-carb, sp, gry min	8086	6.0	2.03	12.180
13.0 - 19.0	40% & as above	8087	6.0	2.14	12.840
19.0 - 24.0	Lt grn-gry sch, po	8088	5.0	.06	
24.0 - 34.0	gry gran chl-ser sch				
34.0 - 64.0	grn grs sch merg w sch grs after 52.0				

From	To	C.L.	Grade
7.0	19.0	12.0	2.08

Logged by JDB

Hole No. U-8831

GIANT YELLOWKNIFE GOLD MINES LIMITED

CORE RECORD

HOLE No. U-8830 SHAFT 2

BEARING N60W LAT. 12216.95 DATE COMPLETED LEVEL 100

DIP AT COLLAR +25 DEP. 7193.06 PURPOSE Silling B-205 Stope WORKING B-205 St.

LENGTH 51.0 ELEV. 5847 SECTION 346N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 8.0	grn chl-ser sch				
8.0 - 31.5	grn-gry ser sch; t.s. 13.0 - 18.5	8084	5.5	1.37	
31.5 - 51.0	grn chl-ser sch, merg w grs sch				

From	To	C.L.	Grade
13.0	18.5	5.5	1.37

Logged by JDB Hole No. U-8830

GIANT YELLOWKNIFE GOLD MINES LIMITED

CORE RECORD

HOLE No. U-B829 | SHAFT 2

BEARING N60W | LAT. 12193.58 | DATE COMPLETED | LEVEL 100

DIP AT COLLAR +25 | DEP. 7196.08 | PURPOSE B-205 Stope sillin g | WORKING B-205 st.

LENGTH 49.0 | ELEV. 5847 | SECTION 325N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 26.0	grn chl-ser sch (Fault 20.0 ?)				
26.0 - 49.0					

Logged by JDB

Hole No. U-B829

GIANT YELLOWKNIFE GOLD MINES LIMITED

CORE RECORD

HOLE No. U-B828 | SHAFT 2

BEARING S60E | LAT. 13503.80 | DATE COMPLETED | LEVEL 575

DIP AT COLLAR -45 | DEP. 7577.58 | PURPOSE Ore Def. | WORKING B-409N

LENGTH 113.0 | ELEV. 5438 | SECTION 1650N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	GOLD ASSAYS OZ./TON
0 - 7.0	banded ser sch w qutz lenses; minor min	8065	7.0	.24	1.680
7.0 - 14.0	30% qutz; py, tr sp & gry min	8066	7.0	.12	.840
14.0 - 21.0	As above	8067	6/7.0	.71	4.970
					7.490
21.0 - 28.0	qutz sect w aspy at interv. inser sch	8068	7.0	.11	.770
28.0 - 34.0	gry buff ser sch, minor qutz & min	8069	6.0	.04	.240
34.0 - 39.0	As above	8072	5.0	.02	.100
39.0 - 43.0	As above w increas qutz & min	8073	4.0	.11	.440
43.0 - 48.5	80% qutz, sp, gry min	8074	5.5	2.32	12.760
48.5 - 53.0	gry-buff ser sch, minor qutz & min	8075	4.5	.15	.675
53.0 - 58.0	As above	8076	5.0	.03	.150
58.0 - 63.0	As above; py	8077	5.0	.08	.400
63.0 - 68.0	As above	8078	5.0	.11	.550
68.0 - 73.0	As above	8079	5.0	.33	1.650

Logged by JDE

Hole No. U-B828

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
73.0 - 80.0	As above	8080	7.0	.13	.910
80.0 - 84.5	80% dk qutz, sparing min	8081	4.5	.72	3.240
84.5 - 90.0	Ser sch w qutz lenses, py	8082	5.5	.24	1.320
90.0 - 93.5	70% qutz; py, tr gry min & sp	8083	3.5	1.80	6.300
					13.420
					36.995
93.5 - 97.5	buff-grn ser sch				
97.5 - 113.0	F.g. grn grs sch merg w grs by 113.0				

	From	To	C.L.	Grade
	0	21.0	21.0	.35
	43.0	48.5	5.5	2.32
	68.0	93.5	25.5	.52
alt.	0	93.5	93.5	.39

SHEET No. 2

HOLE No. U-9228

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B827
BEARING N60W
DIP AT COLLAR 425
LENGTH 53.0

LAT. 12172.82
DEP. 7191.46
ELEV. 5849

DATE COMPLETED
PURPOSE Silling B-205

SHAFT 2
LEVEL 100
WORKING B-205 St.
SECTION 304N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 18.0	grs sch merg w chl-ser sch				
18.0 - 26.5	grn-gry chl-ser sch t.s. 22.5 - 26.5	8064	4.0	.30	
26,5 - 46.5	gry ser sch				
46.5 - 53.0	gry chl-ser sch				

From	To	C.L.	Grade
22.5	26.5	4.0	.30

Logged by JDB

Hole No. U-B827

GIANT YELLOWKNIFE GOLD MINES LIMITED

CORE RECORD

HOLE No. U-9826 | SHAFT 2

BEARING N60W | LAT. 12144.44 | DATE COMPLETED | LEVEL 100

DIP AT COLLAR +30 | DEP. 7185.28 | PURPOSE Silling B-205 Stope | WORKING B-205 st.

LENGTH 53.0 | ELEV. 5852 | SECTION 275N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 36.5	chl-ser sch merg w grs sch; mottled w barren qutz-carb after 16.0				
	t.s. min sect 25.0 - 30.0	8062	5.0	.55	
	t.s. 32.0 - 36.5	8063	4.5	.29	
36.5 - 53.0	gry ser sch				

From	To	S.L.	Grade
25.0	30.0	5.0	.55
32.0	36.5	4.5	.29

Logged by JDB

Hole No. U-9826

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B825 | SHAFT 2
BEARING N60W | LAT. 13593.09 | DATE COMPLETED | LEVEL 575
DIP AT COLLAR 45 | DEP. 7622.45 | PURPOSE Ore Def. | WORKING S-109N
LENGTH 41.0 | ELEV. 5447 | SECTION 1750N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	GOLD ASSAYS OZ./TON
0 - 4.5	40% qutz; py, aspy, v.g., tr gry min & sp	8057	4.5	(4.07 (4.48	19.215
4.5 - 10.5	20% qutz & as above,	8058	6.0	.51	3.060
10.5 - 15.5	grn clastic sch, locally soaked w qutz and py	8059	5.0	.68	3.400
15.5 - 21.0	As above	8060	5.5	.19	1.045
21.0 - 24.5	As above w neg qutz & min	8061	3.5	.04	26.720
25.5 - 41.0	grn-gry sch (clastic?) merg w grs sch				

From	To	C.L.	Grade
0	21.0	21.0	1.27

Logged by JDB

Hole No. U-B825

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-3324
BEARING N60W
DIP AT COLLAR ∠35
LENGTH 54.0

LAT. 12120.93
DEP. 7180.71
ELEV. 5856

DATE COMPLETED
PURPOSE Silling B-205 stope

SHAFT 2
LEVEL 100
WORKING B-205 St.
SECTION 252N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 54.0	grn-gry chl-ser sch, ser sch 26.5 - 35.0				

Logged by JDB

Hole No. U-3324

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8823
BEARING S60E
DIP AT COLLAR 45
LENGTH 35.0
LAT. 13586.64
DEP. 7633.62
ELEV. 5447
DATE COMPLETED
PURPOSE Ore Def.
SHAFT 2
LEVEL 575
WORKING B-4C9N
SECTION 1750N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 7.0	50% qutz; cubes py, speck v.g.	8054	7.0	(4.55 (4.82	31.850
7.0 - 14.5	60% qutz; cubes py, v.g.	8055	7.5	(4.80 (4.41	33.075
14.5 - 18.0	grn clastic sch, py	8056	3.5	.29	1.015
18.0 - 35.0	lt gry comp chl-ser sch				65.940

From	To	C.L.	Grade
0	18.0	18.0	3.66

Logged by JDB

Hole No. U-8823

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-3822
BEARING N60W
DIP AT COLLAR +55
LENGTH 47.0

LAT. 12093.68
DEP. 7172.43
ELEV. 5858

DATE COMPLETED
PURPOSE Silling B-205 stope

SHAFT 2
LEVEL 100
WORKING B-205 St.
SECTION 225W

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 21.0	grn-gry chl-ser sch				
21.0 - 47.0	gry-buff ser sch, qutz-carb strs,				
	t.s. 35.5 - 38.0	8053	2.5	.29	

From	To	C.L.	Grade
35.5	38.0	2.5	.29

Logged by JDB

Hole No. U-3822

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B821
BEARING --
DIP AT COLLAR -90
LENGTH 95.0
LAT. 13590
DEP. 7628
ELEV. 5440
DATE COMPLETED
PURPOSE Ore Def.
SHAFT 2
LEVEL 575
WORKING B-409N
SECTION 1750N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 2.0	Cs.				
2.0 - 7.5	20% qutz; py, aspy, sp	8049	5.5	3.70	
7.5 - 13.5	grn clastic sch, local bands py	8050	6.0	.07	
13.5 - 62.0	grn clastic sch, minor py	8051	4.5	.67	3.015
62.0 - 66.5	grn clastic sch lightly soaked w qutz & py	8052	6.5	4.50	29.250
66.5 - 73.0	20% qutz soaked in dk sch, py				32.265
73.0 - 95.0	F.G. - mg. di; chll'd cont 73.0				

From	To	C.L.	Grade
2.0	7.5	5.5	3.70
6.0	73.0	11.0	2.93

Logged by JOB

Hole No. U-B821

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B820
BEARING N60W
DIP AT COLLAR 45
LENGTH 32.0
LAT. 13633.71
DEP. 7651.50
ELEV. 5447
DATE COMPLETED
PURPOSE Ore Def.
SHAFT 2
LEVEL 575
WORKING B-409N
SECTION 1800N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	GOLD ASSAYS OZ./TON
0 - 6.5	60% grn qutz, chl, py; v.g. in 2 places	8045	6.5	2.66	17.290
6.5 - 14.0	grn chl sch w minor qutz & bands py	8046	7.5	.42	3.150
14.0 - 21.0	30% qutz sect in grn clastic sch; grn qutz w cubes py & v.g.	8047	7.0	(1.31 (4.81	21.420
21.0 - 25.0	grn clastic sch w bands py	8048	4.0	.31	1.240
25.0 - 32.0	grn clastic sch				43.100

From	To	C.L.	Grade
0	25.0	25.0	1.72

Logged by JOB

Hole No. U-B820

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8819
BEARING S60E
DIP AT COLLAR 45
LENGTH 42.0
LAT. 13629.31
DEP. 7659.50
ELEV. 5447
DATE COMPLETED
PURPOSE Ore Def.
SHAFT 2
LEVEL 575
WORKING B-409N
SECTION 1800N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 7.0	70% grn qutz; cubes py, chl, po, local sp & gry min	8038	7.0	(2.69 (2.74	18.970
7.0 - 14.0	80% grn qutz; cubes py, chl, local sp & gry min, v.g.	8041	7.0	(2.32 (2.14	15.610
14.0 - 21.0	dk grn ser sch partly soaked w qutz; py	8042	7.0	3.24	22.680
21.0 - 28.0	As above w decreasing qutz in clastic sch	8043	7.0	.92	6.440
28.0 - 32.5	As above, po	8044	4.5	1.16	5.220
32.5 - 42.0	grn clastic sch				68.920

From	To	C.L.	Grade
0	32.5	32.5	2.12

Logged by JDB

Hole No. U-8819

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8818
BEARING --
DIP AT COLLAR -90
LENGTH 114.0
LAT. 13631
DEP. 7656
ELEV. 5439
DATE COMPLETED
PURPOSE Ore Def.
SHAFT 2
LEVEL 575
WORKING B-409N
SECTION 1800N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 2.0	Cs				
2.0 - 7.5	40% qutz, aspy, large cubes py	8017	5.5	.76	4.180
7.5 - 12.5	30% & as above	8018	5.0	1.53	7.650
12.5 - 16.0	40% qutz; py, grn chl	8019	3.5	1.43	5.005
16.0 - 23.0	80% qutz; cubes py, grn chl, liberally sprinkled w fine v.g.	8020	7.0	(3.56 (2.94	22.750
23.0 - 30.0	70% & as above, sp, v.g.	8021	7.0	(3.32 (3.33	23.240 36.190
30.0 - 37.0	80% & as above; v.g.	8022	7.0	(5.15 (5.20	(35.000)
37.0 - 44.0	As above; v.g.	8023	7.0	(2.48 (2.31	16.730
44.0 - 51.0	20% qutz in grn sch; chl, py, po	8029	7.0	2.57	17.990
51.0 - 58.0	qutz lenses in grn sch well min w py; po	8030	7.0	4.43	31.010
58.0 - 61.0	As above	8031	3.0	2.09	6.270
61.0 - 65.0	40% grn qutz, cubes py, chl, po	8032	4.0	2.50	10.000
65.0 - 72.0	70% grn qutz, cubes py chl, po. v.g.	8033	7.0	(6.98 (6.53	47.250 (35.000)

Logged by JDB

Hole No. U-8818

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
72.0 - 79.0	60% qutz & as above, tr v.g., sp	8034	7.0	(1.75 (1.69	12.040
79.0 - 85.0	50% & as above, tr v.g. (?)	8035	6.0	(.84 (.87	5.100
85.0 - 93.0	qutz lenses in grn sch well min w py, po	8036	8.0	1.60	12.800
93.0 - 99.0	20% qutz & as above	8037	6.0	2.88	17.280
99.0 - 114.0	grn clastic sch				275.485 (262.045)

From	To	C.L.	Grade Uncut	Grade Cut
2.0	99.0	97.0	2.84	2.70

SHEET No. 2

HOLE No. U-8818

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B817
BEARING --
DIP AT COLLAR +90
LENGTH 44.0
LAT. 13631
DEP. 7656
ELEV. 5447
DATE COMPLETED
PURPOSE Ore Def.
SHAFT 2
LEVEL 575
WORKING B-409N
SECTION 1800N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 2.0	Cs.				
2.0 - 6.5	30% qutz-carb; py	8013	4.5	.84	3.780
6.5 - 10.0	40% & as above	8014	3.5	.21	.775
10.0 - 17.0	80% qutz. chl. py	8015	7.0	1.74	12.180
17.0 - 18.5	bull wte qutz vein	8016	1.5	.15	.225
18.5 - 44.0	grn clastic sch,				16.960

From	To	C.L.	Grade
2.0	18.5	16.5	1.02

Logged by JJB

Hole No. U-B816

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8816
BEARING S60E
DIP AT COLLAR +60
LENGTH 35.0

LAT. 13670.03
DEP. 7688.73 5.83 W
ELEV. 5448

DATE COMPLETED
PURPOSE Ore Def.

SHAFT 2
LEVEL 575
WORKING B-409N
SECTION 1850N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 4.5	silic ser sch impreg w py	8000	4.5	.07	.315
4.5 - 8.5	60% qutz-carb, minor min	8001	4.0	.09	.360
8.5 - 14.0	80% qutz; gry min, sp, sect heavily min w aspy	8002	5.5	(.61 (.62	3.355
14.0 - 20.0	40% qutz; aspy, tr sp & gry min	8003	6.0	(.95 (1.10	6.120
20.0 - 35.0	gry ser sch				10.150

From	To	C.L.	Grade
0	20.0	20.0	.50

Logged by JDB

Hole No. U-8816

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-3815
BEARING N60W
DIP AT COLLAR -60
LENGTH 58.0

LAT. 13679.8
DEP. 7671.9 591
ELEV. 5440

DATE COMPLETED
PURPOSE Ore Def.

SHAFT 2
LEVEL 575
WORKING B-409W
SECTION 1850W

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	GOLD ASSAYS OZ./TON
0 - 2.0	Cs.				
2.0 - 7.5	20% qutz in silic ser sch, py, aspy	7993	5.5	.87	4.785
7.5 - 14.0	m.g. chl-ser sch, tan lent alt fl.	7994	6.5	.01	.065
14.0 - 20.0	As above, no min	7995	6.0	.01	.060
20.0 - 25.5	ser sch w fine xls aspy, py (save rejects) po	7996	5.5	(.37 (.41	2.145
25.5 - 30.5	20% qutz w sp & gry min; fine xls aspy, py v.s.	7997	5.0	(.47 (.58	2.600
30.5 - 36.0	qutz lenses in ser sch, py, fine xls aspy	7998	5.5	(.06 (.03	.220
36.0 - 41.5	20% qutz & as above, po, well min w aspy	7999	5.5	.77	4.235
41.5 - 58.0	grn-gry sch w dk small fl, po, (tuff?).				14.110

From	To	C.L.	Grade
2.0	41.5	39.5	.35

Logged by JGB

Hole No. U-3815

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8814
BEARING S60E
DIP AT COLLAR -60
LENGTH 77.0

LAT. 13670.03
DEP. 7688.73 583W
ELEV. 5440

DATE COMPLETED
PURPOSE Ore Def.

SHAFT 2
LEVEL 575
WORKING B-409N
SECTION 1850N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 2.0	Cs.				
2.0 - 9.0	qutz lenses in silic ser sch, py	7975	7.0	.03	
9.0 - 16.0	30% dk qutz sect in silic ser sch; py; tr gry min	7976	7.0	.08	.560
16.0 - 23.0	20% qutz & as above	7977	7.0	.54	3.780
23.0 - 30.0	As above, tr sp, aspy	7979	7.0	.19	1.330
37.0 - 42.0	buff ser sch, neg qutz & min	7980	7.0	.02	.140
42.0 - 49.0	As above	7981	7.0	.08	.560
49.0 - 54.0	qutz lenses in ser sch, minor min	7982	5.0	.14	.700
54.0 - 60.0	20% qutz; local aspy	7983	6.0	.49	2.940
60.0 - 67.0	30% qutz; pt well min aspy	7984	7.0	1.12	7.840
67.0 - 77.0	dk gry chl-ser sch				19.740

From	To	C.L.	Grade
9.0	67.0	58.0	.34

Logged by JDS

Hole No. U-8814

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8813 | SHAFT 2
BEARING - | LAT. 135.10 | DATE COMPLETED | LEVEL 575
DIP AT COLLAR -90 | DEP. 7567 | PURPOSE Ore Def. | WORKING E-409N
LENGTH 151.0 | ELEV. 5438.5 | SECTION 1650N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 2.0	Cs.				
2.0 - 8.0	gry ser sch w qutz lenses, minor min	7985	6.0	.03	
8.0 - 14.5	As above	7986	6.5	.04	
14.5 - 21.0	gry ser sch, neg qutz & min	7987	6.5	.02	
21.0 - 26.0	As above	7988	5.0	.02	
26.0 - 31.5	As above	7989	5.5	.01	
31.5 - 38.0	20% qutz sect, py	7990	4.5/6.5	.06	.390
38.0 - 44.5	As above, sp	7991	6.5	.18	1.170
44.5 - 49.0	60% qutz; v.g.	7992	4.5	(9.92 (8.87	39.915 (22.500)
49.0 - 54.0	gry ser sch; minor qutz; py	8004	5.0	.06	.300
54.0 - 61.0	70% qutz well min w sp, gry min, aspy & v.g.	8005	7.0	(4.39 (7.86	42.840 35.000)
61.0 - 66.5	70% porcel qutz w cream carb, liberally min w v.g.	8006	5.5	(9.08 (4.77	38.060 (27.500)
66.5 - 71.0	50% qutz; aspy, gry min, sp, v.g.	8007	4.5	(3.54 (3.21	15.165

Logged by JDP | Hole No. U-8813

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
71.0 - 76.0	dk ser sch min w aspy	8008	5.0	.30	1.500
76.0 - 81.0	qutz lenses in ser sch, py	8009	5.0	.02	.100
81.0 - 87.0	qutz lenses in dk ser sch, py, po, aspy xls	8010	6.0	.12	.720
87.0 - 94.0	20% qutz; py, aspy	8011	7.0	.57	3.990
94.0 - 101.0	qutz lenses in ser sch, py, aspy	8012	4/7.0	.02	.140
101.0 - 108.0	As above	8024	7.0	.98	6.860
108.0 - 112.5	20% qutz & as above	8025	4.5	1.45	6.525
112.5 - 120.0	30% qutz & as above	8026	7.5	.97	7.275
120.0 - 127.0	90% qutz; sp, gry min, fine v.g.	8027	7.0	(2.41 (1.97	15.540
127.0 - 131.0	As above; fine v.g.	8028	4.0	(2.57 (2.51	10.160
131.0 - 138.0	50% porcel qutz w yellow carb, sp, gry min, fine v.g.	8039	6/7.0	(2.54 (2.65	18.130
138.0 - 144.0	qutz lenses in ser sch; py aspy	8040	5/6.0	1.64	9.840
144.0 - 151.0	dk chl-ser sch				

From	To	C.L.	Grade Uncut	Grade Cut
31.5	144.0	112.5	1.94	1.62

SHEET No. 2

HOLE No. U-8013

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8812
BEARING -
DIP AT COLLAR -90
LENGTH 64.0
LAT. 13714
DEP. 7709
ELEV. 5440
DATE COMPLETED
PURPOSE Ore Def.
SHAFT 2
LEVEL 575
WORKING 3-409N
SECTION 1900N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 2.0	Cs.				
2.0 - 8.0	60% qutz w retic carb; sparing min, py, sp	7967	6.0	1.10	6.600
8.0 - 15.0	As above	7968	7.0	1.12	7.840
15.0 - 22.0	As above	7969	7.0	.65	4.550
22.0 - 29.0	40% qutz; py, aspy	7970	7.0	.41	2.870
29.0 - 36.0	20% qutz; py, aspy	7971	7.0	.08	.560
36.0 - 43.0	qutz lenses in ser sch; aspy	7972	7.0	.24	1680
43.0 - 50.0	As above	7973	7.0	.05	24.100
50.0 - 57.0	As above	7974	7.0	.02	
57.0 - 64.0	dk gry chl-ser sch				

From	To	C.L.	Grade
2.0	43.0	41.0	.58

Logged by JGB

Hole No. U-8812

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B811
BEARING ---
DIP AT COLLAR 490
LENGTH 44.0
LAT. 13714
DEP. 7709
ELEV. 5449
DATE COMPLETED
PURPOSE Ore Def.
SHAFT 2
LEVEL 575
WORKING B-409N
SECTION 1900N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 1.0	Cs.				
1.0 - 5.0	silic ser sch; py	7964	4.0	.17	.680
5.0 - 10.5	20% qutz; py aspy	7965	5.5	.52	2.860
10.5 - 44.0	dk chl-ser sch; mottled to 25.0 & dense approach grs sch thereafter				3.540

From	To	C.L.	Grade
1.0	10.5	9.5	.37

Logged by JDB

Hole No. U-B811

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-3810
BEARING N60W
DIP AT COLLAR 460
LENGTH 79.0

LAT. 12754.73
DEP. 7273.76
ELEV. 5597

DATE COMPLETED
PURPOSE B-314 stope Layout

SHAFT 2
LEVEL 425
WORKING B-314S
SECTION 850N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	GOLD ASSAYS OZ./TON
0 - 1.0	Cs				
1.0 - 24.5	grn gran grs sch				
24.5 - 56.0	gry chl-ser sch				
56.0 - 60.5	20% qutz; aspy; tr sp	7961	4.5	.64	2.880
60.5 - 65.0	As above	7962	4.5	.43	1.935
65.0 - 72.0	ser sch w qutz lenses; minor min, impreg w 72.0	7963	7.0	.10	.700
72.0 - 78.0	As above	7966	6.0	.51	3.060
78.0 - 79.0	buff ser sch				8.575

From	To	C.L.	Grade
56.0	78.0	22.0	.39

Logged by JPB

Hole No. U-3810

GIANT YELLOWKNIFE GOLD MINES LIMITED

CORE RECORD

HOLE No. U-B 809

BEARING N60W

DIP AT COLLAR +75

LENGTH 45.0

LAT. 12711.76

DEP. 7247.98

ELEV. 5597

DATE COMPLETED

PURPOSE B-314 stope Layout

SHAFT 2

LEVEL 425

WORKING B-314S Dr.

SECTION 800N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 1.0	Cs.				
1.0 - 45.0	C.G. - m.g. gran grs sch, calc. approach chl-ser sch towards 45.0				
	Broke into stope rse 45.0				

Logged by JDB

Hole No. U-B809

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B 808
BEARING N60W
DIP AT COLLAR Hor
LENGTH 307.0
LAT. 13716.44
DEP. 7708.10
ELEV. 5444
DATE COMPLETED
PURPOSE Expl.
SHAFT 2
LEVEL 575
WORKING B-409N
SECTION 1900N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 4.5	qutz lenses in grn-gry ser sch, po, gry min	7954	4.5	1.50	
4.5 - 10.0	As above	7955	5.5	.04	
10.0 - 15.0	silic ser sch; py, tr gry min	7956	5.0	.19	
15.0 - 20.0	As above	7957	5.0	.10	
20.0 - 24.0	As above	7958	4.0	.06	
24.0 - 56.0	gry-buff ser sch; t.s. 32.0 - 36.5 grn after 32.5; clastic (?)	7959	4.5	.02	
56.0 - 77.0	dk gry-grn grs (?) sch w small black flecks				
77.0 - 97.0	f.g. dk gry-grn grs sch; water flow 95.0				
97.0 - 99.0	f.g. black tuffac sch				
99.0 - 144.0	f.g. grn sch grs; local bm tx				
144.0 - 172.0	f.g. sch grs w fine snfl alt, no tip grs types to here				
172.0 - 258.0	tip f.g. grs w chty-ep sect, locally sch				
258.0 - 269.0	grn grs sch				

Logged by JDB

Hole No. U-B808

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
269.0 - 281.5	dk chl-ser sch (clastic)				
281.5 - 292.0	dk slaty sch impreg w py (fault zone? w Fault at 292.0				
292.0 - 307.0	f.g. grs sch w chicken feed tx				

From	To	C.L.	Grade
0	4.5	4.5	1.50

SHEET No. 2

HOLE No. U-B808

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-3807 | SHAFT 2

BEARING 360S | LAT. 13710.99 | DATE COMPLETED | LEVEL 575

DIP AT COLLAR Hor. | DEP. 7717.54 | PURPOSE Ore Def. | WORKING 8-409N

LENGTH 44.0 | ELEV. ~~5444~~ | SECTION 1900N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 35.5	gry & buff partly silic ser sch; p o				
	t.s. 5.5 - 12.0	7951	6.5	.01	
	t.s 15.0 - 18.0	7952	3.0	.60	
	t.s. 27.0 - 30.5	7953	3.5	.32	
35.5 - 40.0	grh grs sch				
40.0 - 44.0	f.g. grn grs				
	t.s. 18.0 - 27.0	7960	9.0	.04	

From	To	C.L.	Grade
15.0	18.0	3.0	.60
27.0	30.5	3.5	.32

Logged by JDB

Hole No. U-3807

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B806
BEARING N60W
DIP AT COLLAR 42.0
LENGTH

LAT. 12783.31
DEP. 7271.53
ELEV. 5681

DATE COMPLETED
PURPOSE B-314 Stope Layout

SHAFT 2
LEVEL 425
WORKING B-314 Sub
SECTION 875W

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 7.0	Ser sch w qutz lenses; aspy	7947	7.0	.04	
7.0 - 14.5	gry ser sch	7948	7.5	.02	
14.5 - 22.0	20% dk qutz, minor min	7949	7.5	.07	
22.0 - 25.5	70% dk qutz-carb, minor min	7950	3.5	.31	
25.5 - 42.0	gry ser sch w qutz lenses, no min				

From	To	C.L.	Grade
22.0	25.5	3.5	.31

Logged by JDB

Hole No. U-B806

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B805
BEARING N60W
DIP AT COLLAR +60
LENGTH 75.0

LAT. 13679.8
DEP. 7671.9
ELEV. 5449

DATE COMPLETED
PURPOSE Ore Def.

SHAFT 2
LEVEL 575
WORKING B-409N
SECTION 1850N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 1.0	Cs.				
1.0 - 8.5	20% qutz, minor min	7933	7.5	.45	3.375
8.5 - 10.0	Silic ser sch	7934	1.5	.27	.405
10.0 - 37.0	gry & buff ser sch, qutz lenses; nosig min				3.780
37.0 - 44.0	dk gry chl-ser sch				
44.0 - 64.5	dk gry, gran, m.g. (basis dyke?)				
64.5 - 75.0	chl-ser sch				

From	To	C.L.	Grade
1.0	10.0	9.0	.42

Logged by JDB

Hole No. U-B805

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B804
BEARING N60W
DIP AT COLLAR Hor.
LENGTH 56.0
LAT. 12783.31
DEP. 7271.53
ELEV. 5683
DATE COMPLETED
PURPOSE B-314 Stope Layout
SHAFT 2
LEVEL 425
WORKING B-314 Sub
SECTION 875N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 4.0	gry ser sch, minor qutz	7940	4.0	.06	
4.0 - 9.0	As above	7941	5.0	.07	
9.0 - 15.5	20% qutz sect; speck v.g.	7942	6.5	(.46 (.47	2.990
15.5 - 19.0	qutz lenses in ser sch, minor min	7943	3.5	.25	.875
19.0 - 24.0	As above	7944	5.0	.02	.100
24.0 - 29.0	As above	7945	5.0	.25	1.250
29.0 - 34.0	As above	7946	5.0	.23	1.150
34.0 - 56.0	gry-buff ser sch; grn chl-ser 54.0 - 56.0				6.365

From	To	C.L.	Grade
9.0	34.0	25.0	.25

Logged by JDB

Hole No. U-B804

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8803
BEARING N60W
DIP AT COLLAR -30
LENGTH 48.0

LAT. 12760.53
DEP. 7261.25
ELEV. 5680

DATE COMPLETED
PURPOSE B-314 Stope Layout

SHAFT 2
LEVEL 425
WORKING B-314 Sub.
SECTION 850W

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 6.0	gry ser sch				
6.0 - 11.0	silic ser sch; minor qutz & min	7935	5.0	.78	3.900
11.0 - 15.0	As above, increas qutz & min	7936	4.0	.02	.080
15.0 - 20.0	20% qutz ore sect, v.g.	7937	5.0	(2.05 (1.84	9.700
20.0 - 23.5	As above, v.g.	7938	3.5	4.15	14.525
23.5 - 30.5	qutz lenses in ser sch, v.g. inone sect.	7939	7.0	(.35 (.42	2.660
30.5 - 36.0	dk tuffac? sch				30.865
36.0 - 48.0	dk gry chl-ser sch				

From	To	C.L.	Grade
6.0	30.5	24.5	1.26

Logged by JDB

Hole No. U-8803

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B802
BEARING N60W
DIP AT COLLAR Hor.
LENGTH 47.0
LAT. 12760.53
DEP. 7261.25
ELEV. 5681
DATE COMPLETED
PURPOSE B-314 Stope Layout
SHAFT 2
LEVEL 425
WORKING B-314 Sub
SECTION 850N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 4.0	gry ser sch, minor qutz & min	7921	4.0	.90	3.600
4.0 - 9.5	As above	7922	5.5	.43	2.365
9.5 - 14.5	30% qutz in ore sect, v.g.	7923	5.0	(.95 (.82	4.400
14.5 - 21.5	20% qutz, local min	7924	7.0	.11	.770
21.5 - 28.5	qutz sect in ser sch, v.g. in one place	7925	7.0	1.14	7.980
28.5 - 35.0	gry ser sch, local min	7926	6.5	.17	1.105
35.0 - 47.0	buff ser sch				20.220

From	To	C.L.	Grade
0	35.0	35.0	.57

Logged by JDB

Hole No. U-B802

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-3801
BEARING -
DIP AT COLLAR -90
LENGTH 68.0
LAT. 13677.5
DEP. 7676 587W.
ELEV. 5440
DATE COMPLETED
PURPOSE Ore Def.
SHAFT 2
LEVEL 575
WORKING S-409N
SECTION 1850N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 2.0	Cs				
2.0 - 9.0	40% dk qutz; large xls aspy	7918	7.0	2.58	18.060
9.0 - 13.5	70% & as above	7919	4.5	2.20 (5.08	9.900 21.510
13.5 - 18.0	50% & as above	7920	4.5	(4.78	
18.0 - 23.0	20% qutz heavily min w aspy	7927	5.0	7.04	35.200 (25.000)
23.0 - 30.0	As above	7928	7.0	8.91	62.370 (35.000)
30.0 - 37.0	As above	7929	7.0	5.94	41.580 (35.000)
37.0 - 42.5	As above	7930	5.5	7.66	42.130 (27.500)
42.5 - 49.5	dk gry ser sch	7931	7.0	.11	.770
49.5 - 54.0	qutz lenses in ser sch, aspy	7932	4.5	7.95	35.775 (22.500)
54.0 - 68.0	dk gry chl-ser sch; minor min				268.295

From	To	C.L.	Grade Uncut	Grade Cut
2.0	54.0	52.0	5.15	3.75

Logged by JDB

Hole No. U-3801

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8800
BEARING --
DIP AT COLLAR 490
LENGTH 41.0
LAT. 13672
DEP. 7685
ELEV. 5448
DATE COMPLETED
PURPOSE Ore Def.
SHAFT 2
LEVEL 575
WORKING B-409N
SECTION 1850N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 7.0	70% qutz-carb, minor sp & gry min	7909	7.0	1.51	10.570
7.0 - 14.0	30% qutz-carb, py, aspy, sp, gry min; tr.v.g.	7913	6/7.0	1.16	8.120
14.0 - 21.0	60% qutz-carp, sp, gry min, v.g.	7914	7.0	2.22	15.540
21.0 - 27.0	40% & as above (no v.g.)	7915	5/6.0	1.01	6.060
27.0 - 32.0	50% & as above, tr v.g.	7916	5.0	(1.55 (1.58	7.800
32.0 - 35.0	As above, tr v.g.	7917	3.0	1.77	5.310
35.0 - 41.0	chl-ser sch w qutz-carb				53.400

From	To	C.L.	Grade
0	35.0	35.0	1.52

Logged by JDB

Hole No. U-8800

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B799
BEARING N60W
DIP AT COLLAR Hor.
LENGTH 38.0

LAT. 13679.8
DEP. 7671.9
ELEV. 5444

DATE COMPLETED
PURPOSE Ore Def.

SHAFT 2
LEVEL 575
WORKING B-409N
SECTION 1850N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	GOLD ASSAYS OZ./TON
0 - 7.0	20% qutz lenses; ore sect in ser sch, tr gry min, sp, v.g.	7906	7.0	(.87 (.47	4.690
7.0 - 13.0	As above	7907	6.0	.35	2.100
13.0 - 18.5	qutz lenses in silic ser sch, local min	7908	5.5	.15	.825 7.615
18.5 - 38.0	grn-gry ser sch, clastic (?)				

From	To	C.L.	Grade
0	18.5	18.5	.41

Logged by JDB

Hole No. U-B799

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B798
BEARING N60W
DIP AT COLLAR -45
LENGTH 75.0
LAT. 12738.01
DEP. 7250.11
ELEV. 5678
DATE COMPLETED
PURPOSE B-314 Stope Layout
SHAFT 2
LEVEL 425
WORKING B-314 Sub
SECTION 825N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 25.0	dk gry ser sch				
25.0 - 30.0	qutz lenses in ser sch, local min	7904	5.0	.29	1.450
30.0 - 35.0	20% qutz, part (6") well min v.g.	7905	5.0	(4.43 (5.50	24.800
35.0 - 41.0	30% qutz, py	7910	6.0	.50	3.000
41.0 - 48.0	70% qutz-carb, sparing min	7711	7.0	2.64	18.480
48.0 - 54.5	silic ser sch, py	7712	6.5	.28	1.820
54.5 - 75.0	dk gry chl-ser sch				49.550

From	To	C.L.	Grade
25.0	54.5	29.5	1.68

Logged by JDB

Hole No. U-B798

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B797
BEARING N 60W
DIP AT COLLAR -30
LENGTH 71.0
LAT. 12738.01
DEP. 7250.11
ELEV. 5679
DATE COMPLETED
PURPOSE B-314 Stope Layout
SHAFT 2
LEVEL 425
WORKING B-314 Sub
SECTION 825N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 14.0	dk gry ser sch				
14.0 - 21.0	20% qutz lenses in ser sch; local min	7879	7.0	.43	3.010
21.0 - 25.5	30% qutz; py, aspy	7894	4.5	23.57	22.500
25.5 - 30.0	gry-buff ser sch, minor min	7895	4.5	.86	3.870
30.0 - 34.0	As above	7896	4.0	.14	.560
34.0 - 40.0	40% qutz; v.g. at intervals; 3" removed	7897	6.0	(11.77 6.98	56.220 (30.000)
40.0 - 45.0	60% qutz; v.g.	7898	5.0	(1.84 (1.90	9.350
45.0 - 50.0	100% qutz carb; sparing gry min & v.g.	7899	5.0	(1.42 (.83	5.600
50.0 - 55.0	As above	7900	5.0	(.83 (.98	4.500
55.0 - 60.0	As above	7901	5.0	(3.00 (3.94	13.880
60.0 - 64.0	20% qutz; local min; silic ser sch	7902	4.0	.28	1.120
64.0 - 71.0	minor sect qutz in gry ser sch	7903	7.0	.09	
					120.610 (94.390)

From	To	C.L.	Grade Uncut	Grade Cut
14.0	64.0	50.0	2.41	1.88

Logged by JDB

Hole No. U-B797

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B796
BEARING N60W
DIP AT COLLAR Hor.
LENGTH 53.0
LAT. 12738.01
DEP. 7250.11
ELEV. 5681
DATE COMPLETED
PURPOSE B-314 Stope Layout
SHAFT 2
LEVEL 425
WORKING B-314 Sub
SECTION 825N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 6.0	gry ser sch				
6.0 - 11.5	20% qutz; sparing min	7872	5.5	.90	4.950
11.5 - 15.0	70% dk qutz, V.G.	7873	3.5	(2.34 (3.04	9.415
15.0 - 20.5	qutz lenses in silic ser sch; py	7874	5.5	.58	3.190
20.5 - 25.0	as above	7875	4.5	.16	.720
25.0 - 32.5	80% qutz-carb richly min; v.g.	7876	7.5	(4.02 (4.39	31.500
32.5 - 39.0	30% qutz-carb, sp	7877	6.5	.49	3.185
39.0 - 44.0	dk tuffac? sch soaked w po & sp, tr cp	7878	5.0	.02	52.960
44.0 - 53.0	gry ser sch w barren qutz-carb				

From	To	C.L.	Grade
6.0	39.0	33.0	1.60

Logged by JDB

Hole No. U-B796

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B795
BEARING S60E
DIP AT COLLAR -45
LENGTH 42.0
LAT. 13094.81
DEP. 7483.69
ELEV. 5590
DATE COMPLETED
PURPOSE B-312 Stope Layout
SHAFT 2
LEVEL 425
WORKING B-306N
SECTION 1250N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 7.0	20% qutz; minor min	7865	7.0	.07	.490
7.0 - 12.0	As above	7866	5.0	.35	1.750
12.0 - 17.0	As above	7867	5.0	.69	3.450
17.0 - 22.0	silic ser sch	7868	5.0	.06	.300
22.0 - 27.0	20% qutz, aspy	7869	5.0	.32	1.600
27.0 - 35.5	dk chl-ser sch				7.590
35.5 - 42.0	grn grs sch				

From	To	C.L.	Grade
0	27.0	27.0	.28

Logged by JDP

Hole No. U-B795

GIANT YELLOWKNIFE GOLD MINES LIMITED

CORE RECORD

HOLE No. U-B794

BEARING N60W

DIP AT COLLAR 45

LENGTH 43.0

LAT. 13099.19

DEP. 7476.11 48'W

ELEV. 5597

DATE COMPLETED

PURPOSE B-310 stope Layout

SHAFT 2

LEVEL 425

WORKING B-308N

SECTION 1250N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 -.6.5	qutz sect in ser sch, minor min	7864	6.5	.02	
6.5 - 43.0	gry ser sch, neg qutz & min				

Logged by JDB

Hole No. U-B794

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8793
BEARING --
DIP AT COLLAR +90
LENGTH 57.0
LAT. 13097
DEP. 7480
ELEV. 5598.5
DATE COMPLETED
PURPOSE 8-310 Stope Def.
SHAFT 2
LEVEL 425
WORKING B-3080
SECTION 1250N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 1.0	Cs.				
1.0 - 8.0	qutz lenses, w carb, in ser sch; py	7860	7.0	.13	.910
8.0 - 15.0	As above	7861	7.0	.06	.420
15.0 - 22.0	As above	7862	7.0	.11	.770
22.0 - 57.0	dk gry ser sch; hem Fault 52.5				2.100

From	To	C.L.	Grade
1.0	22.0	21.0	.10

Logged by JDB

Hole No. U-8793

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B792
BEARING N60W
DIP AT COLLAR -40
LENGTH 50.0

LAT. 13052.67
DEP. 7451.91
ELEV. 5590

DATE COMPLETED
PURPOSE B-408 Stope
Def.

SHAFT 2
LEVEL 425
WORKING B-308N
SECTION 1200N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 4.0	40% qutz, py	7854	4.0	.09	.360
4.0 - 10.5	70% dk qutz-carb, py	7855	6.5	.55	3.575
10.5 - 17.0	40% & as above	7856	6.5	.19	1.235
17.0 - 23.0	20% & as above	7857	6.0	.08	.480
23.0 - 30.0	30% & as above	7858	7.0	.22	1.540
					7.190
30.0 - 36.5	qutz lenses in ser sch; py	7859	6.5	.08	
36.5 - 47.0	buff ser sch				
47.0 - 50.0	grn & black sch w py & po (tuff?) fault?)				

From	To	C.L.	Grade
0	30.0	30.0	.24

Logged by JDB

Hole No. U-B792

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B791
BEARING N60W
DIP AT COLLAR -40
LENGTH 76.0

LAT. 13010.33
DEP. 7430.78 476 W
ELEV. 5592

DATE COMPLETED
PURPOSE B-40S stope
Layout

SHAFT 2
LEVEL 425
WORKING B-30SN
SECTION 1150N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 5.0	qutz lenses in ser sch, aspy	7850	5.0	.37	
5.0 - 11.5	gry ser sch				
11.5 - 13.5	70% dk qutz; sparing min	7851	2.0	.40	
13.5 - 64.0	gry ser sch t.s. 50.0 - 51.0	7852	1.0	.30	
64.0 - 76.0	dk gry chl-ser sch				

From	To	C.L.	Grade
0	5.0	5.0	.37
11.5	13.5	2.0	.40

Logged by JDB

Hole No. U-B791

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B790
BEARING S60E
DIP AT COLLAR Hor.
LENGTH 50.0

LAT. 13670.03
DEP. 7688.73
ELEV. 5444

DATE COMPLETED
PURPOSE Ore Def.

SHAFT 2
LEVEL 575
WORKING B-409N
SECTION 1850N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 5.0	30% qutz-carb in silic ser sch	7846	5.0	.02	.100
5.0 - 10.0	40% qutz- carb, sp & gry min	7847	5.0	.97	4.850
10.0 - 17.0	As above	7848	7.0	.72	5.040
17.0 - 23.0	As above	7848	6.0	.97	5.820
23.0 - 43.0	gry buff ser sch				15.810

From	To	C.L.	Grade
0	23.0	23.0	.68

Logged by JDB

Hole No. U-B790

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B789
BEARING N60W
DIP AT COLLAR ∠30
LENGTH 51.0

LAT. 12783.31
DEP. 7271.53
ELEV. 5684

DATE COMPLETED
PURPOSE B-314 Stope Layout

SHAFT 2
LEVEL 425
WORKING B-314 Sub
SECTION 875N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 7.0	ser sch w qutz lenses, minor min	7816	7.0	.05	
7.0 - 14.0	as above w increas qutz; tr gry min & v.g.	7817	7.0	(1.26 (1.91	11.060
14.0 - 19.0	As above w minor min	7818	5.0	.55	2.750
19.0 - 25.0	50% dk qutz; sparing min	7819	6.0	.67	4.020
25.0 - 30.0	20% qutz; well min	7820	5.0	.42	2.100
30.0 - 34.5	As above w less min	7821	4.5	.25	1.125
34.5 - 39.0	80% qutz; sparing min, v.g. (1" heavy v.g. removed)	7822	4.5	1.44 1.42	6.345
39.0 - 51.0	gry-grn chl-ser sch, merg w grs sch towards 51.0				27.940

From	To	C.L.	Grade
7.0	39.0	32.0	.87

Logged by JDB

Hole No. U-B789

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B788
BEARING N60W
DIP AT COLLAR -45
LENGTH 42.0
LAT. 12760.53
DEP. 7261.25
ELEV. 5686
DATE COMPLETED
PURPOSE B-314 Stope def.
SHAFT 2
LEVEL 425
WORKING B-314 Sub
SECTION 850N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 7.0	qutz lenses in ser sch, local min	7811	7.0	.15	1.050
7.0 - 14.0	As above w 30% sect dk qutz	7812	7.0	.92	6.440
14.0 - 21.0	60% dk qutz, sp, gry min, v.g.	7813	7.0	4.84	33.880
21.0 - 26.0	70% & as above, well min w v.g.	7814	5.0	(13.67 (17.09	76.900 25.000
26.0 - 30.0	as above, v.g.	7815	4.0	1.99	7.960
30.0 - 35.0	buff chl-ser sch				126.230
35.0 - 42.0	grn grs sch				(74.330

From	To	C.L.	Grade Uncut	Grade Cut
0	30.0	30.0	4.20	2.44

Logged by JDB

Hole No. U-B788

GIANT YELLOWKNIFE GOLD MINES LIMITED

CORE RECORD

HOLE No. U-B787
BEARING S60E
DIP AT COLLAR 45
LENGTH 50.0

LAT. 12688.53
DEP. 7237.28
ELEV. 5684

DATE COMPLETED
PURPOSE B-314 stope Layout

SHAFT 2
LEVEL 425
WORKING B-314 Sub.
SECTION 775N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 22.0	f.g. grs sch				
22.0 - 50.0	f.g. chl-ser sch merg w grs sch				

Logged by JDB

Hole No. U-B787

N.M.P.-F3742-3

G-11

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B786

BEARING S60E

DIP AT COLLAR -60

LENGTH 559

LAT. 13447.47

DEP. 7773.45

ELEV. 5438

DATE COMPLETED

PURPOSE Expl.

SHAFT 2

LEVEL 575

WORKING 3-403W

SECTION 1700W

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 2.0	Cs.				
2.0 - 37.0	m.g. grn grs; ep; hem Fract.				
37.0 - 62.0	f.g. grn sch grs				
62.0 - 105.0	f.g. grn grs sch; local sect approach				
	chl-ser sch				
	chl-ser sch (Flowbx?) banded 84.0 - 86.0 & 93.0 - 97.0				
105.0 - 136.0	Chl-ser sch, gry-buff, bx tx;				
136.0 - 146.0	f.g. di				
146.0 - 200.5	grn (clastic)? sch, mottled w qutz; py				
	t.s. hard qutz vein w chl & py (not ore type) 182.0 - 187.5	7823	5.5	.06	
	banded & chty after 187.5; local heavy py				

Logged by [illegible]

Hole No. U-786

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
200.5 - 204.0	40% grn qutz soaked in grn clastic sch; sp; py; v.g. (rich in one sect) most unusual	7824	3.5	(2.38 (2.80	
204.0 - 227.0	grn clastic sch w light chty grn sect, py; locally soaked w qutz:				
	t.s. 213.5 - 219.0	7825	5.5	1.11	6.105
227.0 - 231.0	clastic sch soaked w chty qutz; py, sp, speck v.g.	7826	4.0	1.13 1.23	4.720
231.0 - 242.0	Lt & dk grn clastic sch				
242.0 - 279.0	f.g. di				
279.0 - 301.0	grn clastic sch				
301.0 - 361.0	buff-gry ser sch; min sect. 319.0 - 320.0 t.s. some silic thereafter	7853	1.0	.04	
	t.s. 204.0 - 209.0	7828	5.0	.17	.850
	t.s. 209.0 - 213.5	7829	4.5	.06	.270
	t.s. 194.0 - 200.5	7830	6.5	.05	
	t.s. 219.9 - 227.0	7831	8.0	.29	2.320
	t.s. 231.0 - 238.0	7832	7.0	.06	.420
361.0 - 365.5	20% qutz; py, aspy	7863	4.5	.74	3.330
365.5 - 371.0	30% & as above, sp	7870	5.5	1.82	10.010
371.0 - 377.0	As above	7871	6.0	.49	2.940
377.0 - 383.0	gry ser sch, no qutz or min	7880	6.0	.04	.240
383.0 - 389.0	As above	7881	6.0	.07	.420

SHEET No. 2

HOLE No. U-B786

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
389.0 - 395.0	30% mottled qutz; aspy	7882	6.0	1.07	6.420
395.0 - 402.0	Ore sect in sil ser sch; po	7883	7.0	.43	3.010
402.0 - 407.0	70% qutz; gry min, sp	7884	5.0	1.07	5.350
407.0 - 411.0	As above, v.g.	7885	4.0	1.11	4.440
411.0 - 418.0	qutz lenses in ser sch; minor min	7886	7.0	1.06	7.420
418.0 - 424.0	20% qutz ore lenses in ser sch	7887	6.0	.28	1.680
424.0 - 429.0	gry ser sch, minor min	7888	5.0	.05	.250
429.0 - 436.0	20% qutz, aspy	7889	7.0	.58	4.060
436.0 - 441.0	40% qutz & as above	7890	5.0	.68	3.400
441.0 - 447.0	20% & as above	7891	6.0	1.03	6.180
447.0 - 452.0	As above	7892	5.0	.06	.300
452.0 - 457.0	As above w decreasing qutz & min	7893	5.0	.07	.350

From	To	C.L.	Grade
200.5	231.0	30.5	.76
361.0	457.0	96.0	.59

To be deepened

Dip Tests

Depth	Read	Correct
150	51	46½
300	45	41
450	31	27

SHEET No. 3

HOLE No. U-8786

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
					56.860
457.0 - 461.0	50% rt. angle button core 75% blue-gry qutz, py aspy gry min	8511	4.0	2.74	10.960
461.0 - 465.0	20% button core, as above, orp. stein 1' ground	8512	3.0/4.0	1.31	5.240
465.0 - 473.0	60% rt. angle button core 1' lost ser sch 40% blue qutz, py, aspy	8513	7.0/8.0	.57	4.560
473.0 - 478.0	Gry ser sch. 30% qutz, py, aspy	8514	5.0	.93	4.650
478.0 - 483.0	As above	8515	5.0	.72	3.600
483.0 - 487.0	1' ground, dk grn gry chl-ser sch, clastic Text, 10% qutz, py	8524	3.0/4.0	.01	85.870
487.0 - 497.0	3' ground as above	8525	7.0/10.0	.01	
497.0 - 503.0	Grn-gry buff ser sch, minor qutz, py	8526	6.0	.01	
503.0 - 510.0	Gry ser sch 10% qutz, py, aspy? 3' ground	8527	4.0/7.0	.01	
510.0 - 514.0	Gry silic ser sch 20% qutz, py, aspy, sph?	8528	4.0	.01	
514.0 - 520.0	Gry ser sch, 10% qutz, minor py aspy	8529	6.0	.01	
520.0 - 526.0	1' broken core - gry ser sch 10% qutz py	8530	1.0/6.0	.02	
526.0 - 529.0	1' ground, gry ser chl sch, minor qutz, py	8531	2.0/3.0	.01	
529.0 - 535.0	Grn gry ser sch, compact, f.g. clastic text, negl. qutz, py	8532	6.0	.01	
535.0 - 549.0	As above				
549.0 - 559.0	f.g. compact gry-grn ser sch				

From	To	C.L.	Grade
361.0	483.0	122.0	.70

SHEET No. Deepened

HOLE No. UB 786

GIANT YELLOWKNIFE GOLD MINES LIMITED

CORE RECORD

HOLE No. U-B785 | SHAFT 2

BEARING S60E | LAT. 12667.67 | DATE COMPLETED | LEVEL 425

DIP AT COLLAR 40 | DEP. 7224.26 | PURPOSE B-314 Stope | WORKING B314 Sub

LENGTH 61.0 | ELEV. 5687 | Layout | SECTION 750N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 9.0	grn grs sch				
9.0 - 61.0	gry-grn gran chl-ser sch merg w grs sch				

Logged by JDB

Hole No. U/B785

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8784
BEARING N60W
DIP AT COLLAR +60
LENGTH 59.0

LAT. 12960.24
DEP. 7318.12 549W.
ELEV. 5447

DATE COMPLETED
PURPOSE B-408 stope
Layout

SHAFT 2
LEVEL 575
WORKING B-408S
SECTION 1050N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 1.0	Cs.				
1.0 - 23.0	gran grs sch merg into chl-ser sch				
23.0 - 41.0	gran chl-ser sch merg into ser sch t.s. 38.5 - 41.0	7808	2.5	.03	
41.0 - 47.0	40% qutz-carb, py, aspy	7809	6.0	.67	4.020
47.0 - 49.5	70% qutz-carb; gry min, sp, v.g.	7810	2.5	3.72	9.300
49.5 - 59.0	gry-buff ser sch				

From	To	C.L.	Grade
41.0	49.5	8.5	1.56

Logged by JDB

Hole No. U-8784

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B783
BEARING N60W
DIP AT COLLAR +60
LENGTH 47.0
LAT. 12783.31
DEP. 7271.53
ELEV. 5687
DATE COMPLETED
PURPOSE B-314 stope Layout
SHAFT 2
LEVEL 425
WORKING B-314 Sub
SECTION 875N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 1.0	Cs.				
1.0 - 8.0	qutz lenses m ser sch, minor min	7802	7.0	.04	
8.0 - 15.0	As above, increas qutz & min	7803	7.0	.90	6.300
15.0 - 22.0	20% qutz sect in silic ser sch, local	7804	7.0	.79	5.530
22.0 - 29.0	70% dk qutz, sparing min	7805	7.0	.39	2.730
29.0 - 36.0	80% gry qutz; v.g.	7806	7.0	.98	6.860
36.0 - 41.5	50% qutz; sparing min, slip 41.5	7807	5.5	.77	4.235
41.5 - 47.0	Chl-ser sch grad w grs sch				25.655

From	To	C.L.	Grade
8.0	41.5	33.5	.76

Logged by JDB

Hole No. U-B783

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B782
BEARING S60E
DIP AT COLLAR -50
LENGTH 30.0
LAT. 13503.80
DEP. 7577.58
ELEV. 5446
DATE COMPLETED
PURPOSE Ore Def.
SHAFT 2
LEVEL 575
WORKING B-409N
SECTION 1650N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 5.0	20% qutz; minor min	7797	5.0	.10	.500
5.0 - 11.0	40% qutz; py, aspy	7798	6.0	.96	5.760
11.0 - 13.0	ser sch; minor min	7799	2.0	.02	6.260

From	To	C.L.	Grade
0	11.0	11.0	.57

Logged by JDB

Hole No. U-B782

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8781
BEARING --
DIP AT COLLAR +90
LENGTH 57.0
LAT. 12781.5
DEP. 7274
ELEV. 5687.5
DATE COMPLETED
PURPOSE B-314 Stope Layout
SHAFT 2
LEVEL 425
WORKING B-314 Sub
SECTION B75N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 1.0	Cs.				
1.0 - 6.0	gry ser sch, minor min	7787	5.0	.02	
6.0 - 12.0	as above	7788	6.0	.03	
12.0 - 19.0	as above	7789	7.0	.05	
19.0 - 23.5	as above	7790	4.5	.42	1.890
23.5 - 29.5	20% qutz; py	7791	6.0	.22	1.320
29.5 - 35.0	50% qutz-carb, sparing min	7792	5.5	.22	1.210
35.0 - 40.0	As above	7793	5.0	3.14	15.700
40.0 - 45.0	As above	7794	5.0	2.58	12.900
45.0 - 48.5	silic ser sch	7795	3.5	.03	.105
48.5 - 53.0	60% qutz; gry min, v.g. (2" v.g. removed)	7796	4.5	(1.23 (1.57	6.300
53.0 - 57.0	grn chl-ser sch merg into grs sch				39.425

From	To	C.L.	Grade
19.0	53.0	34.0	1.15

Logged by JDB

Hole No. U-8781

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B780
BEARING N60W
DIP AT COLLAR +25
LENGTH 112.0
LAT. 13510.76
DEP. 7565.54
ELEV. 5444
DATE COMPLETED
PURPOSE Ore Def.
SHAFT 2
LEVEL 575
WORKING B-409N
SECTION 1650N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 6.0	gry ser sch	7777	6.0	.01	
6.0 - 11.5	20% qutz-carb, py, aspy, gry min	7778	5.5	.82	4.510
11.5 - 17.0	80% qutz-carb, gry min; sp, well min v.g.	7770	5.5	(5.04 (5.27	27.500
17.0 - 22.0	70% & as above, v.g.	7780	5.0	4.76	23.800
22.0 - 27.0	20% qutz; py, aspy	7781	5.0	1.11	5.550
27.0 - 29.5	qutz lenses in ser sch, minor min	7782	2.5	.36	.900
29.5 - 37.0	grn ser sch w short min sect	7783	7.5	.04	.300
37.0 - 43.0	as above	7784	6.0	.18	1.080
43.0 - 78.5	gry ser sch				63.640
78.5 - 84.0	20% qutz in silic ser sch, minor min	7785	5.5	.28	1.540
84.0 - 90.0	As above	7786	6.0	.06	.360
90.0 - 92.0	gry ser sch				1.900
92.0 - 112.0	grn grs sch				

From	To	C.L.	Grade
6.0	43.0	37.0	1.72
78.5	90.0	11.5	.16

Logged by JDB

Hole No. U-B780

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B779
BEARING --
DIP AT COLLAR +90
LENGTH 52.0
LAT. 12781.5
DEP. 7274.0
ELEV. 5686.0
DATE COMPLETED
PURPOSE B-314 Stope Layout
SHAFT 2
LEVEL 425
WORKING B-314 Sub
SECTION 850N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 1.0	Cs.				
1.0 - 8.0	qutz lenses in ser sch, minor min	7764	7.0	.06	
8.0 - 11.0	50% dk qutz, gry min, v.g.	7765	3.0	1.34	4.020
11.0 - 17.0	20% qutz, minor min	7773	6.0	.17	1.020
17.0 - 24.0	30% & as above	7774	7.0	.16	1.120
24.0 - 31.0	50% qutz-carb; sp, gry min, speck v.g.	7775	7.0	1.89	13.230
31.0 - 38.5	As above, speck v.g.	7776	7.5	1.10	8.250
38.5 - 45.0	buff ser sch				27.640
45.0 - 52.0	dk gry gran chl-ser sch				

From	To	C.L.	Grade
8.0	38.5	30.5	.90

Logged by JDB

Hole No. U-B779

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-3778
BEARING ---
DIP AT COLLAR +90
LENGTH 43.0
LAT. 12758.5
DEP. 7253
ELEV. 5685.2
DATE COMPLETED
PURPOSE B-314 Stope Layout
SHAFT 2
LEVEL 425
WORKING B-314 Sub
SECTION 825N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	GOLD ASSAYS OZ./TON
0 - 1.0	Cs				
1.0 - 8.0	30% qutz, py, aspy	7760	7.0	.57	3.990
8.0 - 15.0	20% & as above	7761	7.0	.08	.560
15.0 - 22.0	qutz lenses in ser sch, minor min	7762	7.0	.04	.280
22.0 - 27.5	20% qutz & as above	7763	5.5	.33	1.815
27.5 - 31.5	70% qutz; gry min	7771	4.0	.82	3.280
31.5 - 33.5	qutz lenses in ser sch; py, aspy	7772	2.0	.07	9.925
33.5 - 37.5	buff ser sch				
37.5 - 43.0	gry-buff chl-ser sch				

From	To	C.L.	Grade
1.0	31.5	30.5	.32

Logged by JDB

Hole No. U-3778

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B777 | SHAFT 2
BEARING -- | LAT. 12958 | DATE COMPLETED | LEVEL 575
DIP AT COLLAR +90 | DEP. 7321.5 | PURPOSE No. 1 Shoot Def. | WORKING B-408S
LENGTH 114.0 | ELEV. 5447 | SECTION 1050N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 1.0	Cs				
1.0 - 29.0	m.g. gran grs sch				
29.0 - 56.0	m.g. gran chl-ser sch				
56.0 - 64.0	qutz lenses in ser sch; py	7766	8.0	.04	
64.0 - 70.0	as above w increas qutz & min	7767	6.0	.05	
70.0 - 77.0	70% qutz; sp, tr gry min, fine v.g.	7768	7.0	(1.23 (1.14	8.260
77.0 - 81.0	qutz lenses in ser sch; py	7769	4.0	.15	.750
81.0 - 86.0	As above	7770	5.0	.02	.120
86.0 - 92.0	qutz lenses & as above	7800	6.0	.20	1.200
92.0 - 99.0	80% dk qutz-carb richly min w v.g. Fault 99.0	7801	7.0	(9.19 (12.27	75.110 (35.000
99.0 - 103.0	chl-ser sch w qutz carb, Fault 103.0				
103.0 - 109.0	gran ser sch				85.440
109.0 - 114.0	gran chl-ser sch				45.330

From	To	C.L.	Grade Uncut	Grade Cut
70.0	99.0	29.0	2.94	1.56

Logged by JDB

Hole No. U-B777

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B776
BEARING S60E
DIP AT COLLAR 465
LENGTH 79.0

LAT. 12688.53
DEP. 7237.28
ELEV. 5685.0

DATE COMPLETED
PURPOSE B-314 Stope Layout

SHAFT 2
LEVEL 425
WORKING B-314 Sub
SECTION 775N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	GOLD ASSAYS OZ./TON
0 - 11.0	gry & buff ser sch w qutz- carb, local min				
11.0 - 16.0	20% qutz-carb, local gry min	7750	5.0	.01	.050
16.0 - 23.0	50% qutz-carb, py sp, gry min	7751	7.0	.84	5.880
23.0 - 30.0	as above	7752	7.0	.23	1.610
30.0 - 37.0	40% & as above, increas carb.	7753	7.0	.19	1.330
37.0 - 43.5	50% & as above; v.g.	7754	6.5	(1.81 (1.82	11.765
43.5 - 50.0	irreg qutz-carb in ser sch; aspy	7755	6.5	.11	20.635
50.0 - 56.0	As above	7756	6.0	.09	
56.0 - 79.0	qutz-carb sect in ser sch; large xis aspy				

From	To	C.L.	Grade
11.0	43.5	32.5	.63

Logged by JDB

Hole No. U-B776

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B775
BEARING --
DIP AT COLLAR +90
LENGTH 64.0
LAT. 13590
DEP. 7628
ELEV. 5448
DATE COMPLETED
PURPOSE Ore Def.
SHAFT 2
LEVEL 575
WORKING B-409N
SECTION 1750N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 1.0	Cs				
1.0 - 6.5	minor qutz w py in clastic sch	7741	5.5	.95	
6.5 - 64.0	heterog grn clastic sch				
	t.s. 6.5 - 8.0	7747	1.5	.01	
	t.s. 14.5 - 16.5	7748	2.0	.02	
	Sect after 30.0 approach chl-ser Sch &, towards 64.0 grs sch.				

From	To	C.L.	Grade
1.0	6.5	5.5	.95

Logged by JDB

Hole No. U-B775

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B774
BEARING ---
DIP AT COLLAR +90
LENGTH ~~58.0~~ 59.0
LAT. 12691
DEP. 7221
ELEV. 5685.0
DATE COMPLETED
PURPOSE B-314 Stope Layout
SHAFT 2
LEVEL 425
WORKING B-314 Sub
SECTION 775N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 1.0	Cs				
1.0 - 8.0	f.g. grs sch				
8.0 - 26.5	as above merg into gry-buff chl-ser sch				
26.5 - 31.0	40% qutz-carb, mass aspy	7745	4.5	.21	
31.0 - 35.0	50% & as above	7746	4.0	.15	
35.0 - 52.0	mottled ser wch; xis aspy	7749	6.0	.41	
52.0 - 58.0	50% qutz; mass aspy				
58.0 - 59.0	ser sch w qutz-carb				

From	To	C.L.	Grade
26.5	35.0	8.5	.19
52.0	58.0	6.0	.41

Logged by JDB

Hole No. U-B774

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B773
BEARING S60E
DIP AT COLLAR ∠55
LENGTH 83.0
LAT. 12667.67
DEP. 7224.26
ELEV. 5687
DATE COMPLETED
PURPOSE B-314 Stope Layout
SHAFT 2
LEVEL 425
WORKING B-314 Sub
SECTION 750N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 13.0	F.g. grn grs sch				
13.0 - 22.0	grn chl-ser sch				
22.0 - 28.0	qutz-carb lenses in ser sch; minor min	7735	6.0	.04	
28.0 - 32.0	As above	7736	4.0	.58	2.320
32.0 - 37.0	50% qutz-carb; large xis aspy; local gry min	7737	5.0	.16	.800
37.0 - 42.0	As above	7738	5.0	.12	.600
42.0 - 49.0	As above	7739	7.0	.31	2.170
49.0 - 54.0	As above	7740	5.0	.22	1.100
54.0 - 61.0	As above	7742	7.0	.44	3.080
61.0 - 68.0	As above	7743	7.0	.20	1.400
68.0 - 75.0	As above	7744	7.0	.13	.910
75.0 - 83.0	buff ser sch w lge idiom xls aspy				12.380

From	To	C.L.	Grade
28.0	75.0	47.0	.26

Logged by JDB

Hole No. U-B773

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B772 | SHAFT 2

BEARING -- | LAT. 12668.5 | DATE COMPLETED | LEVEL 425

DIP AT COLLAR +90 | DEP. 7222 | PURPOSE B-314 Stope | WORKING B-314 Sub

LENGTH 36.0 | ELEV. 5687 | Layout | SECTION 750N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 1.0	Cs.				
1.0 - 29.0	gry-grn grs sch merg w chl-ser sch				
29.0 - 36.0	gry-grn chl-ser sch, t.s. 31.0 - 32.5	7734	1.5	.03	

Logged by JDB

Hole No. U-B772

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B771
BEARING N60W
DIP AT COLLAR Hor.
LENGTH 119.0
LAT. 13633.21
DEP. 7652.75
ELEV. 5443
DATE COMPLETED
PURPOSE Ore Def.
SHAFT 2
LEVEL 575
WORKING B-409N
SECTION 1800N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 6.5	30% qutz in grn chastic sch; sp	7718	6.5	2.00	13.000
6.5 - 12.0	grn chastic sch; py	7719	5.5	.24	1.320
12.0 - 18.0	As above	7720	6.0	.28	1.680
18.0 - 22.0	As above	7721	4.0	1.63	6.520
22.0 - 91.0	grn chastic sch				22.520
91.0 - 119.0	F.g.-m.g. massdi t.s. 22.0 - 29.5	7733	7.5	.09	

From	TO	C.L.	Grade
0	22.0	22.0	1.02

Logged by JDB

Hole No. U-B771

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B770
BEARING --
DIP AT COLLAR 490
LENGTH 65.0
LAT. 12390
DEP. 7100.5
ELEV. 583.0
DATE COMPLETED
PURPOSE B-215 Stope Layout
SHAFT 2
LEVEL 250
WORKING B-215 Sub
SECTION 450N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	GOLD ASSAYS OZ./TON
0 - 1.0	Cs.				
1.0 - 6.0	20% qutz, minor min	7711	5.0	.05	
6.0 - 12.0	40% qutz; retic carb, py, aspy, tr sp.	7712	6.0	.36	2.160
12.0 - 18.0	50% & as above	7713	6.0	.36	2.160
18.0 - 22.5	As above	7714	4.5	.19	.855
22.5 - 27.5	qutz lenses in ser sch; minor min	7715	5.0	.04	5.175
27.5 - 33.5	As above	7716	6.0	.02	
33.5 - 39.0	As above	7717	5.5	.04	
39.0 - 51.0	buff ser sch w qutz				
51.0 - 65.0	grn chl-ser sch approach grs sch				

From	To	C.L.	Grade
6.0	22.5	16.5	.31

Logged by JDB

Hole No. U-B770

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B769
BEARING S60E
DIP AT COLLAR Hor.
LENGTH 65.0
LAT. 13629.31
DEP. 7659.50
ELEV. 5443
DATE COMPLETED
PURPOSE Ore Def.
SHAFT 2
LEVEL 575
WORKING B-409N
SECTION 1800N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 5.0	50% qutz; py, sp	7704	5.0	1.77	8.850
5.0 - 10.0	As above	7705	5.0	1.23	6.150
10.0 - 15.0	As above, incl. 3' chastic sch	7706	5.0	2.11	10.550
15.0 - 20.0	As above	7707	5.0	.59	2.950
20.0 - 27.0	As above	7708	7.0	.77	5.390
27.0 - 34.0	grn chastic sch w minor qutz & min	7709	7.0	.69	4.830
34.0 - 59.5	grn chastic sch; minor sect qutz & min				
59.5 - 65.0	grn sch grs w epid strs.				
	t.s. 38.0 - 39.0	7710	1.0	1.05	1.050
	t.s. 34.0 - 38.0	7730	4.0	.17	.680
	t.s. 39.0 - 44.0	7731	5.0	.55	2.750
	t.s. 44.0 - 49.0	7732	5.0	.32	1.600
					44.800

From	To	C.L.	Grade
0	49.0	49.0	.91

Logged by JDB

Hole No. U-B769

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B768 | SHAFT 2
BEARING N60W | LAT. 13593.09 | DATE COMPLETED | LEVEL 575
DIP AT COLLAR Hor | DEP. 7622.45 | PURPOSE Ore Def. | WORKING B-409N
LENGTH 255.0 | ELEV. 5443 | SECTION 1750N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 6.0	20% qutz in grn chastic sch	7701	6.0	1.47	8.820
6.0 - 32.0	grn. chaustic sch w minor min sect,	7702	5.5	.31	1.705
	t.s. 11.0 - 16.5				
	t.s. 30.0 - 32.0	7703	2.0	.85	
32.0 - 67.0	gry grn grs sch				
	t.s. 6.0 - 11.0	7722	5.0	.10	.500
	t.s. 16.5 - 22.0	7723	5.5	.19	1.045
	t.s. 22.0 - 30.0	7724	8.0	.04	12.070
	t.s. 32.0 - 37.0	7725	5.0	.02	

	From	To	C.L.	Grade
	0	6.0	6.0	1.47
	11.0	16.5	5.5	.31
	30.0	32.0	2.0	.85
alt.	0	22.0	22.0	.54

Logged by JDB | Hole No. U-B768

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
67.0 - 84.0	chl-ser sch (tuffac?) po				
84.0 - 153.0	gry to grn mott grs sch, snfl alt.				
153.0 - 192.5	f.g. sch grs w ep				
192.5 - 200.0	f.g. gry-grn chl-ser sch				
200.0 - 212.0	gry-buff ser sch, Fault zone 212.0				
212.0 - 236.0	m.g. mass grs, ep				
236.0 - 255.0	f.g. grn grs sch, calc.				

SHEET No. 2

HOLE No. U--B768

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B767
BEARING S60E
DIP AT COLLAR 45
LENGTH 81.0
LAT. 12347.60
DEP. 7027.92
ELEV. 5835.5
DATE COMPLETED
PURPOSE Ore Def. B-215 Stope Layout
SHAFT 2
LEVEL 250
WORKING B-215 Sub
SECTION 375N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 5.0	buff & gry ser sch				
5.0 - 12.0	qutz-carb lenses in ser sch; minor min	7694	7.0	.11	
12.0 - 19.0	As above	7695	7.0	.11	
19.0 - 25.5	20% qutz; py, aspy	7696	6.5	.19	1.235
25.5 - 31.0	As above	7697	5.5	.20	1.100
31.0 - 36.0	40% qutz-carb & as above	7698	5.0	.12	.600
36.0 - 48.0	qutz-carb lenses in ser sch, py				2.935
48.0 - 53.0	20% qutz & as above	7699	5.0	.18	
53.0 - 65.0	grn chl-ser sch w qutz lenses; 12" qutz w gry min; t.s. 64.0-65.0	7700	1.0	.65	
65.0 - 81.0	m.g. grn grs sch w qutz-carb.				

From	To	C.L.	Grade
19.0	36.0	17.0	.17
48.0	53.0	5.0	.18
64.0	65.0	1.0	.65

Logged by JOB

Hole No. U-B767

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B766
BEARING S60E
DIP AT COLLAR Hor.
LENGTH 65.0

LAT. 13586.64
DEP. 7633.62
ELEV. 5443

DATE COMPLETED
PURPOSE Ore Def.

SHAFT 2
LEVEL 575
WORKING B-409N
SECTION 1750N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 6.0	50% qutz-carb, py, sp	7689	6.0	.63	3.780
6.0 - 12.0	60% & as above	7690	6.0	.72	4.320
12.0 - 18.0	50% & as above	7691	6.0	1.50	9.000
18.0 - 60.5	grn heterog chastic sch (tuff) w minor sect min				
	t.s. 30.0 - 32.0	7692	2.0	.87	1.740
	t.s. 39.0 - 45.0	7693	6.0	.46	2.760
60.5 - 61.5	F.g. di				
61.5 - 65.0	sch as above				
	t.s. 18.0 - 25.0	7726	7.0	.04	.280
	t.s. 25.0 - 30.0	7727	5.0	.19	.950
	t.s. 32.0 - 39.0	7728	7.0	.32	2.240
	t.s. 45.0 - 48.0	7729	3.0	.11	25.070

From	To.	C.L.	Grade
0	45.0	45.0	.55

Logged by JDB

Hole No. U-B766

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B765
BEARING --
DIP AT COLLAR +90
LENGTH 51.0
LAT. 12350
DEP. 7024
ELEV. 5835.5
DATE COMPLETED
PURPOSE Low Angle Ore
B-215 stope Layout
SHAFT 2
LEVEL 250
WORKING B-215 Sub.
SECTION 375N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 1.0	Cs				
1.0 - 18.0	gry & buff ser sch w qutz-carb strs, 1" fault gauge 7.0				
18.0 - 25.0	20% qutz, py aspy: tr sp	7687	7.0	.07	
25.0 - 30.0	As above w increas carb,	7688	5.0	.10	
30.0 - 44.0	grn-buff chl-ser sch merg w grs sch				
44.0 - 51.0	grn grs sch				

Logged by JDB

Hole No. U-B765

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B764
BEARING S60E
DIP AT COLLAR 45
LENGTH 62.0

LAT. 12333.84
DEP. 7002.14
ELEV. 5837.5

DATE COMPLETED
PURPOSE B-215 Stope Layout

SHAFT 2
LEVEL 250
WORKING B-215 Sub-Dr.
SECTION 350N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 30.0	buff ser sch, minor qutz & local min t.s. 4.5 - 6.5	7681	2.0	.30	
30.0 - 35.0	50% qutz-carb, py, aspy; tr gry min	7682	5.0	.31	1.550
35.0 - 41.0	gran ser sch (tuffac?) grn chrome micas	7683	6.0	.08	.480
41.0 - 45.0	30% qutz-carb; minor min	7684	4.0	.17	.680
45.0 - 52.0	70% qutz-carb, sparing min; tr sp & gry min	7685	7.0	.64	4.480
52.0 - 55.0	20% qutz-carb lenses; py	7686	3.0	.07	.210
55.0 - 62.0	grn grs sch w pk qutz-carb				7.400

From	To	C.L.	Grade
4.5	6.5	2.0	.30
30.0	55.0	25.0	.29

Logged by JDB

Hole No. U-B764

N.M.P.-F3742-3

G-11

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B763

BEARING S60E

DIP AT COLLAR -45

LENGTH (200.0) ~~285~~ 238

LAT. 13447.47

DEP. ~~7773.45~~

ELEV. 5438

DATE COMPLETED

PURPOSE Lower Orebody Expl.

SHAFT 2

LEVEL 575

WORKING B-403N

SECTION 1700N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 1.0	Cs.				
1.0 - 47.0	m.g. grn sch grs w ep threads & chty ep sect.				
47.0 - 110.5	f.g. grs sch, calc.				
110.5 - 164.0	f.g. diabase, chll'd cont 164.0				
164.0 - 180.0	f.g. gry grn grs sch, local chty bx tx				
180.0 - 200.0	f.g. grn mottled & clastic sch.				

Logged by JDB

Hole No. U-B763

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
203 - 209.0	Grn. clastic sch. negl. min	8482	6.0	.02	
209.0 - 212.0	As above	8483	3.0	.02	
212.0 - 238.0	f.g. diabase				

SHEET No. Deeren

HOLE No. UB 763

GIANT YELLOWKNIFE GOLD MINES LIMITED

CORE RECORD

HOLE No. U-B762
BEARING -
DIP AT COLLAR ∠90
LENGTH 50.0

LAT. 12337.5
DEP. 6996
ELEV. 5837.5

DATE COMPLETED
PURPOSE Low Angle Ore Dev.

SHAFT 2
LEVEL 250
WORKING B-215 Sub.
SECTION 350N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 1.0	Cs.				
1.0 - 8.0	silic ser sch w qutz lenses; minor min	7678	7.0	.10	
8.0 - 14.0	As above with increas qutz-carb	7679	6.0	.05	
14.0 - 20.0	60% qutz-carb, py, aspy, minor sp	7680	6.0	.09	
20.0 - 22.0	grn chl-ser sch, fault (?) 22.0				
22.0 - 50.0	grn grs sch mottled w calc to 39.0				

Logged by JDB

Hole No. U-B762

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8761

BEARING N60W

DIP AT COLLAR -70

LENGTH 119.0

LAT. 12944

DEP. 7346 516.5W

ELEV. 5590

DATE COMPLETED

PURPOSE B-402 stope Layout

SHAFT 2

LEVEL 425

WORKING B-308N

SECTION 1050N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 26.5	buff & gry ser sch; slip 26.5				
26.5 - 33.5	70% dk qutz-carb liberally sprink v.g.	7827	7.0	(6.86 (7.12	48.930 (35.000)
33.5 - 37.0	30% qutz, speck v.g.	7833	3.5	(1.35 (1.14	4.340
37.0 - 44.0	40% qutz; py; sparing min	7834	7.0	.28	1.960
44.0 - 51.0	As above	7835	7.0	1.33	9.310
51.0 - 58.0	As above	7836	7.0	1.06	7.420
58.0 - 63.0	As above	7837	5.0	.39	1.950
63.0 - 68.5	60% qutz; py, sp	7838	5.5	1.76	9.680
68.5 - 73.5	20% qutz; py, sp	7839	5.0	2.35	11.750
73.5 - 78.5	50% qutz, pt richly min w sp & gry min	7840	5.0	3.52	17.600
78.5 - 83.5	As above	7841	5.0	1.33	6.650
83.5 - 89.5	70% qutz-carb & as above	7842	6.0	.41	2.360
89.5 - 94.5	40% qutz richly min w v.g.	7843	5.0	(7.96 (7.67	39.050 (25.000
94.5 - 97.0	gry ser sch w py	7844	2.5	.33	.825

Logged by JDB

Hole No. U-8761

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
97.0 - 112.0	gry-buff ser sch, local qutz & min				
	t.s. 105.0 - 112.0	7845	7.0	.05	
112.0 - 119.0	gry chl-ser sch				

From	To	C.L.	Grade Uncut	Grade Cut
26.5	97.0	70.5	2.29	1.90

SHEET No. 2

HOLE No. U-3761

GIANT YELLOWKNIFE GOLD MINES LIMITED

CORE RECORD

HOLE No. U-B760
BEARING N60W
DIP AT COLLAR -70
LENGTH 64.0

LAT. 12906.08
DEP. ~~7310.72~~ 528W
ELEV. 5990

DATE COMPLETED
PURPOSE No. 1 Shoot Def.

SHAFT 2
LEVEL 425
WORKING B-308N
SECTION 1000N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 2.0	Cs.				
2.0 - 39.0	dk grn-gry chl-ser sch				
39.0 - 42.0	30% qutz; minor min	7676	3.0	.06	
42.0 - 49.0	qutz lenses in grn ser sch, py	7677	7.0	.06	
49.0 - 64.0	grn ser sch approach chl-ser				

Logged by JDB

Hole No. U-B760

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B759
BEARING N60W
DIP AT COLLAR -45
LENGTH 276.0
LAT. 13451.72
DEP. 7766.09
ELEV. 5438
DATE COMPLETED
PURPOSE Lower Orebody Expl.
SHAFT 2
LEVEL 575
WORKING B-403N
SECTION 1700N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 2.0	cs.				
2.0 - 117.5	m.g. mass to sly sch grs with chty-ep sect, ep threads				
117.5 - 129.0	F.g. grn grs sch				
129.0 - 151.0	gry-grn chl-ser sch				
151.0 - 160.0	gry-buff ser sch				
160.0 - 165.0	20% bx qutz-carb, py, aspy, tr. sp	7661	5.0	.61	3.050
165.0 - 169.5	As above	7662	4.5	1.68	7.560
169.5 - 172.0	qutz lenses in ser sch, minor min	7663	2.5	.40	1.000
172.0 - 178.0	30% dk qutz w coarse carb, minor min	7664	6.0	.22	1.320
178.0 - 183.5	qutz lenses in ser sch, minor min	7665	5.5	.25	1.375
183.5 - 189.0	buff ser sch w few qutz lenses	7666	5.5	.18	.990
189.0 - 195.0	As above	7667	6.0	.07	.420
195.0 - 200.0	30% qutz-carb, minor sp & gry min	7668	5.0	.46	2.300

Logged by JDB

Hole No. U-B759

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
200.0 - 206.0	As above				
206.0 - 212.0	20% qutz, py, aspy, tr sp & gry min	7669	6.0	.76	4.560
212.0 - 218.0	As above	7670	6.0	1.48	8.880
218.0 - 223.0	As above w decreas qutz	7671	6.0	1.06	6.360
223.0 - 228.5	As above	7672	5.0	.44	2.200
228.5 - 235.0	qutz lenses in ser sch, local min	7673	5.5	.61	3.355
235.0 - 241.5	30% qutz-carb, py, aspy	7674	6.5	.45	2.925
241.5 - 258.0	buff ser sch	7675	6.5	.97	6.305
					52.600
258.0 - 266.5	grn gran chl-ser sch				
266.5 - 276.0	m.g. grn grs sch				

From	To	C.L.	Grade
160.0	241.5	81.5	.64

Dip Tests

Depth	Read	Correct
150	29	25
276	14½	11½

SHEET No. 2

HOLE No. U-B759

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B 759 | SHAFT B
BEARING N 60 W | LAT. 13451.72 | DATE COMPLETED | LEVEL 575
DIP AT COLLAR -45 | DEP. 7766.09 | PURPOSE Dev. | WORKING B-403 N
LENGTH 428 | ELEV. 5438 | SECTION 1700 N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
276.0 - 283.0	chl ser sch w qtz carb lenses: minor min	10852	7.0	.02	
283.0 - 286.5	grs sch w qtz carb lenses: minor min	10853	3.5	.01	
286.5 - 296.0	dk grn sch grs				
296.0 - 356.0	f. g. to m.g. grs w hem & ep				
356.0 - 392.0	as above w gry fl				
392.0 - 393.0	grs sch w qtz carb lenses: py	10854	1.0	.03	
393.0 - 399.0	f. g. dk grn grs				
399.0 - 400.0	grs sch w heavy pyrite	10855	1.0	.12	
400.0 - 428.0	c. g. grs w hem & ep				

Dip Test

Depth	Read	Corr.
428	14°	11°

Logged by Deepened

Hole No. U-B 759

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B758
BEARING S60E
DIP AT COLLAR 40
LENGTH 126.0

LAT. 13022.45
DEP. 7509.18
ELEV. 5591

DATE COMPLETED
PURPOSE B-312 stope Layout

SHAFT 2
LEVEL 425
WORKING B-312N
SECTION 1200N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 7.0	70% gry qutz-carb, py, aspy, v.g.	7038	6.5/7.0	(4.68 (3.24	27.720
7.0 - 13.0	90% dk blue qutz; sparing min, v.g.	7039	6.0	(4.03 (5.43	28.380
13.0 - 17.0	As above, 2" heavy v.g. removed	7040	4.0	(12.92 (20.50	(51.680 (20.000
17.0 - 22.0	As above; v.g. (plentiful)	7041	5.0	4.53	22.650
22.0 - 26.5	50% dk qutz; py, minor aspy	7042	4.5	.89	4.005
26.5 - 33.5	grn ser sch min w sp	7043	7.0	.16	1.120
33.5 - 38.0	30% qutz-carb; py, aspy, sp, gry min	7044	4.5	.45	2.475
38.0 - 42.5	50% dk qutz; well min w sp & gry min, v.g.	7045	4.5	(1.57 (1.57	7.065
42.5 - 50.0	80% qutz-carb richly min w sp & gry min; plent. v.g.	7046	7.5	(5.71 (7.00	(47.625 (37.500
50.0 - 56.5	barren qutz-carb in ser sch	7047	6.5	.18	1.170
56.5 - 62.0	80% qutz-carb, sparing aspy & sp; Fine v.g.	7048	5.5	(1.53 (1.06	7.095
62.0 - 67.0	60% qutz-carb well min w sp. Fine v.g.	7049	5.0	(1.19 (1.42	6.500
67.0 - 71.5	As above; v.g.	7050	4.5	(3.82 (4.26	18.180

Logged by JDB

Hole No. U-B758

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
71.5 - 76.5	gry ser sch., minor min	7651	5.0	.40	2.000
76.5 - 83.0	50% dk qutz-carb intere w gry ser sch; py; v.g.	7652	6.5	(1.05 (1.06	6.825
83.0 - 90.0	As above; v.g.	7653	7.0	(1.20 (2.07	11.480
90.0 - 91.0	As above; v.g.	7654	1.0	(1.07 (2.78	1.920
91.0 - 96.0	20% qutz-carb; minor min	7655	5.0	.93	4.650
96.0 - 101.5	qutz-carb lenses in ser sch; minor min	7656	5.5	.77	4.235
101.5 - 126.0	buff ser sch				256.775

From	To	C.L.	Grade Uncut	Grade Cut
0	101.5	101.5	2.52	2.11

SHEET No. 2

HOLE No. U-B758

GIANT YELLOWKNIFE GOLD MINES LIMITED

CORE RECORD

HOLE No. U-B757
BEARING N60W
DIP AT COLLAR +60
LENGTH 60.0

LAT. 13551.91
DEP. 7593.82
ELEV. 5446.5

DATE COMPLETED
PURPOSE Ore Def.

SHAFT 2
LEVEL 575
WORKING B-409N
SECTION 1700N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 5.5	20% qutz., local min	7032	5.5	.29	
5.5 - 9.5	silic ser sch, fine po (tuffac.?)	7033	4.0	.09	
9.5 - 59.0	silic ser sch, finely dissem po (tuffac?)				
	t.s. 14.5 - 18.5	7034	4.0	.61	
	t.s. 22.0 - 27.0	7035	5.0	.60	
	t.s. 27.0 - 30.5	7036	3.5	.10	
	t.s. 54.5 - 59.0	7037	4.5	.26	
59.0 - 60.0	Chl-ser sch				
	t.s. 9.5 - 14.5	7657	5.0	.01	
	t.s. 18.5 - 22.0	7658	3.5	.01	

From	To.	C.L.	Grade
0	5.5	5.5	.29
14.5	18.5	4.0	.61
22.0	27.0	5.0	.60
54.5	59.0	4.5	.26

Logged by JDB

Hole No. U-B757

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B756
BEARING 360E
DIP AT COLLAR +25
LENGTH 90.0
LAT. 13063.58
DEP. 7537.79 410W
ELEV. 5597
DATE COMPLETED
PURPOSE No. 1 shoot Def.
SHAFT 2
LEVEL 425
WORKING 2-312N
SECTION 1250N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 7.0	40% lent qutz., py, asoy, gry min	7027	7.0	1.36	9.520
7.0 - 14.0	qutz lenses in ser sch, minor min	7028	7.0	.53	3.710
14.0 - 20.0	As above	7029	6.0	.20	1.200
20.0 - 54.0	f.g.-m.g. grn grs sch, calc.				14.430
54.0 - 64.0	f.g. buff-grn chl-ser sch				
64.0 - 70.0	30% qutz-carb, sparing min	7030	6.0	.57	3.420
70.0 - 73.5	qutz lenses in ser sch; minor min; strong Fault zone 73.5	7031	3.5	.23	.805
					4.225
73.5 - 77.0	gry-grn chl-ser sch				
77.0 90.0	f.g. mass grs w ep threads.				

From	To	C.L.	Grade
0	20.0	20.0	.72
64.0	73.5	9.5	.44

Logged by JDB

Hole No. U-B756

GIANT YELLOWKNIFE GOLD MINES LIMITED

CORE RECORD

HOLE No. U-B755 | SHAFT 2

BEARING N60W | LAT. 13510.76 | DATE COMPLETED | LEVEL 575

DIP AT COLLAR +50 | DEP. 7565.54 | PURPOSE Ore Def. | WORKING B-409N

LENGTH 87.0 | ELEV. 5446.5 | SECTION 1650N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 79.0	gry ser sch w silic sect carrying py and aspy; minor local po; tuffac (?) H_2O at 35'				
	t.s. 10.0 - 15.0	7024	5.0	.47	
	t.s. 62.5 - 65.5	7025	3.0	.24	
	t.s. 72.0 - 73.5	7026	1.5	.34	
79.0 - 87.0	f.g. grn grs sch				
	t.s. 5.0 - 10.0	7659	5.0	.04	
	t.s.15.0 - 17.0	7660	2.0	.05	

From	To	C.L.	Grade
10.0	15.0	5.0	.47
62.5	65.5	3.0	.24
72.0	73.5	1.5	.34

Logged by JDB

Hole No. U-B755

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-2 754

BEARING S60E

DIP AT COLLAR -31°

LENGTH 190.0

LAT. 13022.45

DEP. 7509.18

ELEV. 5597

DATE COMPLETED

PURPOSE No. 1 Shoot Definition

SHAFT 2

LEVEL 425

WORKING 8312 N-Dr.

SECTION 1200N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	GOLD ASSAYS OZ./TON
0.0 - 5.0	40% qutz-carb lenses in ser sch min with py aspy and grey min, well developed lenses of qutz and carb alternate in gray-grn ser sch	6048	5.0	2.40	12.000
5.0 - 10.0	As above	6049	5.0	1.19	5.950
10.0 - 14.0	90% blue qutz with minor traces of carb min with, py, fine aspy and traces of sph-V.G. throughout-remarkable change in appearance after 10.0	6050	4.0	(7.62 (7.17	(29.560 (20.000
14.0 - 19.0	As above, traces of V.G. throughout	7001	5.0	(7.34 (6.83	(35.400 (25.000
19.0 - 24.0	As above with VG throughout	7002	5.0	(8.85 (9.85	(46.750 (25.000
24.0 - 29.0	As above with VG throughout	7003	5.0	(3.80 (1.76	13.900
29.0 - 32.0	As above with V.G. - vuggy carb at 32.0 indicating possible fault zone	7004	3.0	(10.30 (8.36	(27.990 (15.000
32.0 - 35.5	30% qutz-carb lenses in ser sch min with py aspy and sph, speck of v.G. at 32.5	7005	3.5	(2.31 (2.02	7.560
					179.110 124.410
35.5 - 41.0	Dk grn chl-ser sch				
41.0 - 62.0	Lt to dk gray-grn ser sch with local carb lenses				

Logged by [illegible]

Hole No. U-2754

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
62.0 - 73.0	Fg gray-grn chl-ser sch with gradation to ser sch around 73.0				
73.0 - 84.0	Fg gray compact ser sch				
84.0 - 89.0	60% qutz-carb lenses in ser sch min with py and sspy	7010	5.0	.82	4.100
89.0 - 94.0	As above but with increasing blue qutz	7011	5.0	.92	4.600
94.0 - 100.0	30% qutz-carb lenses in ser sch min with py and sspy	7012	6.0	.73	4.330
100.0 - 105.0	As above	7013	5.0	.43	2.150
105.0 - 125.0	Fg gray ser sch with local carb lenses and neg min				
125.0 - 137.0	Fg compact light gray ser sch, possibly tuffaceous				
137.0 - 157.0	Fg grn grs sch-gradation towards sch grs at 157.0				
157.0 - 175.0	M to fg. grn sch grw				
175.0 - 190.0	M to fg mass grs with definite traces of spherulitic pillow structure				

From	To	C.L.	Grade Uncut	Grade Cut
0	35.5	35.5	5.04	3.50
84.0	105.0	21.0	.72	--

Dip Test

Depth	Read	Correct
180	33	29½

SHEET No. 2

HOLE No. U-2754

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8 753 | SHAFT 2

BEARING -- | LAT. 134.50 | DATE COMPLETED | LEVEL 575

DIP AT COLLAR -90° | DEP. 7770 | PURPOSE Lower Orebody Exploration | WORKING B403N-Dr.

LENGTH 246.0 | ELEV. 5437.5 | SECTION 1700N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 2.0	Casing				
2.0 - 46.0	M to f.g. grn greenstone with epidote prominent throughout				
46.0 - 106.0	M g green to gray grn grs sch, in part sch grs				
106.0 - 117.0	F g gray-grn chl-ser sch				
117.0 - 130.0	F g gray compact ser sch with local carb lenses				
130.0 - 135.0	Qutz-carb lenses in ser sch spar min	7006	5.0	.03	
135.0 - 140.0	As above	7007	5.0	.03	
140.0 - 144.0	As above	7008	4.0	.04	
144.0 - 158.0	Fg gray ser sch with local carb lenses				
158.0 - 164.0	Qutz-carb lenses in ser sch spar min with pyrrhitite and minor py	7009	6.0	.02	
164.0 - 177.0	F.g. gray compact ser sch				
177.0 - 181.0	Qutz-carb lenses in ser sch pin with py, 1 ft. core ground	7014	3.0/4.0	.05	
181.0 - 210.5	M to fg green to gray-grn chl-ser sch				
210.5 - 219.0	Fairly sharp contact at 210.5 indicating dyke-possibly diabase-very fine grained becoming medium to coarse grained towards 216.0				

Logged by J.H. | Hole No. U-8 753

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
219.0 - 246.0	M g dark green sch grs, in part mass grs				

SHEET No. 2

HOLE No. U-2763

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B752 | SHAFT 2

BEARING -- | LAT. 13024 | DATE COMPLETED March 8, 1950 | LEVEL 425

DIP AT COLLAR 490 | DEP. 7505 | PURPOSE 425 | WORKING B312N-Dr.

LENGTH 59.0 | ELEV. 5599 | No. 1 Shoot Definition | SECTION 1200N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 1.0	Casing				
1.0 - 6.0	60% qutz-carb lenses min with py and aspy	6041	5.0	.92	4.600
6.0 - 10.0	As above	6042	4.0	.96	3.840
10.0 - 15.0	30% qutz-carb lenses in ser sch well min with py and minor aspy	6043	5.0	.74	3.700
15.0 - 20.0	As above	6044	5.0	.16	.800
20.0 - 26.0	Qutz-carb lenses in ser sch	6045	6.0	.03	
26.0 - 31.0	30% qutz-carb lenses spar min	6046	5.0	1.45	7.250
31.0 - 37.0	As above	6047	6.0	.63	3.780
					24.150
37.0 - 59.0	Fg gray compact ser sch				

From	To	S.L.	Grade
1.0	37.0	36.0	.67

Logged by JAH | Hole No. U-B752

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-3751 | SHAFT 2

BEARING N60W | LAT. 13003.45 | DATE COMPLETED | LEVEL 575

DIP AT COLLAR +60° | DEP. | PURPOSE No. 1 Shoot | WORKING B4083-Dr.

LENGTH 79.0 | ELEV. 5446 | Definition | SECTION 1100N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 1.0	Casing				
1.0 - 15.0	Fg grn grs sch				
15.0 - 23.0	Fg gray-grn chl-ser sch				
23.0 - 25.0	Fg gray ser sch				
25.0 - 29.0	20% qutz-carb lenses in ser sch spar min with py and aspy	6031	4.0	.03	.120
29.0 - 33.0	60% qutz-carb lenses well min with py aspy and traces of sph	6032	4.0	.88	3.520
33.0 - 36.0	90% blue qutz with minor carb min with py aspy and sph, V.G. prominent	6033	5.0	(3.86 (7.77	25.000
36.0 - 41.5	30% qutz-carb well min with py and aspy	6034	3.5	.07	.245
41.5 - 62.0	Fg gray compact ser sch				28.885
62.0 - 79.0	Fg gray grn chl-ser sch				

From	To	C.L.	Grade
25.0	41.5	16.5	1.75

Logged by JAH | Hole No. U-3751

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-S 750
BEARING N 60W
DIP AT COLLAR 450
LENGTH 67.0
LAT. 13026.85
DEP. 7501.56
ELEV. 5599
DATE COMPLETED
PURPOSE No. 1 Shoot Definition
SHAFT 2
LEVEL 425
WORKING S 312N-Dr.
SECTION 1200N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 5.0	80% blue qutz with minor carb min with py aspy and gray min	6035	5.0	1.34	
5.0 - 21.0	F g gray compact ser sch				
21.0 - 25.0	60% qutz-carb lenses in ser sch min with py and aspy.	6036	4.0	.95	3.800
25.0 - 30.0	As above but with decreasing min	6037	5.0	.64	3.200 / 7.000
30.0 - 34.0	20% qutz-carb lenses in ser sch spar min	6038	4.0	.07	
34.0 - 40.0	Qutz carb lenses in ser sch	6039	6.0	.07	
40.0 - 46.0	As above	6040	6.0	.07	
46.0 - 67.0	F g gray ser sch with local carb lenses- encountered water at 66'				

From	To	O.L.	Grade
0	5.0	5.0	1.34
21.0	30.0	9.0	.77

Logged by [illegible]

Hole No. U-S750

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B 749 | SHAFT 2

BEARING 360E | LAT. 13063.58 | DATE COMPLETED | LEVEL 425

DIP AT COLLAR 45 114 | DEP. 7537.79 410W | PURPOSE No. 1 Shoot Def. | WORKING B312N-Dr.

LENGTH 62.0 | ELEV. 5599 | SECTION 1250N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 3.0	50% qutz lenses in ser sch, ½' core ground	6011	2.5/3.0	1.08	
3.0 - 12.0	Fg gray ser sch				
12.0 - 17.0	40% bx like qutz-carb well min with py and aspy	6012	5.0	.05	
17.0 - 22.0	50% qutz-carb lenses well min with fine aspy and py	6013	5.0	.37	
22.0 - 27.0	As above	6014	5.0	.22	
27.0 - 32.0	As above	6015	5.0	.28	
32.0 - 39.5	Fg gray ser sch				
39.5 - 46.0	Qutz carb lenses in ser sch	6016	6.5	.05	
46.0 - 51.0	70% qutz-carb lenses in ser sch well min with py and aspy	6017	5.0	.22	1.100
51.0 - 56.0	As above but with traces of gray min, V.G. at 53.0	6018	5.0	(.76 (.77	3.500
56.0 - 62.0	40% qutz-carb lenses in ser sch min with py and aspy	6019	6.0	.19	1.140 6.040

To be deepened

From	To	C.L.	Grade
0	3.0	3.0	1.08
12.0	32.0	20.0	.23
46.0	62.0	16.0	.37

Logged by [illegible] | Hole No. U-B749

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
	Deepending of U-B 749				
62.0 - 66.0	30% qutz-carb lenses in ser sch min with py and aspy	7015	4.0	.82	6.040 3.280
66.0 - 71.0	80% blue qutz with minor carb min with py and fine aspy, V.C. at 68.0 and 70.0	7016	5.0	(5.03 (6.68	29.250 (25.000
71.0 - 76.0	As above with V.G. well distributed	7017	5.0	(4.58 (5.97	26.350 25.000
76.0 - 81.0	As above, V.C. at 80.0	7018	5.0	(.63 (.59	3.050
81.0 - 86.0	60% qutz-carb lenses min with py and aspy	7019	5.0	(.27 (.35	1.550
86.0 - 92.0	As above but with traces of sph, VG at 88.0	7020	6.0	(2.31 (2.04	13.020 82.540
92.0 - 97.0	20% qutz-carb in 3' sect, followed by ser sch	7021	5.0	1.09	5.450
97.0 - 102.0	As above	7022	5.0	.40	2.000
102.0 - 106.5	buff ser sch, minor qutz & min; fault	7023	4.5	.02	89.090
106.5 - 114.0	Zone 106.5 mass. m.g. grn grs w chty cp sect.				

From	To	C.L.	Grade
46.0	102.0	56.0	1.60

SHEET No. 2

HOLE No. U-3749

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B748 | SHAFT 2

BEARING --- | LAT. 7370.5 | DATE COMPLETED March 6, 1950 | LEVEL 575

DIP AT COLLAR +90° | DEP. 13045.5 | PURPOSE No. 1 Shoot | WORKING 94083-Dr.

LENGTH 116.0 | ELEV. 5446 | Definition | SECTION 1100N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 1.0	Casing				
1.0 - 25.0	Mg green to gray- grn grn sch				
25.0 - 36.0	Gradation from grs sch to chl-ser sch with brown alt flecks.				
36.0 - 47.5	Fg gray ser sch.				
47.5 - 51.0	40% qutz-carb lenses well min with py and aspy	6020	3.5	.26	.910
51.0 - 56.0	80% blue qutz min with py and aspy, V.G. at three places	6021	5.0	(1.01 (.64	4.100
56.0 - 61.0	As above, prominent V.G. from 56.0 to 57.0	6022	5.0	(2.00 (5.62	19.050
61.0 - 66.0	40% qutz-carb lenses well min with py and aspy, traces of sph	6023	5.0	(1.57 (1.54	7.750
66.0 - 71.0	As above	6024	5.0	.73	2.650
71.0 - 76.0	90% blue qutz min with py aspy sph and traces of gray min, prominent V.G. throughout, 1" sample of prominent V.G. taken from core.	6025	5.0	(5.21 (7.12	30.300
76.0 - 81.0	As above, prominent V.G.	6026	5.0	(8.39 (9.43	44.300
81.0 - 86.0	As above, V.G.	6027	5.0	(.42 (.31	1.800
86.0 - 91.0	30% qutz-carb lenses in ser sch, spar min.	6028	5.0	.04	.200

Logged by [illegible] | Hole No. U-B748

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
91.0 - 96.0	20% qutz-cart lenses in ser sch, spar min	6029	5.0	.04	.200
96.0 - 101.0	As above	6030	5.0	.03	.150
101.0 - 116.0	Fg gray ser sch				111.910

N.B.- Water encountered at 96'

	From	To	C.L.	Grade
	47.5	86.0	38.5	2.89
alt.	47.5	101.0	53.5	2.09

SHEET No. 2

HOLE No. U-5742

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8747 | SHAFT 2

BEARING -- | LAT. 13067 | DATE COMPLETED | LEVEL 425

DIP AT COLLAR 490 | DEP. 7535 | PURPOSE No. 1 Shoot | WORKING B312N-Dr.

LENGTH 80.0 | ELEV. 5599 | Definition | SECTION 12500N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
1.0 - 1.0	Casing				
1.0 - 6.0	30% qutz-carb lenses in ser sch min with py and aspy	3996	5.0	.13	
6.0 - 11.0	60% qutz-carb lenses min with py asph and traces of sph	3997	5.0	.39	
11.0 - 16.0	As above except no traces of sph	3998	5.0	.65	
16.0 - 21.0	As above	3999	5.0	.22	
21.0 - 26.0	30% qutz-carb lenses and as above	4000	5.0	.13	
26.0 - 33.0	Qutz-carb lenses in ser sch, spar min	6001	7.0	.01	
33.0 - 39.0	As above but with increasing min	6002	6.0	.09	
39.0 - 44.0	40% qutz-carb lenses in ser sch min with py and aspy	6003	5.0	.13	.650
44.0 - 50.0	60% qutz-carb min as above	6004	6.0	.13	.780
50.0 - 55.0	As above	6005	5.0	.06	.300
55.0 - 60.0	As above	6006	5.0	.11	.550
60.0 - 66.0	Fg grey ser sch with qutz-carb lenses	6007	6.0	.09	.540

Logged by [illegible] | Hole No. U-8747

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
66.0 - 71.0	30% qutz-carb lenses in ser sch min with py and aspy	6008	5.0	.01	
71.0 - 76.0	As above	6009	5.0	.01	
76.0 - 82.0	Qutz-carb lenses in ser sch spar min with py	6010	5.0	.04	
82.0 - 89.0	Fg gray ser sch with local carb lenses				

From	To	C.L.	Grade
1.0	26.0	25.0	.30
39.0	60.0	21.0	.10

SHEET No. 2

HOLE No. U-3242

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-3746 | SHAFT 2

BEARING --- | LAT. 13510 | DATE COMPLETED March 5, 1950 | LEVEL 575

DIP AT COLLAR 490° | DEP. 7567 | PURPOSE Ore Def. | WORKING 3409N-Dr.

LENGTH 58.0 | ELEV. 5446.5 | SECTION 16500'

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 1.0	Casing				
1.0 - 6.0	20% qutz-carb lenses in ser sch	3988	5.0	.05	.250
6.0 - 11.0	70% qutz-carb lenses in ser sch min with py aspy and sph	3989	5.0	.11	.550
11.0 - 16.0	40% qutz-carb and as above	3990	5.0	.10	.500
16.0 - 23.0	20% qutz-carb lenses in ser sch (tuff like) spar min with py and aspy	3991	7.0	.01	1.300
23.0 - 29.0	As above	3992	6.0	.03	
29.0 - 34.0	40% qutz-carb lenses in ser sch min with py and aspy	3993	5.0	.04	
34.0 - 39.0	80% qutz-carb wall min with py aspy and minor sph	3994	5.0	(.97 (1.00	4.900
39.0 - 44.5	60% qutz-carb and as above	3995	5.5	(.46 (.47	2.530
44.5 - 58.0	Fg gray-grn ser sch, in part chl-ser sch-sharp contact at 44.5, local carb lenses with nog min				

From	To	C.L.	Grade
1.0	16.0	15.0	.09
34.0	44.5	10.5	.70

Logged by [illegible] | Hole No. U-3 746

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8 745
BEARING N60W
DIP AT COLLAR 45°
LENGTH 88.0

LAT. 13068.04
DEP. 7530.00 4/9W
ELEV. 5599

DATE COMPLETED March 5/50
PURPOSE No. 1 Shoot Definition

SHAFT 2
LEVEL 425
WORKING 83120-Dr.
SECTION 1250N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 9.5	Fg gray ser sch				
9.5 - 15.0	50% qutz-carb lenses in ser sch min with py and aspy	3967	5.5	.20	1.100
15.0 - 20.0	30% qutz-carb lenses and as above	3968	5.0	.17	.850
20.0 - 26.0	As above but with local sections of 90% blue qutz	3969	6.0	.75	4.500
					6.710
26.0 - 31.0	As above	3970	5.0	.05	
31.0 - 36.0	As above, 1 ft. core ground at 35.0	3971	4.0/5.0	.01	
36.0 - 39.0	As above- gradation to ser sch ground 39.0	3972	3.0	.08	
39.0 - 48.0	Fg gray ser sch				
48.0 - 53.0	Qutz-carb lenses in ser sch spar min	3973	5.0	.03	
53.0 - 58.0	As above	3974	5.0	.12	
58.0 - 63.0	As above but with increasing min	3975	5.0	.04	
63.0 - 68.0	As above	3976	5.0	.12	
68.0 - 73.0	40% qutz-carb lenses in ser sch min with py and aspy	3977	5.0	.13	

Logged by JAM

Hole No. U-8745

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
73.0 - 78.0	As above	3978	5.0	.10	
78.0 - 81.0	Qutz-carb lenses in ser sch	3979	3.0	.06	
81.0 - 83.0	Fg gray ser sch - Hole struck water course at 83.0				

From	To	C.L.	Grade
9.5	26.0	16.5	.40

SHEET No. 2

HOLE No. U-3745

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B744
BEARING ---
DIP AT COLLAR +90°
LENGTH 71.0
LAT. 13519.5
DEP. 7597.0
ELEV. 5446.5
DATE COMPLETED March 4/1950
PURPOSE Ore def.
SHAFT 2
LEVEL 575
WORKING B409N-Dr.
SECTION 1700N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 1.0	Casing				
1.0 - 6.0	70% qutz with minor carb min with py aspy and minor sph	3983	5.0	.24	
6.0 - 11.0	As above	3984	5.0	.33	
11.0 - 16.0	As above	3985	5.0	.21	
16.0 - 21.0	30% qutz-carb lenses and as above	3986	5.0	.06	
21.0 - 24.5	As above	3987	3.5	.13	
24.5 - 57.0	Tg gray compact ser sch				

From	To	C.L.	Grade
1.0	16.0	15.0	.26

Logged by JAH

Hole No. U-B 744

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8743
BEARING ----
DIP AT COLLAR -90°
LENGTH 48.0
LAT. 13110
DEP. 7559.5
ELEV. 5599
DATE COMPLETED
PURPOSE No. 1 Shoot Definition
SHAFT 2
LEVEL 425
WORKING B312N-Dr.
SECTION 1300N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 1.0	Casing				
1.0 - 5.0	30% qutz-with minor carb well min with py	3980	4.0	1.00	
5.0 - 30.0	Fg grey to grey-grn dense ser sch				
30.0 - 34.0	Qutz-carb leases in ser sch	3981	4.0	.06	
34.0 - 38.0	As above	3982	4.0	.03	
38.0 - 48.0	Fg grey ser sch				

From	To	C.L.	Grade
1.0	5.0	4.0	1.00

Logged by JAH

Hole No. U-8743

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8742 | SHAFT 2
BEARING 360S | LAT. 13547.63 | DATE COMPLETED | LEVEL 575
DIP AT COLLAR Hor. | DEP. 7601.22 | PURPOSE Ore Def. | WORKING B-409N-Dr.
LENGTH 48.0 | ELEV. 542.2 | SECTION 1700B

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 4.0	60% qutz-carb in ser sch min with py aspy and sph	2444	4.0	.35	1.400
4.0 - 10.0	20% qutz-carb lenses in ser sch spar min with py and aspy	2445	6.0	.17	1.020
					2.420
10.0 - 38.0	Fg gray compact ser sch with a few carb lenses, possibly tuff, in part				
38.0 - 48.0	Fg gray to gray-grn ser sch				

From	To	C.L.	Grade
0	10.0	10.0	.24

Logged by JHS | Hole No. U-8742

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8741
BEARING N60W
DIP AT COLLAR 45°
LENGTH 50.0

LAT. 13110.58
DEP. 7556.17
ELEV. 5599

DATE COMPLETED
PURPOSE No. 1 Shoot Def.

SHAFT 2
LEVEL 425
WORKING 331W-Dr
SECTION 1300W

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	GOLD ASSAYS OZ./TON
0.0 - 5.0	60% qutz and minor carb well min with py and minor aspy	2446	5.0	.29	1.450
5.0 - 10.0	30% qutz-carb and as above	2447	5.0	.04	.200
10.0 - 15.0	As above	2448	5.0	.29	1.450
15.0 - 21.0	As above but increasing proportion of blue qutz	2449	6.0	.14	.840
21.0 - 26.0	20% qutz-carb lenses in ser sch	2450	5.0	.03	.150
26.0 - 29.0	40% qutz-carb min with py and aspy	3966	3.0	.33	.990
29.0 - 50.0	Sp gray ser sch with local carb lenses.				5.080

From	To	C.L.	Grade
0	29.0	29.0	.17

Logged by JAK

Hole No. U-8741

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-3740
BEARING N 60W
DIP AT COLLAR Hor.
LENGTH 50.0

LAT. 13551.91
DEP. 7593.82
ELEV. 5442

DATE COMPLETED
PURPOSE Ore Def.

SHAFT 2
LEVEL 575
WORKING 2409N-Dr.
SECTION 1700 N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 5.0	50% qutz-carb lenses in ser sch min with py, aspy and minor sph	2439	5.0	.16	.800
5.0 - 8.0	20% qutz-carb lenses and as above	2440	3.0	.11	.330
					1.130
8.0 - 16.0	Fg gray compact ser sch				
16.0 - 19.0	Fg gray ser sch with local carb lenses min with pyrrhotite	2441	3.0	.02	
19.0 - 38.0	Fg gray ser sch, mottled appearance				
38.0 - 43.0	20% qutz-carb lenses spar min	2442	5.0	.02	
43.0 - 47.0	Qutz-carb lenses in ser sch spar min as above	2443	4.0	.03	
47.0 - 50.0	Fg gray compact ser sch				

From	To	C.L.	Grade
0	8.0	8.0	.14

Logged by dal

Hole No. U-3740

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8739 | SHAFT 2
BEARING N60W | LAT. 13510.76 | DATE COMPLETED March 3/50 | LEVEL 575
DIP AT COLLAR Hor. | DEP. 7565.54 610W | PURPOSE Ore Def. | WORKING 8400W-Dr.
LENGTH 51.0 | ELEV. 5442 | SECTION 1650W

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 6.0	Fg grey ser sch with local carb lenses				
6.0 - 11.0	40% qutz-carb lenses in ser sch min with py aspy and sph	2422	5.0	1.93	9.650
11.0 - 16.0	80% qutz and minor carb well min with py aspy and sph, V.C. at 14.0	2423	5.0	(.91 (2.28	7.950
16.0 - 21.0	As above, abund sph, speck of V.C. at 18.5	2424	5.0	(3.21 (3.52	16.800
21.0 - 27.0	40% qutz-carb lenses in ser sch well min with py, aspy and sph-fine V.C.	2425	6.0	(6.54 (5.83	37.080
27.0 - 32.0	As above	2426	5.0	.34	1.700
32.0 - 37.0	40% qutz- in ser sch min with py aspy and sph-short section of chl-ser sch with no qutz	2436	5.0	.89	4.450
37.0 - 42.0	40% qutz lenses in ser sch min as above	2437	5.0	.57	2.850
42.0 - 45.5	As above	2438	3.5	.61	2.135 83.615
45.5 - 51.0	Fg grey to grey-grn ser sch				

From	To	C.L.	Grade
6.0	45.5	39.5	2.11

Logged by JAS | Hole No. U-8739

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8 738
BEARING 360E
DIP AT COLLAR Hor.
LENGTH 34.0

LAT. 13503.80
DEP. 7577.58
ELEV. 5442

DATE COMPLETED March 2, 1950
PURPOSE Ore Def.

SHAFT 2
LEVEL 575
WORKING 8409N-Dr.
SECTION 1650N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 5.0	40% qutz-carb lenses in scr sch min with py, aspy and traces of sph	2416	5.0	.65	3.250
5.0 - 10.0	As above but with increasing qutz as well as sph min	2417	5.0	.21	1.050
10.0 - 15.0	20% qutz-carb lenses in scr sch spar min with py and aspy	2418	5.0	.56	2.800
15.0 - 20.0	60% qutz with minor carb min with py aspy and sph	2419	5.0	.37	1.850
20.0 - 25.0	As above with V.G. at 23.5	2420	5.0	(2.21 (2.21	11.050
25.0 - 28.0	Fg gray scr sch with local qutz lenses	2421	3.0	.04	20.000
28.0 - 34.0	Fg gray scr sch with gradation to chl-scr sch				

From	To	C.L.	Grade
o	25.0	25.0	.80

Logged by MAH

Hole No. U-8738

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8737
BEARING N60W
DIP AT COLLAR -45°
LENGTH 127.0

LAT. 13169.83
DEP. 7553.47 450W
ELEV. 5592

DATE COMPLETED
PURPOSE No. 1 Shoot Definition

SHAFT 2
LEVEL 425
WORKING 3312N-Dr
SECTION 1350N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 1.0	Casing				
1.0 - 6.0	50% qutz-carb min with py and aspy	2405	5.0	.42	2.100
6.0 - 11.0	As above	2406	5.0	.61	3.050
11.0 - 15.0	30% qutz-carb min as above	2407	4.0	.58	2.320
					7.470
15.0 - 20.0	Qutz-carb lenses in ser sch min with py	2408	5.0	.03	.150
20.0 - 26.0	Fg gray ser sch with local carb lenses, 1' core ground	2409	5.0/6.0	.10	.600
26.0 - 31.0	40% qutz with minor carb min with py and aspy	2410	5.0	.07	.350
31.0 - 36.0	60% qutz and as above	2411	5.0	.33	1.650
36.0 - 41.0	As above	2412	5.0	.30	1.500
41.0 - 46.0	As above	2413	5.0	.21	1.050
46.0 - 51.0	As above but with increasing carb	2414	5.0	.17	.850
51.0 - 58.0	20% qutz-carb lenses in ser sch scar min with py and aspy	2415	7.0	.22	1.540
					4.590
58.0 - 67.0	Fg gray ser sch				
67.0 - 73.0	20% qutz-carb lenses in ser sch scar min with py and aspy	2427	6.0	.34	2.040

Logged by JAH

Hole No. U-8737

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
73.0 - 78.0	60% qutz-carb lenses and as above	2428	5.0	.34	1.700
78.0 - 84.0	As above	2429	6.0	.31	1.860
84.0 - 90.0	As above	2430	6.0	.32	1.920
90.0 - 96.0	As above but with increasing carb, 1 ft. core ground at 96.0	2431	5.0/6.0	.35	2.100 / 9.680
96.0 - 102.0	Fg gray ser sch with local carb lenses, 1ft core ground at 102.0	2432	5.0/6.0	.04	
102.0 - 107.0	Qutz carb lenses in ser sch min with py and minor aspy	2433	5.0	.09	
107.0 - 112.0	As above	2434	5.0	.04	
112.0 - 117.0	As above	2435	5.0	.03	
117.0 - 127.0	Fg gray ser sch with local carb lenses and neg min				

From	To	C.L.	Grade
1.0	15.0	14.0	.53
31.0	58.0	27.0	.24
67.0	96.0	29.0	.33

SHEET No. 2

HOLE No. U-3737

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-3736
BEARING N60W
DIP AT COLLAR Hor.
LENGTH 120.0

LAT. 13169.83
DEP. 7553.47
ELEV. 5596

DATE COMPLETED
PURPOSE No. 1 Shoot Expl.

SHAFT 2
LEVEL 425
WORKING B-312N
SECTION 1350N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 7.0	30% qutz, pt chty; minor min	7601	7.0	.07	
7.0 - 12.0	silic ser sch; minor min	7602	5.0	.02	
12.0 - 16.0	As above	7603	4.0	.04	
16.0 - 72.0	buff ser sch, chty tn; local qutz; may in part be tuffac				
72.0 98.0	grn-buff chl-ser sch, minor qutz-carb				
98.0 - 120.0	grn grs sch				

Logged by JDB

Hole No. U-3736

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8735
BEARING N60W
DIP AT COLLAR -65°
LENGTH 127.0
LAT. 13143.5
DEP. 7502.3
ELEV. 5590
DATE COMPLETED Feb. 28/50
PURPOSE No. 1 Shoot Def.
SHAFT 2
LEVEL 425
WORKING 8308N-Dr.
SECTION 1300N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 2.0	Casing				
2.0 - 8.0	Fg gray ser sch with qutz-carb lenses spar min with py	3933	7.0	.04	
8.0 - 13.0	60% blue qutz min with py and aspy	3934	5.0	.34	1.700
13.0 - 18.0	As above but with increasing carb content	3935	5.0	.34	1.700
18.0 - 23.0	As above	3936	5.0	.46	2.300
23.0 - 28.0	As above	3937	5.0	.34	1.700
28.0 - 34.0	30% qutz-carb lenses in ser sch min with py and aspy	3938	6.0	.31	1.860
34.0 - 40.0	80% blue qutz spar min with pya and aspy, possible V.G.	3939	5.0/6.0	(.32 (.32	1.920
40.0 - 45.0	50% qutz-carb min with py and aspy	3340	5.0	.63	3.150
45.0 - 50.0	As above, possible V.G.	3341	5.0	.74	3.700
50.0 - 55.0	40% blue qutz in ser sch min with py and aspy	3951	5.0	.48	2.400
55.0 - 60.0	As above	3952	5.0	1.08	5.400
60.0 - 65.0	70% blue qutz and min carb well min with py and aspy	3953	5.0	.19	.950

Logged by LAM

Hole No. U-8735

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
65.0 - 69.0	As above	3954	4.0	.34	1.360
69.0 - 73.0	As above	3955	4.0	.62	2.480
73.0 - 77.0	As above	3956	4.0	.93	3.720
77.0 - 83.0	30% qutz-carb lenses in ser sch well min with py and aspy	3957	6.0	.44	2.640
83.0 - 89.0	As above	3958	6.0	.20	1.200
89.0 - 94.0	As above but increasing min	3959	5.0	.25	1.250
94.0 - 100.0	As above	3960	6.0	.39	2.340
100.0 - 106.0	As above	3961	6.0	.22	1.320
106.0 - 112.0	As above	3962	6.0	.52	3.120
112.0 - 118.0	As above	3963	6.0	.18	1.080
118.0 - 123.0	Qutz-carb lenses in ser sch min with pay and aspy	3964	5.0	.14	.700
123.0 - 127.0	40% qutz-carb lenses in ser sch min with py and aspy	3965	4.0	.25	1.000
					48.990

From	To	C.L.	Grade
8.0	127.0	119.0	.41

SHEET No. 2

HOLE No. U-8735

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-3734
BEARING --
DIP AT COLLAR -90°
LENGTH 51.0

LAT. 13099.19
DEP. 7476.11 48/W
ELEV. 5590

DATE COMPLETED Feb. 27/50
PURPOSE No. 1 Shoot Def.

SHAFT 2
LEVEL 425
WORKING B308N-Dr.
SECTION 1250N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 1.0	Casing				
1.0 - 6.0	60% qutz with minor carb in ser sch well min with py and aspy	3923	5.0	.03	.150
6.0 - 11.0	As above	3924	5.0	.12	.600
11.0 - 16.0	40% qutz and as above	3925	5.0	.29	1.450
16.0 - 21.0	As above	3926	5.0	.75	3.750
21.0 - 26.0	20% qutz-carb lenses in ser sch spar min with py and aspy	3927	5.0	.07	.350
26.0 - 30.0	70% blue qutz min with py aspy and traces of sph	3931	4.0	.48	1.920
30.0 - 34.0	30% blue qutz with local carb min as above	3932	4.0	.34	1.360
					9.580
34.0 - 45.0	Fg gray ser sch with local carb lenses				
45.0 - 51.0	Fg gray grn chl-ser sch				

From	To	C.L.	Grade
1.0	34.0	33.0	.29

Logged by JBB

Hole No. U-3 734

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8733
BEARING N 60W
DIP AT COLLAR -30°
LENGTH 116.0

LAT. 12907.93
DEP. 7602.57 270W
ELEV. 5434

DATE COMPLETED Feb. 26/50
PURPOSE A.S.D. Zone Definition

SHAFT 2
LEVEL 575
WORKING 8403N.Dr.
SECTION 1150N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 40.0	Fg gray-grn chl-ser sch in part ser sch with local banding				
40.0 - 64.0	Fg gray ser sch with local carb lenses and acc min				
64.0 - 69.0	30% qutz-carb lenses in ser sch spar min with py and aspy,	3916	5.0	.12	
69.0 - 74.0	As above but with short sections of 50% qutz-carb	3917	5.0	.43	
74.0 - 79.0	As above	3918	5.0	.16	
79.0 - 93.5	Fg gray-grn chl-ser sch, approaching grs sch.				
93.5 - 96.0	Fg black slate - well defined contacts				
96.0 - 116.0	M to fg grn grs sch				

From	To	C.L.	Grade
64.0	79.0	15.0	.23

Dip Test

Depth	Read	Correct
116.0	29°	25°

Logged by [illegible]

Hole No. U-8733

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8 732 | SHAFT 2

BEARING N60W | LAT. 12812.41 | DATE COMPLETED Feb. 28/50 | LEVEL 575

DIP AT COLLAR -45° | DEP. 7674.87 166W. | PURPOSE Lower Orebody | WORKING B404 Dr.

LENGTH 235.0 | ELEV. 5435 | Extension | SECTION 11CON

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0.0 - 2.0	Casing				
2.0 - 7.0	20% qutz-carb lenses in ser sch	3919	5.0	.14	
7.0 - 12.5	As above	3920	5.5	.08	
12.5 - 18.0	Fg gray ser sch				
18.0 - 25.0	30% qutz-cart lenses in ser sch	3921	7.0	.26	
25.0 - 31.5	Fg gray ser sch				
31.5 - 38.0	30% qutz-carb lenses in ser sch spar min with py and aspy	3922	6.5	.06	
38.0 - 40.0	As above	3928	2.0	.13	
40.0 - 75.0	Fg gray ser sch, in part chl-ser sch				
75.0 - 78.0	20% qutz-lenses well min with aspy and minor py	3929	3.0	.06	
78.0 - 83.0	Fg gray ser sch				
83.0 - 88.0	20% qutz-lenses min with py and minor aspy	3930	5.0	.13	
88.0 - 104.0	Fg. gray chl-ser sch with local carb lenses				

Logged by JAR | Hole No. U-8732

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
104.0 - 137.0	Fg. gray-grn grs sch, locally chl-ser sch				
137.0 - 163.0	Gradation into ser sch with a few carb lenses				
163.0 - 169.0	Qutz-carb lenses in ser sch min with py	3942	6.0	.41	2.460
169.0 - 176.0	As above but with increasing min	3943	7.0	.03	.210
176.0 - 181.0	50% qutz-carb lenses min with py aspy and traces at gray min	3944	5.0	.29	1.450
181.0 - 186.0	As above, decreasing min, 1' core ground at 183.0	3945	4.0/5.0	.10	4.120
186.0 - 192.0	20% qutz-carb lenses in ser sch spar min with gya and aspy	3946	6.0	.12	
192.0 - 198.0	As above	3947	6.0	.03	
198.0 - 204.0	40% qutz-carb lenses and as above, 1' core ground at 204.0	3948	5.0/6.0	.04	
204.0 - 210.0	As above but with increased min	3949	6.0	(.26 (.25	
210.0 - 221.5	Fg gray ser sch with local calc lenses.				
221.5 - 224.0	60% blue qutz and carb min with py and aspy, V.C., well defined contacts against ser sch	3950	2.5	(.81 (.88	
224.0 - 228.0	Fg gray ser sch with local carb lenses				
228.0 - 235.0	Fg gray-grn chl-ser sch with gradation to grs sch toward 235.0				

From	To	C.L.	Grade
18.0	25.0	7.0	.26
163.0	181.0	18.0	.23
204.0	210.0	6.0	.25
221.5	224.0	2.5	.84

SHEET No. 2

HOLE No. U-3732

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
	Dip Tests Depth — Read — Correct 150' — 43° — 39° 35 235' — 41° — 37° 33				

SHEET No. 3

HOLE No. U-3732

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-3731
BEARING N60W
DIP AT COLLAR -65
LENGTH 167.0
LAT. 13099.19
DEP. 7476.11
ELEV. 5590
DATE COMPLETED Feb. 26/50
PURPOSE No. 1 Shoot Def.
SHAFT 2
LEVEL 425
WORKING B-308N
SECTION 1250N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 2.0	Cs.				
2.0 - 9.5	dk gry chl-ser sch				
9.5 - 14.5	40% dk qutz in ser sch, sparing min	7520	5.0	.55	
14.5 - 27.0	dk gry chl-ser sch				
27.0 - 59.0	dk gry chty tuff & sch w sect solid py replace.				
	t.s. 39.5 - 45.0	7521	5.5	.04	
	t.s. 45.0 - 50.0	3901	5.0	.12	
	t.s. 50.0 - 55.0	3902	5.0	.18	
	t.s. 55.0 - 59.0	3903	4.0	.16	
59.0 - 77.0	Fg. gray ser sch with local qutz-carb lenses				
77.0 - 81.5	20% qutz-carb lenses in ser sch min with py and minor aspy	3904	4.5	.21	.945
81.5 - 87.0	60% qutz-carb and as above	3905	5.5	.37	2.035
87.0 - 93.0	30% qutz-carb lenses spar min with py and aspy	3906	6.0	.09	.540
93.0 - 99.0	As above				
99.0 - 116.0	Fg gray ser sch with local qutz-carb lenses and spar min	3907	6.0	.30	1.800
					5.320
116.0 - 121.0	90% qutz with minor carb min with py and aspy	3908	5.0	.86	4.300

Logged by J.H

Hole No. U-3731

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
121.0 - 127.0	As above	3909	6.0	.26	1.560
127.0 - 132.0	As above	3910	5.0	.22	1.100
132.0 - 137.0	50% qutz-carb and as above	3911	5.0	.94	4.700
137.0 - 142.0	80% blue qutz with minor carb min with py aspy gray min and minor sch	3912	5.0	.96	4.800
142.0 - 147.0	20% qutz-carb lenses in ser sch, spar min	3913	5.0	.37	1.850
147.0 - 153.0	As above, well min with py	3914	6.0	.49	2.940
					21.250
153.0 - 162.0	Fg gray ser sch, in part chl-ser sch				
162.0 - 167.0	30% qutz-carb lenses min with py and aspy	3915	5.0	.27	

From	To	C.L.	Avr. Grade
9.5	14.5	5.0	.55
45.0	59.0	14.0	.16
77.0	99.0	22.0	.24
116.0	153.0	37.0	.57
162.0	167.0	5.0	.27

SHEET No. 2

HOLE No. U-B 731

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8 730
BEARING --
DIP AT COLLAR 490
LENGTH 62
LAT. 12810.5
DEP. 7677.8
ELEV. 5442
DATE COMPLETED
PURPOSE ASD Zone Def.
SHAFT 2
LEVEL 575
WORKING B-404N
SECTION 1100N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 1.0	Cs.				
1.0 - 8.0	20% qutz in partly silic ser sch; py, aspy	7514	7.0	.47	3.290
8.0 - 15.0	30% qutz; sp, gry min	7515	7.0	.79	5.530
15.0 - 22.0	qutz lenses in ser sch; local min	7516	7.0	.08	.560
22.0 - 29.0	as above	7517	7.0	.31	2.170
29.0 - 34.0	20% qutz-carb, py, aspy	7518	5.0	.22	1.100
					12.650
34.0 - 50.0	gry ser sch; t.s. 39.5 - 43.0	7519	3.5	.45	
50.0 - 62.0	comp chl-ser sch merg w grs sch				

From	To	C.L.	Avg. Grade
1.0	34.0	33.0	.37
39.5	43.0	3.5	.45

Logged by JDB

Hole No. U-8730

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-3729
BEARING N60W
DIP AT COLLAR 45
LENGTH 56.0
LAT. 12812.41
DEP. 7674.87
ELEV. 5441
DATE COMPLETED
PURPOSE ASD Zone Def.
SHAFT 2
LEVEL 575
WORKING B-40W
SECTION 1100N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 7.0	qutz lenses in ser sch; minor min	7506	7.0	.15	1.050
7.0 - 115	As above	7507	4.5	.06	.270
11.5 - 17.0	20% qutz; py aspy, tr gry min & sp	7508	5.5	.14	.770
17.0 - 22.0	40% qutz-carb; aspy, sp	7509	5.0	.44	2.200
22.0 - 29.0	qutz-carb in silic ser sch, py	7510	7.0	.35	2.450
29.0 - 34.0	as above	7511	5.0	.36	1.800
34.0 - 41.5	30% qutz-carb, aspy, sp	7512	7.5	.57	4.275
41.5 - 56.0	grn-gry chl-ser sch.				12.815

From	To	C.L.	Avg. Grade
17.0	41.5	24.5	.43
0.0	41.5	41.5	.30

Logged by JDB

Hole No. U-3729

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8 728

BEARING N60W

DIP AT COLLAR -65

LENGTH 172.0

LAT. 13052.67

DEP. 7451.91

ELEV. 5590

DATE COMPLETED

PURPOSE No. 1 Shoot Def.

SHAFT 2

LEVEL 425

WORKING B-308N

SECTION 1200N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 2.0	Cs.				
2.0 - 9.0	90% dk blue qutz; sparing v.g.	7632	7.0	.61	4.270
9.0 - 14.0	20% qutz; minor min	7633	5.0	.39	1.950
14.0 - 29.0	gry ser sch; neg qutz & min t.s. 27.0 - 29.0	7638	2.0	.18	6.220
29.0 - 34.0	as above w minor qutz & min	7634	5.0	.07	
34.0 - 39.0	as above	7635	5.0	.28	1.400
39.0 - 44.0	20% qutz; py, aspy	7636	5.0	.31	1.550
44.0 - 48.0	buff ser sch; neg qutz & min	7639	4.0	.03	.120
48.0 - 52.0	80% qutz-carb (dk); py (v.s.)	7640	4.0	13.93) 10.57)	20.000
52.0 - 57.0	qutz lenses in ser sch, minor min	7641	5.0	.12	1.100
57.0 - 62.0	as above	7642	5.0	.04	.200
62.0 - 67.0	20% qutz; py, aspy	7643	5.0	.07	.350
67.0 - 72.0	as above	7644	5.0	.38	1.900
72.0 - 79.0	as above; increas carb	7645	7.0	.08	.560

Logged by [illegible]

Hole No. U-8728

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
79.0 - 84.0	qutz lenses in ser sch, minor min	7646	5.0	.27	1.350
84.0 - 89.0	as above	7647	4/5.0	.47	2.350
89.0 - 104.5	dk gry chl-ser sch(tuffac?)				
104.5 - 110.0	20% qutz-carb, scaring min	7648	5.5	.03	
110.0 - 115.0	banded ser sch	7649	5.0	.07	
115.0 - 120.0	as above	7650	5.0	.06	
120.0 - 125.5	70% dk blue qutz; sp; heavy v.g.	7501	5.5	(19.83	27.500
125.5 - 132.0	30% qutz-carb; py aspy	7502	6.5	(21.73 1.58	10.270
132.0 - 137.5	50% qutz-carb, tr sr & gry min	7503	5.5	3.01	16.555
137.5 - 142.5	qutz-carb lenses in silic ser sch; minor min	7504	5.0	.27	1.350
142.5 - 147.5	as above	7505	5.0	.10	.500
147.5 - 152.0	as above	7513	4.5	.51	2.295
152.0 - 162.0	Chl-ser sch				58.470
162.0 - 172.0	Como grs sch w tan lent alt fl.				

From	To	C.L.	Grade
2.0	14.0	12.0	.51
34.0	89.0	55.0	.56
120.0	152.0	32.0	1.82

SHEET No. 2

HOLE No. U-8728

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8727
BEARING N60W
DIP AT COLLAR 460
LENGTH 38.0
LAT. 13015
DEP. 7474.5
ELEV. 5599
DATE COMPLETED
PURPOSE No. 1 Shoot Def.
SHAFT 2
LEVEL 425
WORKING B-313a
SECTION 1175N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 1.0	Cs.				
1.0 - 7.0	gry ser sch, minor qutz & min	7626	6.0	.01	
7.0 - 12.0	as above w more qutz & min	7627	5.0	.36	1.800
12.0 - 17.0	as above;	7628	5.0	.19	.950
17.0 - 21.0	50% dk qutz; sparing min	7629	4.0	.62	3.280
21.0 - 24.0	gry ser sch; minor qutz & min	7630	3.0	.03	6.030
24.0 - 38.0	gry (dk) chl-ser sch t.rs 33.0 - 35.0	7631	2.0	.27	

From	To	C.L.	Grade
7.0	21.0	14.0	.43
33.0	35.0	2.0	.27

Logged by JDB

Hole No. U-8727

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-3726
BEARING -
DIP AT COLLAR 490
LENGTH 44.0
LAT. 12992.5
DEP. 7462.5 440W
ELEV. 5529
DATE COMPLETED
PURPOSE No. 1 Shoot Def.
SHAFT 2
LEVEL 425
WORKING 8-312N
SECTION 1150N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 1.0	Cs.				
1.0 - 5.0	50% qutz-carb., py, aspy	7614	4.0	1.36	
5.0 - 8.0	dk gry ser sch	7615	3.0	.04	
8.0 - 12.0	as above	7616	4.0	.04	
12.0 16.0	qutz lenses in ser sch, local min	7617	4.0	.22	.880
16.0 - 21.0	20% qutz; minor min	7618	5.0	.50	2.500
21.0 - 25.0	as above	7624	4.0	.01	3.380
25.0 - 30.0	as above	7625	5.0	.02	
30.0 - 44.0	dk gry ser sch, nosig min				

From	To	C. L.	Grade
1.0	5.0	4.0	1.36
12.0	21.0	9.0	.37

Logged by JBB

Hole No. U-3726

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-2725
BEARING N60W
DIP AT COLLAR 191.0
LENGTH 191.0

LAT. 12812.41
DEP. 7674.87
ELEV. 5435

DATE COMPLETED
PURPOSE Lower Orebody Ext.

SHAFT 2
LEVEL 575
WORKING 8-404N
SECTION

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 5.0	20% qutz-carb, py, aspy	7611	5.0	.07	
5.0 - 10.0	30% & as above	7612	5.0	.17	
10.0 - 15.0	20% & as above	7613	5.0	.04	
15.0 - 22.0	qutz lenses in ser sch, minor min	7619	7.0	.04	
22.0 - 26.5	30% qutz, py, aspy	7620	4.5	.12	
26.5 - 54.0	gry-buff ser sch, qutz lenses & local min t.s. 46.0 - 50.5	6521	4.5	.08	
54.0 - 94.0	f.g. grn grs sch; porous sect (soln of py?)				
94.0 - 136.0	gry-buff ser sch; t.s. 99.0 - 104.0 cb in vugs 130.0 (fault)	7622	5.0	.07	
136.0 - 141.0	20% qutz, py, aspy (ASD Z one type)	7623	5.0	.05	
141.0 - 145.5	60% qutz-carb; py, aspy (ASD Zone type)	7637	4.5	.25	
145.5 - 156.0	buff ser sch approach chl-ser towards 156.0				
156.0 - 191.0	grn chl grs sch; Fine snfl.				

From	To	C.L.	Grade
5.0	10.0	5.0	.17
22.0	26.5	4.5	.12
141.0	145.5	4.5	.25

Logged by JJC

Hole No. U-2725

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B724
BEARING N60W
DIP AT COLLAR Hor.
LENGTH 34.0

LAT. 12866.49
DEP. 7680.26
ELEV. 5437.5

DATE COMPLETED
PURPOSE ASD Zone Def.

SHAFT 2
LEVEL 575
WORKING B-404N
SECTION 1150N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 5.0	qutz lenses in ser sch, local min	7605	5.0	.22	1.100
5.0 - 9.5	as above	7606	4.5	.15	.675
9.5 - 12.0	20% qutz; py aspy	7607	2.5	.18	.450
12.0 - 34.0	gry-buff ser sch w qutz lenses				2.225

From	To	C.L.	Grade
0	12.0	12.0	.18

Logged by JDB

Hole No. U-B724

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8 723 | SHAFT 2

BEARING - | LAT. 13007.5 | DATE COMPLETED | LEVEL 125

DIP AT COLLAR +90 | DEP. 7434.5 | PURPOSE No. 1 Shoot Def. | WORKING B-30SW

LENGTH 94.0 | ELEV. 5599 | SECTION 1150W

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 1.0	Cs.				
1.0 - 8.0	20% qutz-carb in dk ser sch; py	7595	7.0	.20	1.400
8.0 - 15.0	90% dk blue qutz; sp, gry min	7596	7.0	(1.16 (1.25	8.400
15.0 - 22.0	as above, v.g.	7597	7.0	(.54 (.72	4.410
22.0 - 29.0	As above; water flow in fault 24.0	7598	7.0	(1.49 (1.45	10.220
29.0 - 36.0	as above; coppery v.g.	7599	7.0	5.53	35.000
36.0 - 41.0	30% qutz in dk ser sch & as above	7600	5.0	.44	2.200
41.0 - 44.5	As above	7601	3.5	.33	1.155
44.5 - 50.0	60% qutz (dk): sparing min	7602	5.5	.65	3.575
50.0 - 57.0	80% dk qutz & as above	7603	7.0	(.56 (.61	4.060
57.0 - 64.0	90% dk qutz & as above; v.g.	7604	7.0	.30	2.100
64.0 - 69.0	20% qutz-carb; sparing min	7605	5.0	.17	.850
69.0 - 74.0	As above	7609	5.0	.23	1.150
74.0 - 78.5	as above w de cross. qutz-carb	7610	4.5	.26	1.170

Logged by JDP | Hole No. U-8723

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
78.5 - 94.0	grn gran chl-ser sch merg w grs sch				

From	To	C.I.	Grade
1.0	78.5	77.5	.97

SHEET No. 123

HOLE No. U-8723

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8722 | SHAFT 2
BEARING N60W | LAT. 12866.49 | DATE COMPLETED | LEVEL 575
DIP AT COLLAR -51 | DEP. 7680.26 188W | PURPOSE Lower Orebody | WORKING B-4040
LENGTH 235.0 | ELEV. 5434 | Expl. | SECTION 1150W

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 2.0	Cs.				
2.0 - 9.0	qutz lenses in ser sch, minor min	7583	7.0	.03	
9.0 - 16.0	as above	7584	7.0	.06	
16.0 - 21.0	as above	7595	5.0	.51	
21.0 - 25.0	as above	7586	4.0	.08	
25.0 - 30.0	20% qutz; py, aspy	7587	5.0	1.32	6.600
30.0 - 35.5	qutz lenses in ser sch, py, aspy	7588	5.5	.24	1.320
35.5 - 40.5	20% qutz, py, aspy	7589	5.0	.32	1.600
					9.520
40.5 - 50.0	dk gry chl-ser sch w qutz lenses				
50.0 - 87.0	gry ser sch w qutz lenses, (tuffac? 69.0 - 73.0) (tuffac? 85.0 - 87.0)				
87.0 - 127.0	grn grs sch				
127.0 - 158.5	buff ser sch; fault bx 158.5				
158.5 - 164.0	70% qutz; sparing min, v.g. native au	7590	5.5	.91	5.005

Logged by JGS | Hole No. U-8722

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
164.0 - 172.0	buff ser sch; qutz-carb; no sig min	7591	8.0	.13	1.040
172.0 - 178.0	20% qutz, py, aspy	7592	6.0	.26	1.560
178.0 - 183.0	As above; less qutz	7593	5.0	.33	1.650
183.0 - 186.5	As above	7594	3.5	.66	2.310
186.5 - 222.0	buff ser sch, qutz-carb lenses				11.565
222.0 - 235.0	buff-gry chl-ser sch				

From	To	C.L.	Grade
16.0	21.0	5.0	.51
25.0	40.5	15.5	.61
158.5	186.5	28.0	.41

SHEET No. 2

HOLE No. U-8722

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-2721 | SHAFT 2
BEARING N60W | LAT. 13010.33 | DATE COMPLETED | LEVEL 425
DIP AT COLLAR -60 | DEP. 7430.78 | PURPOSE | WORKING B-308N
LENGTH 167.0 | ELEV. 5591 | No. 1 Shoot Def. | SECTION 1150N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 1.0	Cs.				
1.0 - 8.0	20% qutz; py, aspy	7569	7.0	1.00	7.000
8.0 - 14.5	90% dk blue qutz well min w v.g.	7570	6.5	(16.26 (14.20	98.995
14.5 - 21.0	30% qutz; py, aspy	7571	6.5	1.14	7.410
21.0 - 25.5	qutz lenses in ser sch; py, aspy	7572	4.5	.09	113.405
25.5 - 67.0	dk gry chl-ser sch				
67.0 - 73.0	20% qutz-carb, py, aspy	7573	6.0	.07	.420
73.0 - 80.0	As above	7574	7.0	.05	.350
80.0 - 87.0	30% qutz-carb & as above	7575	7.0	.19	1.330
87.0 - 94.0	As above	7576	7.0	.05	.350
94.0 - 101.0	40% qutz-carb & as above	7577	7.0	.26	1.820
101.0 - 108.0	As above	7578	7.0	.50	3.500
108.0 - 115.0	Silic ser sch; py	7579	7.0	.08	.560
115.0 - 122.0	As above	7580	7.0	.03	.210

Logged by JDB | Hole No. U-2721

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
122.0 - 129.0	30% qutz-carb, gry min, sp.	7581	7.0	.49	3.430
129.0 - 133.5	qutz lenses in ser sch, minor min	7582	4.5	.03	11.970
133.5 - 141.0	dk ser sch, qutz lenses				
141.0 - 167.0	dk gry chl-ser sch q qutz lenses				

From	To	C.L.	Calc. Grade Uncut	Cut
1.0	21.0	20.0	5.67	2.34
67.0	129.0	62.0	.19	--

SHEET No. 2

HOLE No. U-5721.

N.M.P.-F3742-3

G-11

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8720

BEARING N60W

DIP AT COLLAR 460

LENGTH 51.0

LAT. 12966

DEP. 7402

ELEV. 5598

DATE COMPLETED

PURPOSE No. 1 Shoot Def.

SHAFT 2

LEVEL 425

WORKING B-308W

SECTION 1100W

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 1.0	Cs.				
1.0 - 3.5	40% qutz; minor min	7564	2.5	1.76	4.400
3.5 - 9.0	90% dk blue qutz; gry min; sp; heavy v.g.	7565	5.5	(12.46 (17.06	81.180
9.0 - 14.0	As above	7566	5.0	(3.94 (4.38	20.800
14.0 - 19.5	As above	7567	5.5	(10.62 (11.22	60.225
19.5 - 22.0	qutz ribbons in ser sch; v.g.	7568	2.5	(3.01 (4.91	9.900
22.0 - 51.0	gry-buff ser sch				176.505
					90.100

From	To	C.L.	Calc. Grade Uncut	Cut
1.0	22.0	21.0	8.40	4.29

Logged by JDB

Hole No. U-8720

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B719
BEARING N60W
DIP AT COLLAR -35
LENGTH 222.0

LAT. 12866.49
DEP. 7680.26
ELEV. 5435

DATE COMPLETED
PURPOSE Lower Orebody Ext.

SHAFT 2
LEVEL 575
WORKING B-404N
SECTION 1150N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 1.0	Cs.				
1.0 - 8.0	qutz lenses in ser sch, py, aspy (local)	7539	7.0	.12	.840
8.0 - 15.5	as above	7540	6.5/7.5	.20	1.500
15.5 - 18.0	80% qutz; sp, gry min, v.g.	7541	2.5	(1.09 (1.11	2.750
18.0 - 23.0	40% qutz-carb, sparing min	7547	5.0	.31	1.550
23.0 - 27.0	30% qutz-carb & as above	7548	4.0	.12	.480 7.120
27.0 - 56.5	gry-buff ser sch, qutz-carb lenses				
	t.s. min sect., 50.0 - 56.5	7549	6.5	.14	
56.5 - 72.0	dk chl-ser sch;				
72.0 - 110.5	grn chl grs sch, calc				
110.5 - 133.5	gry buff ser sch w qutz lenses; t/s. 123.0 - 124.0 tuffac (?) 125.0 - 133.5	7550	1.0	.44	
133.5 - 137.0	20% qutz-carb; py, aspy	7551	3.5	.37	1.295
137.0 - 142.0	40% qutz-carb & as above	7552	5.0	.70	3.500
142.0 - 147.0	50% qutz-carb & as above, minor sp.	7553	5.0	.78	3.900

Logged by [illegible]

Hole No. U-B719

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
147.0 - 152.0	40% qutz-carb, gry min & sp	7554	5.0	1.49	7.450
152.0 - 156.5	20% qutz-carb; py, aspy	7555	4.5	.17	.765
156.5 - 162.0	40% qutz-carb; gry min; sp; v.g.	7556	5.5	(1.28 (.62	5.225
162.0 - 167.0	30% qutz & as above	7557	5.0	.17	.850
167.0 - 172.0	as above	7558	5.0	.48	2.400
172.0 - 179.0	60% qutz-carb, py, aspy	7559	7.0	.27	1.890
179.0 - 184.0	40% & as above	7560	5.0	.18	.900
184.0 - 190.0	30% and as above	7561	6.0	1.02	6.120
190.0 - 194.0	qutz lenses inser sch, minor min	7562	4.0	.03	34.295
194.0 - 200.0	as above	7563	5/6.0	.03	
200.0 - 205.0	as above, broken core & water flow 205.0				
205.0 - 222.0	dk chl ser sch(tuffac?)				

From	To	C.L.	Grade
1.0	27.0	26.0	.27
133.5	190.0	56.5	.60

Dip Test

Depth	Read	Correct
150	25½	22

SHEET No. 2

HOLE No. U-2719

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8718 | SHAFT 2
BEARING N60W | LAT. 12979.5 | DATE COMPLETED | LEVEL 425
DIP AT COLLAR -70 | DEP. 7383.5 502W | PURPOSE No. 1 Shoot Def. | WORKING B-308W
LENGTH 110° | ELEV. 5590 | SECTION 1100W

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 3.0	Cs.				
3.0 - 7.0	dk gry sers sch, neg qutz & min; Fault bx 7.0	7532	4.0	.05	
7.0 - 11.0	dk qutz-carb, 80% v.g.	7533	4.0	(7.05 (7.52	(29.120 (20.000
11.0 - 15.5	60% qutz-carb & as above, py	7534	4.5	(3.22 (2.50	12.870
15.5 - 20.0	80% black qutz, v.g.	7535	4.5	(1.77 (1.57	7.515
20.0 - 23.0	as above, rich v.g.	7536	3.0	12.14	(36.420 (15.000
23.0 - 28.0	20% bx qutz; minor sp & gry min	7537	5.0	.49	2.450
28.0 - 47.0	gry ser sch, minor qutz & min; trs. 28.0 - 31.0 -	7541	3.0	.44	88.375
47.0 - 53.0	qutz lenses in ser sch, minor min	7542	6.0	.09	57.835 1.320
53.0 - 58.0	20% qutz; py, aspy	7543	5.0	.18	.900
58.0 - 65.0	30% qutz & as above	7544	7.0	.36	
65.0 - 72.5	80% qutz-carb; gry min; sp, v.g.	7545	7.5	(1.38 (.90	2.590 8.550
72.5 - 74.5	qutz lenses in ser sch; minor min	7546	2.0	.13	.260
74.5 - 110.0	gran chl-ser sch.				12.300

Logged by JGS | Hole No. U-8718

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON

From	To	C.L.	Grade Uncut	Grade Cut
7.0	31.0	24.0	3.73	2.46
53.0	74.5	21.5	.57	--

SHEET No. 2

HOLE No. U-8718

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B717
BEARING -
DIP AT COLLAR -90
LENGTH 44.0
LAT. 12944
DEP. 7346
ELEV. 5590
DATE COMPLETED
PURPOSE No. 1 Shoot Def.
SHAFT 2
LEVEL 425
WORKING B-308N
SECTION 1050N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 2.0	Cs.				
2.0 - 8.0	gry-buff ser sch, minor qutz & min	7526	6.0	.08	
8.0 - 13.5	qutz lenses in ser sch; minor py aspy	7527	5.5	.55	3.025
13.5 - 18.5	40% qutz-carb, part well min, gry min	7528	5.0	1.67	8.350
18.5 - 23.5	30% qutz-carb & as above	7529	5.0	.65	3.250
23.5 - 28.5	80% qutz-carb richly min w sp, spock v.g.	7530	5.0	(2.46	12.900
28.5 - 34.0	qutz lenses in ser sch, minor min	7531	5.5	(2.70 .03	27.525
34.0 - 44.0	dk gry chl-ser sch w qutz lenses				

From	To	C.L.	Grade
8.0	28.5	20.5	1.34

Logged by JDB

Hole No. U-B717

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8716
BEARING -
DIP AT COLLAR +90
LENGTH 79.0
LAT. 13009
DEP. 7483.7
ELEV. 5599
DATE COMPLETED
PURPOSE No. 1 shoot Def.
SHAFT 2
LEVEL 425
WORKING B-313E
SECTION 1175N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 5.0	30% qutz; py, aspy	7515	5.0	.42	2.100
5.0 - 8.5	80% dk qutz; gry min, sp	7516	3.5	.45	1.575
8.5 - 14.5	dk ser sch w qutz lenses, minor min	7517	6.0	.06	3.675
14.5 - 19.5	qutz lenses in ser sch, py, aspy	7518	5.0	.11	
19.5 - 24.0	20% qutz, py, aspy	7519	4.5	.20	.900
24.0 - 31.0	30% qutz & as above	7520	7.0	.36	2.520
31.0 - 38.0	as above	7521	7.0	.56	3.920
					7.340
38.0 - 43.0	qutz lenses in ser sch, minor min.	7522	5.0	.13	
43.0 - 50.0	20% qutz, py, aspy	7523	7.0	.16	
50.0 - 57.0	60% qutz-carb, py, aspy	7524	7.0	.33	
57.0 - 64.0	20% qutz; minor min	7525	7.0	.04	
64.0 - 79.0	gry ser sch, qutz lenses, no min				

From	To	C.L.	Grade
0	8.5	8.5	.43
19.5	38.0	18.5	.39
~~50.0~~	~~57.0~~	~~7.0~~	~~.33~~

42.5

Logged by JDB

Hole No. U-8716

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-3715 | SHAFT 2
BEARING - | LAT. 12999 | DATE COMPLETED | LEVEL 425
DIP AT COLLAR +90 | DEP. 7501 | PURPOSE No. 1 Shoot Def. | WORKING B-313E
LENGTH 109.0 | ELEV. 5599 | SECTION 1175N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 1.0	Cs				
1.0 - 5.0	40% qutz; py, aspy	7498	4.0	1.67	6.680
5.0 - 10.0	80% qutz; sp, gry min	7499	5.0	1.95	9.750
10.0 - 12.0	60% qutz & as above	7500	2.0	1.21	2.420
12.0 - 17.0	qutz lenses in ser sch; local min	7501	5.0	..40	2.000
17.0 - 24.0	20% qutz (after 19.5) tr sp & gry min	7503	7.0	.71	4.970
24.0 - 31.0	30% qutz-carb; gry min; py, aspy, v.g.	7502	7.0	.97	6.790
31.0 - 35.5	As above	7504	4.5	.32	1.440
35.5 - 40.5	qutz lenses in sil ser sch; minor min	7505	5.0	.07	34.050
40.5 - 45.5	as above	7506	5.0	.14	
45.5 - 50.0	as above	7507	4.5	.03	
50.0 - 57.0	20% qutz; py, aspy	7508	7.0	.32	
57.0 - 61.5	as above	7509	4.5	.08	
61.5 - 66.0	as above	7510	4.5	.10	

Logged by JDB

Hole No. U-3715

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
66.0 - 70.0	30% qutz & as above	7511	4.0	.10	
70.0 - 76.0	20% qutz & as above	7512	6.0	.14	
76.0 - 81.5	30% qutz & as above; fault bx 81.0	7513	5.5	.11	
81.5 - 87.0	as above	7514	5.5	.18	
87.0 - 94.0	gry ser sch				
94.0 - 109.0	gry-grn chl-ser sch merg w grs sch				

From	To	C.L.	Grade
1.0	35.5	34.5	.98
50.0	57.0	7.0	.32

SHEET No. 2

HOLE No. U-B715

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-3714
BEARING -
DIP AT COLLAR 490
LENGTH 123.0
LAT. 12938.5
DEP. 7518
ELEV. 5599
DATE COMPLETED
PURPOSE No. 1 Shoot Def.
SHAFT 2
LEVEL 425
WORKING B-313E
SECTION 1175N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 1.0	Cs				
1.0 - 16.5	m.g. grn grs sch,				
16.5 - 22.0	20% qutz-carb, py, aspy	7491	5.5	1.12	6.160
22.0 - 29.0	80% qutz; sp, gry min, v.g.	7492	7.0	(2.02 (2.75	16.730
29.0 - 36.0	qutz lenses in ser sch, py, aspy	7493	7.0	.29	2.030
36.0 - 40.5	As above	7494	4.5	.14	.630
40.5 - 46.0	50% qutz; aspy, sp, v.g.	7495	5.5	1.60	8.800
46.0 - 53.0	30% qutz; py, aspy tr gry min & v.g.	7496	7.0	1.05	7.350
53.0 - 58.5	ser sch; minor qutz & min	7497	5.5	.12	.660
					42.360
58.5 - 104.0	gry buff ser sch, hem fract, fault 87.0				
104.0 - 108.5	gry chl-ser sch				
108.5 - 123.0	m.g. grn grs sch				

From	To	C.L.	Grade
16.5	58.5	42.0	1.00

Logged by JDB

Hole No. U-3714

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B713
BEARING North
DIP AT COLLAR Hor.
LENGTH 480.0

LAT. 13232.18 1401 N
DEP. 7549.21
ELEV. 5595

DATE COMPLETED
PURPOSE Expl.

SHAFT 2
LEVEL 425
WORKING B-312N
SECTION 1400N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 33.5	f.g. - m.g. sch grs w chty, bx sect,				
33.5 - 48.0	f.g. m.g. grn grs sch				
48.0 - 60.0	f.g. gry-grn chl sch, grad w chl-ser sch				
60.0 - 88.5	m.g. grn calc grs sch, worm trail tx				
88.5 - 129.0	chl-ser sch merg w ser sch; worm trail tx				
129.0 - 134.0	gry ser sch				
134.0 - 140.0	qutz lenses in ser sch, minor min	7486	6.0	.19	
140.0 - 145.0	as above; silic	7487	5.5	.01	
145.5 - 150.0	40% qutz-carb; py, aspy; speck v.g.; sp	7488	4.5	(.52 (.48	
150.0 - 155.0	ser sch w qutz lenses & minor min	7489	5.0	.05	
155.0 - 159.5	As above	7490	5.0	.01	
159.5 - 173.0	gry buff ser sch				
173.0 - 182.0	gry chl-ser sch				
182.0 - 208.0	m.g. grn grs sch, local snfl,				

Logged by JDB

Hole No. U-B713

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
208.0 - 262.0	m.g. grn sch grs, chty-ep sect,				
262.0 - 339.0	m.g. dk grn grs sch; calc,				
339.0 - 373.0	as above merg w chl sch				
373.0 480.0	grn sch grs w chty ep sect & hem fract, variol after 465.0				
	Water flow 240.0 & 440.0				

From	To	C.L.	Grade
134.0	140.0	6.0	.19
145.5	150.0	4.5	.50

SHEET No. 2

HOLE No. U-3713

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B712
BEARING -
DIP AT COLLAR -90
LENGTH 142.0
LAT. 12978
DEP. 7535
ELEV. 5599
DATE COMPLETED
PURPOSE No. 1 Shoot Def.
SHAFT 2
LEVEL 425
WORKING B-313B
SECTION 1175N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 1.0	Cs.				
1.0 - 29.0	grn grs sch				
29.0 - 33.5	as above w barren qutz-carb				
33.5 - 36.0	30% barren qutz-carb in grs sch	7477	2.5	.07	
36.0 - 41.0	60% qutz-carb, part richly min w sp & gry min	7478	5.0	(1.39 (1.40	6.950
41.0 - 45.0	buff min sch	7479	4.0	.23	.920
45.0 - 50.5	as above	7480	5.5	.44	2.420
50.5 - 57.0	40% qutz-carb, py aspy, gry min, sp	7481	6.5	.30	1.950
57.0 - 64.0	as above, orp-realg	7482	7.0	.46	3.220
64.0 - 71.0	gry ser sch, minor min	7483	7.0	.24	1.680
71.0 - 78.0	as above	7484	7.0	.43	3.010
78.0 - 91.0	gry ser sch				20.150
91.0 - 97.0	30% qutz-carb; minor min; hem & water flow 97.0 (fault)	7485	6.0	.09	
97.0 - 117.0	gry ser sch				
117.0 - 135.0	m.g. grn grs sch				

Logged by JDB

Hole No. J-B712

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
135.0 - 142.0	m.g. sch grn grs w hem fract				

From	To	C.L.	Grade
36.0	78.0	42.0	.48

SHEET No. 2

HOLE No. U-8712

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8711
BEARING -
DIP AT COLLAR -90
LENGTH To be deepened (137)

LAT. 12761.5
DEP. 7662
ELEV. 5434

DATE COMPLETED
PURPOSE ASD Zone Def.

SHAFT 2
LEVEL 575
WORKING UB-4041
SECTION 1050N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 2.0	Cs				
2.0 - 4.0	60% qutz-carb, tr gry min	7472	2.0	.42	.840
4.0 - 9.0	20% qutz, py, aspy	7473	5.0	.22	1.100
9.0 - 16.0	As above	7474	7.0	.22	1.540
16.0 - 23.0	As above w less qutz; sp	7475	7.0	.08	3.480
23.0 - 30.0	qutz lenses in ser sch, minor min	7476	7.0	.05	

From	To	C. L.	Grade
2.0	16.0	14.0	.24

Logged by JDB

Hole No. U-8711

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
30.0 - 37.0	gry-buff ser sch				
37.0 - 43.0	20% qutz-carb; minor min	7604	6.0	.03	
43.0 - 48.0	As above				
48.0 - 83.0	grn-gry chl-ser sch w qutz-carb lenses				

SHEET No. Deepened

HOLE No. U-8711

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
84.0 - 91.0	grn ser sch merg w chl-ser sch				
91.0 - 103.0	grn chl-ser sch				
103.0 - 130.0	f.g. grn grs sch				
130.0 - 135.0	grn chl-ser sch				
135.0 - 137.0	f.g. grn grs sch				

SHEET No. Deeper

HOLE No. U-3711

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B710
BEARING -
DIP AT COLLAR +90
LENGTH 72.0
LAT. 12761.5
DEP. 7662
ELEV. 5442
DATE COMPLETED
PURPOSE ASD Zone Def.
SHAFT 2
LEVEL 575
WORKING B-404N
SECTION 1050N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	GOLD ASSAYS OZ./TON
0 - 1.0	Cs.				
1.0 - 8.0	20% qutz lenses; py, aspy	7468	7.0	.09	.630
8.0 - 15.0	30% qutz & as above	7469	7.0	.24	1.680
15.0 - 22.5	20% qutz & as above	7470	7.5	.16	1.200
22.5 - 29.0	gry ser sch; minor qutz & neg min	7470	6.5	.07	3.510
29.0 - 66.0	gry ser sch; qutz lenses				
66.0 - 72.0	grn chl schor grs sch				

From	To	C. L.	Grade
1.0	22.5	21.5	.16

Logged by JDB

Hole No. U-B710

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B709
BEARING -
DIP AT COLLAR +90
LENGTH 89.0
LAT. 12968
DEP. 7552.5
ELEV. 5599
DATE COMPLETED
PURPOSE No. 1 Shoot Def.
SHAFT 2
LEVEL 425
WORKING B-313C
SECTION 1175N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 1.0	Cs.				
1.0 - 17.5	dk gry tuffac sch; chty & heavily min w po, py 0 - 3.0 & 15.5 - 17.5				
17.5 - 39.0	buff gran ser sch				
39.0 - 43.5	20% barren qutz-carb lenses	7463	4.5	.22	
43.5 - 48.5	40% qutz; gry min, sp	7464	5.0	.94	4.700
48.5 - 53.5	min ser sch	7465	5.0	.08	.990
53.5 - 58.5	as above w less min	7466	5.0	.02	5.690
58.5 - 64.0	buff ser sch, neg min	7467	5.5	.03	
64.0 - 89.0	gry buff ser sch				

From	To	C.L.	Grade
39.0	48.5	9.5	.60

Logged by JDB

Hole No. U-B 709

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B708
BEARING N60W
DIP AT COLLAR 45
LENGTH 111.0

LAT. 13047.23
DEP. 7366.87 550W
ELEV. 5446

DATE COMPLETED
PURPOSE No. 1 Shoot def.

SHAFT 2
LEVEL 575
WORKING B-40SS
SECTION 1150W

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 12.5	gry-grn grs sch merg w chl-ser sch				
12.5 - 14.0	20% qutz in sil ser sch, py; tr gry min, sp	7445	1.5	.51	
14.0 - 19.0	gry ser sch, minor qutz; py	7446	5.0	.03	
19.0 - 24.0	as above				
24.0 - 52.0	gry banded ser sch, trs. 34.0 - 36.0 rs. 45.5 - 47.0	7447 7462	2.0 1.5	.11 .38	
52.0 - 63.5	grn chl-ser sch				
63.5 - 111.0	f.g. grn grs sch				

From	To	C.L.	Grade
12.5	14.0	1.5	.51
45.5	47.0	1.5	.38

Logged by JDB

Hole No. U-B708

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-E707
BEARING -
DIP AT COLLAR -90
LENGTH 133.0
LAT. 12958.5
DEP. 7568.5
ELEV. 5599
DATE COMPLETED
PURPOSE No. 1 Shoot Def.
SHAFT 2
LEVEL 575
WORKING B-313E
SECTION 1175N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 1.0	Cs.				
1.0 - 14.0	f.g. tuffac sch w qutz-carb lenses				
	t.s. 3.0 - 8.0	7449	5.0	.05	
	t.s. 24.0 - 26.0	7450	2.0	.09	
14.0 - 44.0	gry chl-ser sch, fault bx 44.0				
44.0 - 49.0	ser sch w qutz-carb lenses & py	7451	5.0	.38	1.900
49.0 - 53.5	as above	7452	4.5	.14	.630
53.5 - 55.0	90% qutz; sp, gry min; v.g.	7453	1.5	2.82	4.230
55.0 - 59.0	gry ser sch; minor min sect;	7454	4.0	.20	.800
59.0 - 72.0	gry ser sch,				7.560
72.0 - 78.0	gry ser sch, minor min sect,	7455	6.0	.04	
78.0 - 80.5	as above	7456	2.5	.03	
80.5 - 86.0	30% qutz, py, aspy, sp	7457	5.5	.38	2.090
86.0 - 92.0	gry ser sch minor qutz & min	7458	6.0	.06	.360
92.0 - 97.0	30% qutz; py, aspy, sp	7459	5.0	.36	1.800

Logged by JDB

Hole No. U-E707

N.M.P.-F3744-5

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
97.0 - 104.0	20% qutz & as above	7460	7.0	.16	1.120
104.0 - 111.0	qutz lenses in ser sch & as above	7461	7.0	.13	.910
					3.830
					6.280
111.0 - 133.0	gry ser sch, no qutz or min, hit water flow 130.0				

From	To	C.L.	Grade
44.0	59.0	15.0	.50
80.5	111.0	30.5	.20

SHEET No. 2

HOLE No. U-B707

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B 706
BEARING -
DIP AT COLLAR 490
LENGTH 78.0
LAT. 13045.5
DEP. 7370
ELEV. 5446
DATE COMPLETED
PURPOSE No. 1 Shoot Def
SHAFT 2
LEVEL 575
WORKING B-4083
SECTION 1150N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 1.0	Cs.				
1.0 - 19.0	gry-grn grs sch w tan alt fl.,				
19.0 - 35.0	as above merg into comp chl-ser sch				
35.0 - 39.0	40% qutz-carb, sparing min	7437	4.0	.19	
39.0 - 44.5	gry chl-ser sch, minor qutz & min	7438	5.5	.08	
44.5 - 52.0	80% qutz well min; v.g.	7439	7.5	(4.79 (4.87	36.225 1.540
52.0 - 59.0	gry ser sch min w py	7440	7.0	.22	37.765
59.0 - 63.0	gran ser sch, neg min	7441	4.0	.02	
63.0 - 68.0	30% qutz-carb, py	7442	5.0	.16	
68.0 - 73.0	gry ser sch; minor qutz-carb, py	7443	5.0	.05	
73.0 - 77.0	30% qutz-carb, minor min	7444	4.0	.69	
77.0 - 78.0	gry ser sch				

From	To	C.L.	Grade
44.5	59.0	14.5	2.60
73.0	77.0	4.0	.69

Logged by JDB

Hole No. U-B706

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B705
BEARING N60W
DIP AT COLLAR +80
LENGTH 76.0
LAT. 11897
DEP. 7360
ELEV. 5758
DATE COMPLETED
PURPOSE B-208 St. Ext.
SHAFT 2
LEVEL 250
WORKING B-2103
SECTION 150N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 1.0	Cs				
1.0 - 5.0	grn chl grs sch				
5.0 - 48.5	grn chl-ser sch grad w chl sch; qutz-carb lenses				
48.5 - 55.0	grn-buff ser sch,				
55.0 - 59.0	50% qutz-carb, py, aspy, gry min	7436	4.0	.34	
59.0 - 61.5	grn bx (fault)				
61.5 - 76.0	grn chl grs schor chl sch				

Logged by JDB

Hole No. U-B705

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-B704
BEARING S60E
DIP AT COLLAR +45
LENGTH 140.0
LAT. 13402.33
DEP. 7452.73
ELEV. 5444
DATE COMPLETED
PURPOSE Expl.
SHAFT 2
LEVEL 575
WORKING B-407N
SECTION 1500N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 24.0	f.g. dk grn-gry grs sch				
24.0 - 38.0	gry buff comp chl-ser sch				
38.0 - 45.0	buff ser'c banded tuffac sch				
45.0 - 48.0	black slaty sch				
48.0 - 54.5	gry & buff ser'c tuffac. sch,				
54.5 - 59.0	ser sch; py; tr gry min	7428	4.5	.26	1.540
59.0 - 64.0	As above; minor aspy	7429	5.0	.28	1.400
64.0 - 69.0	As above w some qutz-carb, tr sp	7430	5.0	.56	2.800
69.0 - 71.0	As above	7431	2.0	.25	.500
71.0 - 74.0	80% qutz-carb; sparing min	7432	3.0	.84	2.520
74.0 - 78.5	Ser sch, minor py	7433	4.5	.50	2.250
78.5 - 84.5	As above	7434	6.0	.33	1.980
84.5 - 91.5	As above	7435	7.0	.31	2.170
91.5 - 140.0	Dense buff ser sch; som bx tx				15.160

Logged by JDB

From	To	C.L.	Grade
54.5	91.5	37.0	.41

Hole No. U-B704

GIANT YELLOWKNIFE GOLD MINES LIMITED
CORE RECORD

HOLE No. U-8703
BEARING -
DIP AT COLLAR 480
LENGTH 102.0

LAT. 13471
DEP. 7433.5 704W.
ELEV. 5446

DATE COMPLETED
PURPOSE Expl.

SHAFT 2
LEVEL 575
WORKING E-402W
SECTION 1550W

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	OZ./TON
0 - 2.0	Os.				
2.0 - 3.0	black slaty sch				
3.0 - 5.0	chty buff impreg v po & py				
5.0 - 28.0	grn-gry locally banded tuffac sch,				
28.0 - 55.0	f.g. grn gro sch				
55.0 - 102.0	c.g. grn basic intr vallig fab; water flow 86.0; hem fract,				

Logged by JDP

Hole No. U-8703