GIANT YELLOWKNIFE GOLD MINES LIMITED

CORE RECORD

HOLE No. U-B435 | BEARING N60W | DIP AT COLLAR -45 | LENGTH 57.0

LAT. 12294.56 | DEP. 7272.57 | ELEV. 5906

DATE COMPLETED | PURPOSE No. 1 Shoot Pillar Definition

SHAFT 2 | LEVEL 100 | WORKING B-106N | SECTION 450N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS OZ./TON	GOLD ASSAYS OZ./TON
0.0 - 1.5	lt gry ser sch	5407	1.5	.07	
1.5 - 6.0	90% qutz & carb., aspy, gry min; sp., v.g.	5408	4.5	12.23	55.035 (22.500)
6.0 - 11.0	as above; consid fine v.g.	5409	5.0	10.00	50.000 (25.000)
11.0 - 18.0	30% qutz in banded ser sch; local min	5410	7.0	.56	3.920
18.0 - 23.0	50% qutz in ser sch; py, aspy	5411	5.0	2.94	14.700
23.0 - 29.0	50% qutz incl. 18" high grade; v.g., aspy,	5412	6.0	.45	2.700
29.0 - 35.0	60% qutz, aspy, gry min, sp. v.g.	5413	6.0	3.06	18.360
35.0 - 40.0	as above, speck v.g.	5414	5.0	1.27	6.350
40.0 - 43.0	gry ser sch w qutz lenses carrying sp	5415	3.0	.31	0.930
43.0 - 49.0	60% qutz w aspy, gry min & sp, speck v.g.	5416	6.0	2.91	17.460
49.0 - 55.0	80% qutz-carb; sparing min	5417	6.0	.35	2.100
					171.555
55.0 - 57.0	dk gry ser sch w minor qutz & neg min				(114.020)
					96.920

From	To	C.L.	Calc. Grade Uncut	Cut	Recut
1.5	55.0	53.5	3.20	2.13	1.81

Logged by J.D.B.

Hole No. U-B435