

GIANT YELLOWKNIFE GOLD MINES LIMITED

CORE RECORD

HOLE No. U-B 631SHAFT 2BEARING -----LEVEL 575DIP AT COLLAR -900LAT. 12455.5DATE COMPLETED -----DEP. 7593.0PURPOSE Deep OreWORKING B404N-DrLENGTH 221.0ELEV. 5433.0ExplorationSECTION 750N

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS	
				OZ./TON	OZ./TON
0.0 - 2.0	Casing				
2.0 - 37.0	Fg grn chl-ser sch				
37.0 - 61.0	Fg gray ser sch with local carb lenses				
61.0 - 80.0	Fg gray grn chl-ser sch in part ser sch				
80.0 - 99.0	Fg gray compact ser sch				
99.0 - 101.0	Qtz-carb lenses in ser sch spar min with py	6759	2.0	.28	
101.0 - 118.0	Fg gray compact ser sch				
116.0 - 120.0	20% qtz-carb lenses in ser sch well min with py and aspy	6760	4.0	.09	
120.0 - 124.0	40% qtz-carb lenses and as above	6761	4.0	.35	1.400
124.0 - 129.0	As above	6762	5.0	.22	1.100
129.0 - 131.0	60% qtz-carb lenses min with py aspy gray min and sph	6763	2.0	.41	.820
					<u>3.320</u>

Logged by JAHHole No. U-B 631

FOOTAGE	DESCRIPTION	SAMPLE No.	SAMPLE LENGTH	GOLD ASSAYS													
				OZ./TON	OZ./TON												
131.0 - 155.0	Fg gray ser sch with local quartz-carb lenses and traces of banding throughout																
155.0 - 214.0	Fg gray ser sch																
214.0 - 221.0	Very fg dark gray compact ser sch																
	<table><tr><td><u>From</u></td><td><u>To</u></td><td><u>C.L.</u></td><td><u>Calc. Grade</u></td></tr><tr><td>99.0</td><td>101.0</td><td>2.0</td><td>.28</td></tr><tr><td>120.0</td><td>131.0</td><td>11.0</td><td>.30</td></tr></table>	<u>From</u>	<u>To</u>	<u>C.L.</u>	<u>Calc. Grade</u>	99.0	101.0	2.0	.28	120.0	131.0	11.0	.30				
<u>From</u>	<u>To</u>	<u>C.L.</u>	<u>Calc. Grade</u>														
99.0	101.0	2.0	.28														
120.0	131.0	11.0	.30														
	<table><tr><td colspan="3"><u>Dip Test</u></td></tr><tr><td><u>At</u></td><td><u>Angle Read</u></td><td><u>Corrected Angle</u></td></tr><tr><td>150'</td><td>87°</td><td>86°</td></tr></table>	<u>Dip Test</u>			<u>At</u>	<u>Angle Read</u>	<u>Corrected Angle</u>	150'	87°	86°							
<u>Dip Test</u>																	
<u>At</u>	<u>Angle Read</u>	<u>Corrected Angle</u>															
150'	87°	86°															