

GIANT YELLOWKNIFE GOLD MINES LIMITED

CORE RECORD

HOLE No. U-8686SHAFT 2BEARING N60WLEVEL 125DIP AT COLLAR -30WORKING 8-312WLENGTH To be deepened ¹⁸⁵LAT. 13231.73

DATE COMPLETED _____

DEP. 7545.72PURPOSE Expl.ELEV. 5522SECTION 1400W

FOOTAGE	DESCRIPTION	SAMPLE NUMBER	SAMPLE LENGTH	GOLD ASSAYS	
				OZ./TON	OZ./TON
0 - 21.0	f.g. gra sch gra				
21.0 - 47.0	grs chl-ser sch				
47.0 - 51.5	40% qtz, py, aspy, sp	7313	4.5	.92	4.140
51.5 - 56.0	gry ser sch	7314	6.5	.01	.065
56.0 - 63.0	40% qtz, py, aspy, sp	7315	5.0	.30	1.500
63.0 - 68.0	As above	7316	5.0	.14	.700
68.0 - 72.0	30% and as above	7317	4.0	.24	.960
72.0 - 77.0	50% qtz & as above	7318	5.0	.21	1.050
77.0 - 81.0	30% and as above	7319	4.0	.19	.760
					<u>9.175</u>
	<u>From</u>	<u>To</u>	<u>C. L.</u>	<u>Grade</u>	
	47.0	81.0	34.0	.27	

Logged by JOBHole No. U-8686

FOOTAGE	DESCRIPTION	SAMPLE NO.	SAMPLE LENGTH	GOLD ASSAYS	
				OZ./TON	OZ./TON
82.0 - 140.0	gry chl-scr sch, quartz-carb lenses				
140.0 - 157.0	finely banded scr sch (tuffac) silic 150.0 - 156.0				
157.0 - 169.5	chty sch (tuff) heavily impreg w py				
169.5 - 173.5	finely banded tuffac sch.				
173.5 - 185.0	f.g. grs sch				