

**MikroPul** LIMITED



**HOSOKAWA MICRON INTERNATIONAL INC.**

1940 STEELES AVENUE EAST, BRAMALEA, ONTARIO L6T 1A7

TEL (416) 791-3553  
FAX (416) 791-4839  
TELEX: 069-7572

FACSIMILE COVER SHEET

From: MIKROPUL LIMITED Date: AUGUST 05, 1988  
Sent By: G.J. (Dave) DAVIES  
Sent To: KENT MORTON - GIANT YELLOW KNIFE MINES  
No. of Pages (including this cover sheet) 3

Please advise if illegible or if received by the wrong company.

FAX: (403) 873-2980

Comments & Special Instructions:

Subject: MikroPul Proposal: S-8119

Per your request of July 29, 1988, please see the attached budget proposal.

Yours very truly,  
MIKROPUL LIMITED

A handwritten signature in dark ink, appearing to read "G.J. Davies", is written over the typed name.

G.J. (Dave) Davies,  
General Sales Manager.

Enclosures.

/jv

# MikroPul LIMITED

Giant Yellowknife Mines  
August 05, 1988

Page 2  
Our Proposal: S-8119

## MIKROPULSAIRE DATA SHEET

CUSTOMER: GIANT YELLOW KNIFE MINES  
PROPOSAL NO: S-8119  
MODEL NO: H.208-10-20  
CUSTOMER EQUIP. NO: -----  
SERIAL NO: -----  
APPLICATION: VENTING DRYER  
MATERIAL HANDLED: ARSENIC TRIOXIDE  
GAS VOLUME: 10,000 A.C.F.M.  
GAS TEMPERATURE: 500 °C.  
INLET LOADING: 15 GR/ACF (15T/DAY)  
PARTICLE SIZE: UNKNOWN  
LOCATION: INDOORS

## EQUIPMENT SPECIFICATION

REF. DRG. NO: D-23987  
CLOTH AREA: 2450 FT.<sup>2</sup>  
FILTER MATERIAL: NEXTEL  
FILTER RATIO: 4 FPM (BY CUSTOMER)  
HOUSING: 12 GA. ASTM A515  
PLENUM: 12 GA. ASTM A515  
HOPPER: 12 GA. ASTM A515  
FILTER ACCESS: CLEAN AIR PLENUM  
VENTURIS: S.S.  
RETAINERS: ASTM A515 PERFORATED TUBES  
DIAPHRAGM VALVES: GOYEN  
SOLENOID VALVES: GOYEN  
TIMER: MIKROPUL  
SUPPORT LEGS: INCLUDED  
SERVICE PLATFORM: BY OTHERS  
ACCESS LADDER: BY OTHERS  
PAINTING: PRIME ONLY  
INSULATION: BY OTHERS  
EXPLOSION VENTS: NO  
PRESSURE GAUGE: MAGNEHELIC GAUGE  
SCREW CONVEYOR: NO  
DISCHARGE VALVE: BY OTHERS  
ADDIT. FEATURES: -----


BUDGET PRICE ..... \$220,000.00

F.O.B.: POINT OF MANUFACTURE.  
SHIPMENT: TEN (10) TO TWELVE (12) WEEKS  
AFTER DRAWING APPROVAL.



**NOTES-**

1. ELECTRICAL: TOTALLY ENCLOSED CEAA 12 (OPTIONAL) 1-CEA  
EXPLOSION PROOF CEAA 7 OR 9 (OPTIONAL)
2. POWER REQUIREMENTS: SOLENOID 110-1-60  
TIMER 110-1-60  
AIRLOCK 575-3-60
3. TIMER, MANOMETER, BAGS, RETAINERS & BLOWTUBES<sup>2</sup>  
FOR INSTALLATION BY OTHERS<sup>1</sup>
4. COMPRESSED AIR SUPPLY TO BE CLEAN AND FREE OF OIL  
AND WATER AT ALL TIMES.
5. PAINT: ONE COAT OF GREEN PRIMER 1231 EXTERIOR AND  
INTERIOR  
OPTIONAL EXTRA-FINISH COAT EXTERIOR ONLY  
GREEN HAMMERTONE FINISH E-983.

— 1000	REPEL		<b>DUCON-MIKROPULIN</b>
— 1.7	max. 20		
—	HTS	<b>GENERAL RANGE OF</b> <b>7" TM SERIES 20 TO 200</b> <b>HOT LGI FILTER BAGS</b>	
—			<b>D-23987</b>