Royal Oak Mines Inc.

SHAFT: B | HEADING: 908 HDB | HOLE COMPLETED: | DRILLER: | PLOTTED ON: # 34 | PAGE: ___ OF ___
LEVEL: 950 | AREA: 1100 | DATE LOGGED: Mar 7/92 | LOGGED BY: N Nevada | SCALE: | INPUT:

DRILL HOLE: 23137 | NORTHING: 1300 N | EASTING: 144.5 W | ELEVATION: 5063.5 | LENGTH: 136 | CAT:

DIST	AZIM	DIP	DIST	AZIM	DIP	DIST	AZIM	DIP	DIST	AZIM	DIP	DIST	AZIM	DIP
0	S60E	+50	15		51.5	100		51.5						

DIST	Id	ROCK DESCRIPTION Nam	Col	Grs	Com	Text	Alt	STRUCT. B/S S	A1	J/F F	A2	MINERALS % Gangue Qtz	Car	% METALLIC Gs	Py	Gs	Asp	Au ASSAY DATA Dist	Smpl #	Wdth	Assy 1	Assy 2	COMMENTS 1	COMMENTS 2
6.5		GST	GR	FM	M	Hom	WAL																	
41.5		MF	GR	FG	M	Hom																		
58.0		CLS	TGR	FG	(S)		BAF					3	2	FG	TR		[illegible]	47.0	73716		.012		+10% BAF Gr 6"	+047
												5	2		TR			53.0	17		.014			
												5	2		TR			58.0	18		.016			
[illegible]		CLS	TGR	FG	S	COT	SER					20	10		TR		TR	63.0	19		.013		(wispy sericite flecks)	Qtz [illegible]
												20	5		TR			68.0	20		.014			
								S60				10	2		TR			73.0	21		.012			
												8	2					78.0	22		.012			
												8	2					83.0	23		.011			
												8	2					88.0	24		.011			
												8	2					93.0	25		.012			
111.5		TAT	TGY	FG	S	COT	QCU					5	2	VF	TR			98.0	26		.016			
															TR			103.0	27		.014			
															TR	VF	TR	107.0	28		.013			
															TR			111.5	29		.013			
115.0		SES	TGY	FG	S	COT						10	5	MG	1.5	FG	0.5	115.0	30	3.5	.288		.288/3.5	
136.0		TAT	TGY	FG	S	COT						4	2					121.0	31		.013		Gr 1'	
												4	2					126.0	32		.034			
B.T.												4	2					131.0	33		.017			
EOH												6	2	FG	0.5	VF	TR	136.0	34		.021			