Royal Oak Mines Inc.

SHAFT: B | HEADING: 9-14 NDR. | HOLE COMPLETED: | DRILLER: | PLOTTED ON: 2WHT/GRN #34 | PAGE: 1 OF 1

LEVEL: 1100 | AREA: 1100 | DATE LOGGED: Feb 22/92 | LOGGED BY: N Nendsa | SCALE: | INPUT:

DRILL HOLE	NORTHING	EASTING	ELEVATION	LENGTH	CAT
23084A	1675N	004 E	5056.5	114'	

DIST	AZIM	DIP	DIST	AZIM	DIP	DIST	AZIM	DIP	DIST	AZIM	DIP	DIST	AZIM	DIP
0	N60W	+28	15'		+30½	90'		+28						

DIST	Id	ROCK DESCRIPTION Nam	Col	Grs	Com	Text	Alt	STRUCT. B/S S	A1	J/F F	A2	MINERALS % Gangue Qtz	Car	% METALLIC Gs	Py	Gs	Asp	Au ASSAY DATA Dist	Smpl #	Wdth	Assy 1	Assy 2	COMMENTS 1	COMMENTS 2
6.5		CLS	GY	FG	S	COT						3						6.5	73567		.022			
13.5		SCS	TGY	FG	S	COT						10		FG	1.0	FG	TR	13.5	68	7.0	.653		.596/20	
22.5		QC	BK	FG	(S)	COT						60			0.5		0.1	18.0	69	4.5	.544			
												65			0.5		TR	22.5	70	4.5	.935			
		CLS	TGR	FG	S	COT	SER					7			0.3			26.5	71	4.0	[illegible]			
												7			0.2			30.0	72		[illegible]			
		CLS	GY	FG	S	CRA	QCV					4	2		TR			35.0	73		.034		[illegible]	
												4	2		TR			41.0	74		[illegible]		[illegible]	
74.0		CGT	GR	FG	S	COT						4		FM	TR	FG	TR	46.0	75	5	.237		possible pillow selvages and interflow bands	
																		51.0	76		.071			
																		56.0	77		.016		blotches of	medium gr py
								S	60									61.0	78		.019			
																		66.0	79		[illegible]			
																		70.0	80		.028			
																		74.0	81		[illegible]			
		DIA	BK	FG	(M)													76.0	82		.018			
86.0		CLS	GG	FG	(S)	COT						7		FG	0.5			81.0	83		.116		dyke "alteration"	
												10			1			86.0	84	5.0	.461		G: 1' to 82 some	hematite alt.
89.0		CLS	GR	FG	(S)	COT						3						89.0	85		.018			
114.0		DIA	GR	MG	M	HOM																		